

Sherwin Williams - Pro-Mar Alkyd Semi-Gloss Enamel

Series
MATERIAL SAFETY DATA SHEET
 FOR COATINGS, RESINS AND RELATED MATERIALS
 (Approved by U.S. Department of Labor 'Essentially Similar' to form OSHA-20)

MANUFACTURER'S NAME: SHERWIN-WILLIAMS COMPANY
 61 Prospect Avenue N.W.
 Cleveland, Ohio 44115
 DATE OF PREPARATION: 4-Mar-86
 EMERGENCY TELEPHONE NO.: (216) 566-2917
 INFORMATION TELEPHONE NO.: (216) 566-2902

Section I -- PRODUCT IDENTIFICATION

DUCT NAME: PRO-MAR® Alkyd Semi-Gloss Enamel
 DUCT NUMBERS AND COLORS:
 134 W 100 Brilliant White
 134 W 101 Pastel Base
 134 W 102 Midtone Base
 134 W 103 Deepstone Base
 134 W 107 Antique White
 134 W 108 Dover White
 --- Including Non-Lead Tinted Colors ---
 DUCT CLASS: Alkyd Enamel

Section II -- HAZARDOUS INGREDIENTS

AS SH.	INGREDIENT	% by WEIGHT	ACGIH-TLV	OSHA-PEL	UNITS	T.P.
2-88-7	Mineral Spirits 140-Flash.	35-40	100	500	PPM	0.5

Section III -- PHYSICAL DATA

EVAPORATION RATE -- Slower than Ether
 VAPOR DENSITY -- Heavier than Air
 LING RANGE (F) 355 - 416
 % VOLATILE VOLUME 55-62
 WT/GAL 9.0-10.5

Section IV -- FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: Combustible, Flash above 99 and below 200 F
 FLASH POINT: 105 F PHCC
 LEL: 0.9
 INHIBITING MEDIA: Carbon Dioxide, Dry Chemical, Foam
 USUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to composition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.
 SPECIAL FIRE FIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Continued on page 2

B34 Series PRO-MAR® Alkyd Semi-Gloss Enamel page 2

Section V -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE -- See Section II
 EFFECTS OF OVEREXPOSURE:
 ACUTE: In a confined area vapors in high concentration are anesthetic. Overexposure may result in lightheadedness and staggering gait.
 CHRONIC: Irritant to skin and upper respiratory system. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.
 EMERGENCY AND FIRST AID PROCEDURES:
 IF INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
 IF ON SKIN: Wash affected area thoroughly with soap and water.
 IF IN EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

Section VI -- REACTIVITY DATA

STABILITY -- Stable
 HAZARDOUS DECOMPOSITION PRODUCTS: By fire: Carbon Dioxide, Carbon Monoxide
 HAZARDOUS POLYMERIZATION -- Will Not Occur

Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
 Remove all sources of ignition. Ventilate and remove with inert absorbent.
 WASTE DISPOSAL METHOD:
 Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.
 Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section VIII -- PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE:
 Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.
 VENTILATION:
 Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.
 RESPIRATORY PROTECTION:
 If personal exposure cannot be controlled below applicable limits by ventilation, wear respiratory device approved by NIOSH/MSHA for protection against materials in Section II.
 PROTECTIVE GLOVES:
 Wear gloves which are recommended by glove supplier for protection against materials in Section II.
 EYE PROTECTION:
 Wear safety spectacles with unperforated sideshields.

Continued on page 3

B34 Series PRO-MAR® Alkyd Semi-Gloss Enamel page 3

Section IX -- PRECAUTIONS

DOL STORAGE CATEGORY -- 2
 PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:
 Contents are COMBUSTIBLE. Keep away from heat and open flame.
 Consult NFPA Code. Use approved Bonding and Grounding procedures.
 Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.
 OTHER PRECAUTIONS:
 This coating contains materials classified as nuisance particulates, for example titanium dioxide, calcium carbonate, etc. (see ACGIH TLV List, Preface and Appendix D), which may be present at hazardous levels only during sanding or abrading of the dried film.
 Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CFR 1910.1200(g)(4), for similar complex mixtures.
 The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.