

MATERIAL SAFETY 3M
DATA SHEET 3M Center
St. Paul, Minnesota
55144-1000
1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.
All rights reserved. Copying and/or downloading of this
information for the purpose of properly utilizing 3M products
is allowed provided that:

- 1) the information is copied in full with no changes unless
prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise
distributed with the intention of earning a profit thereon.

DIVISION: CONSTRUCTION AND HOME IMPROVEMENT PRODS

TRADE NAME:

3M Brand Adhesive, & Wax Remover, Catalog Nos. 3607 and 3622

ID NUMBER/U.P.C.:

70-0704-1896-0	00-51131-03607-9	70-0705-3791-8	00-51131-03607-9
70-0706-3792-4	00-51131-03607-9	70-0706-4402-9	00-51131-03607-9
70-0709-1826-6	00-51131-03622-2	70-0709-7632-2	- - -

ISSUED: March 01, 2001

SUPERSEDES: January 08, 2001

DOCUMENT: 05-3853-8

1. INGREDIENT	C.A.S. NO.	PERCENT
VM & P NAPHTHA.....	8032-32-4	45 - 55
XYLENE.....	1330-20-7	35 - 45
ETHYLBENZENE.....	100-41-4	7 - 13

This product contains the following toxic chemical or chemicals subject to
the reporting requirements of Section 313 of Title III of the Emergency
Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:

XYLENE

ETHYLBENZENE

2. PHYSICAL DATA

BOILING POINT:..... 245 F
VAPOR PRESSURE:..... 30 mmHg
@ 100 F
VAPOR DENSITY:..... > 3 Air=1
EVAPORATION RATE:..... ca. 7.1 Ether=1
SOLUBILITY IN WATER:..... < 0.1 %
SPECIFIC GRAVITY:..... ca. 0.82 Water=1
PERCENT VOLATILE:..... 100 %
pH:..... N/A
VISCOSITY:..... Thin liquid.
MELTING POINT:..... N/D

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

2. PHYSICAL DATA (continued)

APPEARANCE AND ODOR:

Liquid, colorless, aromatic odor

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:..... ca. 52 F

FLAMMABLE LIMITS - LEL:..... 0.9 %

FLAMMABLE LIMITS - UEL:..... 6.0 %

AUTOIGNITION TEMPERATURE:..... N/D

EXTINGUISHING MEDIA:

Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Flammable liquid.

NFPA HAZARD CODES: HEALTH: 2 FIRE: 3 REACTIVITY: 0

UNUSUAL REACTION HAZARD: none

OSHA FIRE HAZARD CLASS: Class IB Flammable Liquid

4. REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:

Strong oxidizing agents.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Thermal decomposition products are carbon monoxide, carbon dioxide and smoke particles when subjected to excessive heat and flame.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Ventilate area. Extinguish all ignition sources. Contain spill. Cover with absorbent material. Collect using non-sparking tools. Place in a U.S. DOT-approved container.

RECOMMENDED DISPOSAL:

Incinerate in a permitted hazardous waste incinerator in the presence of a combustible material. Incinerate large quantities in a permitted hazardous waste incinerator.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: 100 % per CARB VOC def.; 816 g/l per SCAQMD.
VOC Less H2O & Exempt Solvents: 816 gms/liter South Coast Air Quality Mgmt Dist Method.

Since regulations vary, consult applicable regulations or authorities before disposal. U.S. EPA Hazardous Waste Number = D001 (Ignitable)

EPCRA HAZARD CLASS:

FIRE HAZARD: Yes PRESSURE: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

6. SUGGESTED FIRST AID

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:

Wash affected area with soap and water.

INHALATION:

If signs/symptoms occur, remove person to fresh air. If signs/symptoms continue, call a physician.

IF SWALLOWED:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:

Avoid eye contact. Avoid eye contact with vapor, spray, or mist. The following should be worn alone or in combination, as appropriate, to prevent eye contact: Wear unvented goggles during operations in which exposure is likely.

SKIN PROTECTION:

Avoid skin contact. Wear appropriate gloves when handling this material.

RECOMMENDED VENTILATION:

Do not use in a confined area or areas with little or no air movement. Use with appropriate local exhaust ventilation. Use in a well-ventilated area. Provide sufficient ventilation to maintain emissions below recommended exposure limits. If exhaust ventilation is not adequate, use appropriate respiratory protection.

RESPIRATORY PROTECTION:

Avoid breathing of vapors, mists or spray. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: half-mask organic vapor respirator, full-face organic vapor respirator.

PREVENTION OF ACCIDENTAL INGESTION:

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Wash hands after handling and before eating. Do not ingest.

RECOMMENDED STORAGE:

Store in a cool place. Store away from flammable and combustible materials. Store away from heat. Store out of direct sunlight. Keep container closed when not in use. Keep container in well-ventilated area. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Keep container tightly closed. Flammable liquid and vapor. Keep away from heat, sparks, open flame, and other sources of ignition. Prevent all sources of ignition. Vapors may ignite explosively.

HMIS HAZARD RATINGS: HEALTH: 2 FLAMMABILITY: 3 REACTIVITY: 0
PERSONAL PROTECTION: B

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
VM & P NAPHTHA.....	100	PPM	TWA	CMRG	
VM & P NAPHTHA.....	300	PPM	TWA	ACGIH	
VM & P NAPHTHA.....	300	PPM	TWA	OSHA	
XYLENE.....	100	PPM	TWA	ACGIH	

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

EXPOSURE LIMITS (continued)

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
XYLENE.....	150	PPM	STEL	ACGIH	
XYLENE.....	100	PPM	TWA	OSHA	
XYLENE.....	150	PPM	STEL	OSHA	
ETHYLBENZENE.....	100	PPM	TWA	ACGIH	
ETHYLBENZENE.....	125	PPM	STEL	ACGIH	
ETHYLBENZENE.....	100	PPM	TWA	OSHA	
ETHYLBENZENE.....	125	PPM	STEL	OSHA	

* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Exposure Guidelines
- OSHA: Occupational Safety and Health Administration

8. HEALTH HAZARD DATA

EYE CONTACT:

Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, and hazy vision.

SKIN CONTACT:

Mild Skin Irritation: signs/symptoms can include redness, swelling, and itching.

INHALATION:

May be harmful or fatal if inhaled.

Intentional concentration and inhalation may be harmful or fatal.

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

Single overexposure, above recommended guidelines, may cause:

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Prolonged or repeated overexposure, above recommended guidelines, may cause:

Nervous System Effects: signs/symptoms can include emotional changes, lack of coordination, tremors and sensory loss.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

8. HEALTH HAZARD DATA (continued)

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD, THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Prolonged or repeated overexposure, above recommended guidelines, may cause:

Kidney Effects: signs/symptoms can include reduced urine volume, blood in urine and back pain.

Liver Effects: signs/symptoms can include yellow skin(jaundice) and tenderness of upper abdomen.

IF SWALLOWED:

Harmful or fatal if swallowed.

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue, blurred vision, slurred speech, giddiness, tremors and convulsions.

Aspiration Pneumonitis: signs/symptoms can include coughing, difficulty breathing, wheezing, coughing up blood and pneumonia, which can be fatal.

CANCER:

WARNING: Contains a chemical which can cause cancer. (100-41-4) (IARC possible human carcinogen 2B)

SECTION CHANGE DATES

HEADING	SECTION CHANGED SINCE	January 08, 2001	ISSUE
---------	-----------------------	------------------	-------

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.