

MAGNESIUM METAL

Material Safety Data Sheet

Mallinckrodt Chemical Inc.

P.O. Box 800

Paris, Kentucky 40362

Emergency Telephone Number

314-539-1600

Effective Date: 07-17-91 Supersedes 08-09-85

PRODUCT IDENTIFICATION:

Synonyms: Magnesium ribbon, magnesium powder, magnesium clipping

Formula CAS No.: 7439-95-4

Molecular Weight: 24.30

Hazardous Ingredients: Magnesium metal

Chemical Formula: Mg

PRECAUTIONARY MEASURES

DANGER! FLAMMABLE SOLID. MAY CAUSE IRRITATION.Avoid contact with eyes, skin and clothing.
Keep away from heat, sparks and flame.
Wash thoroughly after handling.

EMERGENCY FIRST AID

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes.
SEE SECTION 5.

Physical Data

SECTION 1

Appearance: Silver solid.

Odor: Odorless.

Solubility: Insoluble in water.

Boiling Point: 1100 C (2030 F)

Vapor Density (Air=1): No information found.

Melting Point: 649 C (1200 F)

Vapor Pressure (mm Hg): No information found.

Specific Gravity: 1.74

Evaporation Rate: No information found.

NFPA Ratings: Health: 0 Flammability: 1 Reactivity: 1

Fire and Explosion

SECTION 2

Information-----
Fire:

When heated in air to a temperature near its melting point, magnesium may ignite and burn. Dangerous in the form of dust or flakes, and when exposed to flame or by violent chemical reaction with oxidizing agents.

Explosion:

Fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Minimum explosible concentration 0.030 grams/liter. Water used on molten magnesium will produce hydrogen gas and may cause an explosion.

Fire Extinguishing Media: Melting flux, dry sand, or metal extinguishing powders. Do not use water. Use of water on molten magnesium will produce hydrogen gas and may cause an explosion.

Special Information: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

Reactivity Data

SECTION 3

Stability:

Stable under ordinary conditions of use and storage. Slowly oxidizes in moist air.

Hazardous Decomposition
Products:

Toxic gases and vapors may be released if involved in a fire.

Hazardous Polymerization:

This substance does not polymerize.

Incompatibilities:

Magnesium reacts dangerously with many substances, including oxides, carbonates, cyanides, chlorinated hydrocarbons, sulfates, acids, and other metals. Please refer to the NFPA publication "Fire Protection Guide on Hazardous Materials" most recent edition for details.
Reacts with acids to form hydrogen gas.

Leak/Spill Disposal Information

SECTION 4

Fire Hazard. Remove all sources of ignition and incompatible materials. Spills: Sweep up and containerize for reclamation, salvage, or disposal in a method that does not generate dust. Disposal: Whatever cannot be saved for reclamation or salvage may be disposed in an approved waste disposal facility.

Ensure compliance with local, state and federal regulations.

Health Hazard Information

SECTION 5

A. Exposure/Health Effects

Inhalation: Inhalation of dusts may irritate the respiratory tract and may cause metal fume fever. Symptoms may include coughing, chest pain, fever, and leukocytosis.

Ingestion: May cause abdominal pain and diarrhea.

Skin Contact: Particles embedded in the skin may cause eruptions. Molten magnesium may cause serious skin burns.

Eye Contact: May cause irritation.

Chronic Exposure: No information found.

Aggravation of
Pre-existing Conditions: Existing wounds contaminated with magnesium are very slow to heal.

B. FIRST AID

Inhalation: Remove to fresh air. Get medical attention for any breathing difficulty.

Ingestion: Give several glasses of water to drink to dilute. If large amounts were swallowed, get medical advice.

Skin Exposure: Remove any contaminated clothing. Wash skin with soap or mild detergent and water for at least 15 minutes. Get medical attention if irritation develops or persists.

Eye Exposure: Wash eyes with plenty of water for at least 15 minutes. If irritation develops, get medical attention.

C. TOXICITY (RTECS, 1986)

No LD50/LC50 information found relating to normal routes of occupational exposure.

Occupational Control Measures SECTION 6

Airborne Exposure Limits: None established.

Ventilation System: A local exhaust system which captures the contaminant at its source is recommended to prevent dispersion of the contaminant into the workroom air.

Personal Respirators (NIOSH Approved) For conditions of use where exposure to the dust is apparent, a dust/mist respirator may be worn. For emergencies, a self-contained breathing apparatus may be necessary.

Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection: Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work area.

Storage and Special Information SECTION 7

Keep in tightly closed container. Store in a cool, dry, ventilated area. Protect against physical damage. Store finely divided chips or shavings in detached fire-resistant building, protected from moisture and away from chlorine, bromine, iodine, acids, and all possible sources of ignition. Heavier sections may be stored in the open.

Mallinckrodt provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT MAKES NO REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR TO THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

MAGME

Addendum to Material Safety Data Sheet

REGULATORY STATUS

Hazard Categories for SARA
Section 311/312 Reporting

MAGME
MAGNESIUM METAL