

ITEM: 4CH78 - Marking Paint Fluorescent Green 15

PICK_REQ: 1061383294

MATERIAL SAFETY DATA SHEET (MSDS)

MSDS: B0841

This MSDS should be attached or kept with the respective product with which it is associated.

#####

INCLUDED LIVER AND CARDIAC ABNORMALITIES.

REMARKS: 4CH78 - Marking Paint Fluorescent Green 15
 SKIN CONTACT, SKIN ABSORPTION, INHALATION, EYE CONTACT

MATERIAL SAFETY DATA SHEET

SECTION 4 - FIRST AID MEASURES

24 H

FIRST AID - EYE CONTACT:
 HOLD EYELIDS APART AND FLUSH WITH WATER FOR AT LEAST 15 MINUTES.
 GET MEDICAL ATTENTION.

WWW.RUSTOLEUM.COM

FIRST AID - SKIN CONTACT:
 WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

FIRST AID - INHALATION:

IF YOU EXPERIENCE DIFFICULTY BREATHING, GET MEDICAL ASSISTANCE IMMEDIATELY. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY.

REVISION DATE: 06/21/2005

FIRST AID - INGESTION:

ASPIRATION HAZARD: IDENTIFICATION NUMBER: V2333838, V2355838, V2358838
 DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION.

SUPPLIER:

RUST-OLEUM CORPORATION

11 HAWTHORN PARKWAY SECTION 5 - FIRE FIGHTING MEASURES

VERN

FLASH POINT (SETAFLASH): -156 F

VAPOR PRESSURE: 0.9 mmHg

UPPER EXPLOSIVE LIMIT: 11.2

RUST-OLEUM CORPORATION

11 HAWTHORN PARKWAY

WILMINGTON, DE 19806 DRY CHEMICAL, FOAM, WATER FOG

USA

UNUSUAL FIRE AND EXPLOSION HAZARDS:

PERFORATION OF THE PRESSURIZED CONTAINER MAY OCCUR WHEN EXPOSED TO EXTREME HEAT. WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY CLOSED. FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME.

CHEM

SPECIAL FIREFIGHTING PROCEDURES:

EVACUATE AREA AND FIGHT FIRE FROM UPWIND. RUST-OLEUM GAS 68476-86-8 30.0

ALIPHATIC PETROLEUM

64742-89-8 15.0

400 PPM

N.E.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

DO NOT BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: 150 PPM

REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE POLYMER (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE CONTAINERS SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST.

NAPH

ETHYLBENZENE

100-41-4

1.0

100 PPM

125 PPM

SECTION 7 - HANDLING AND STORAGE

CHEM

HANDLING:

AVOID BREATHING VAPORS. WORK IN WELL-VENTILATED AREA. WASH HANDS BEFORE EATING. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. WASH THOROUGHLY AFTER HANDLING.

ALIP

DISTILL

STORAGE:

200 PPM

300 PPM

DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F.

NAPHTHA

ETHYLBENZENE

100 PPM

N.E.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS/SECTION 3 - HAZARDS IDENTIFICATION

USE EXPLOSION-PROOF VENTILATION EQUIPMENT. USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE EMERGEN LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION.

SYSTEM CA

EXPLOSION. EXTREME

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN EFFECTS ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN PROLONGED CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

EFFECTS OF OVEREXPOSURE - INHALATION:

IRITATION OF THE EYES, NOSE, THROAT, AND LUNGS. PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR ANY OTHER CIRCUMSTANCES WHERE AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION.

EFFECTS O

ASPIRATION HAZARD IF SWALLOWED; CAN ENTER LUNGS AND CAUSE DAMAGE. SU

MAY BE IRRITATED IF SWALLOWED.

USE IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THIS MATERIAL THROUGH THE SKIN. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION.

IARC LI

CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A L

EYES, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION)

USE SAFETY EYEWEAR/OCULAR PROTECTION TO PREVENT EYE IRRITATION

OVEREXPOSURE TO VAPORS IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER

REFER TO SAFETY SUPERVISOR OR MANUFACTURER FOR FURTHER INFORMATION

REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION.

REPROD

INCLUDED LIVER,

EYES, AND LUNGS IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER

WASH THOROUGHLY WITH SOAP AND WATER. EYES, EARS, AND SKIN SHOULD BE WASHED

EFFECTS IN

LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES: NONE KNOWN

HOSLINGATEENREGULATIONS15AS FOLLOWS

MAKORHESSTYSHREKNOHAN AIR

THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT.

ODOR: S

CHEMICAL NAME: ND CAS NUMBER

REFERENCE: LIQUID 7732-18-5

EMACROPTONBONEE FASTER THAN EITHER

ENNEBYLVANTIANRIGHT-SOHNOW:

THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%.

FREEZE

SHEETEAC NAMEITY: 0.8700

CAS NUMBER

WATER PRESSURE: ND

7732-18-5

CHLORINE CARBONATE

1317-65-3

BRESUMASUSATE: LIQUID

7727-43-7

ISEMSECAWONOREDORANBERREVEADIGNEBEND) MIXTURE

POLYMER ANCHORED ORANGE DYE DISPERSION MIXTURE

SECTION 10

MODIFIED ALKYD

PROPRIETARY

CONDITIONS TO AVOID:

ENDIPORSEHAPORSTABONE6520 DEG. F. AVOID ALL POSSIBLE SOURCES OF IGNITION.

WARNING!

THIS PRODUCT CONTAINS ONE OR MORE CHEMICAL(S) KNOWN BY THE STATE OF CALIFORNIA TO CAUSE CANCER.

INCOMPAT

WARNINGUS DECOMPOSITION:

THIS PRODUCT CONTAINS A DECOMPOSITION PRODUCT WHICH IS A CAUSE OF IRRITATING FUMES. CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

OPEN FLA

ENTERUSONOLYNEHIZATIONS:WALEFODDOESOR UNDER NORMAL CONDITIONS.

CANADIAN WHMIS CLASS: AB5, D2A, D2B
THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

SECTION

CANADIAN WHMIS CLASS: AB5, D2A, D2B

PRODUCT LD50: ND

PRODUCT LC50: ND

SECTION 16 - OTHER INFORMATION

CHEM

HMS RATINGS:

HEALTH: LIQUEFIED PETROLEUM GAS N.D.

N.D.

FLAMMABILITY: 4

REACTIVITY: 0ALIPHATIC PETROLEUM

N.D.

N.D

PERSONAL PROTECTION: DISTILLATES

VOLUME ORGANIC COMPOUNDS, DG/L: 540 MAX

N.D.

REASON FOR CHANGES: N.D.

N.D.

LEGEND: DYE DISPERSION

N.A. - NOT APPLICABLE

N.E. - NOT ESTABLISHED

>25 ML/KG (ORAL, RAT) >700 PPM (

N.D. - NOT DETERMINED

ETHYLBENZENE

3500 MG/KG (ORAL, RAT) N.D

THE INFORMATION CONTAINED ON THIS MSDS HAS BEEN CHECKED AND SHOULD BE ACCURATE. HOWEVER, IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

ECOLOGICAL INFORMATION: PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

SECTION 13 - DISPOSAL INFORMATION

DISPOSAL INFORMATION:

DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER STORM DRAINS OR SEWER SYSTEMS.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: AEROSOL

PACKING GROUP:

DOT TECHNICAL NAME:

HAZARD SUBCLASS:

DOT HAZARD CLASS: 2.1

RESP. GUIDE PAGE: 126

DOT UN/NA NUMBER: UN1950

SECTION 15 - REGULATORY INFORMATION

CERCLA - SARA HAZARD CATEGORY:

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA "HAZARD CATEGORIES" PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES: IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

SARA SECTION 313:

LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME CAS NUMBER

TOLUENE 108-88-3

ETHYLBENZENE 100-41-4

TOXIC SUBSTANCES CONTROL ACT:

ITEM: 5H911 - Marking Paint Caution Blue 15 Oz

PICK REQ: 1061383294

MATERIAL SAFETY DATA SHEET (MSDS)

MSDS: A9371

This MSDS should be attached or kept with the respective product with which it is associated.

#####

MAY BE HARMFUL IF SWALLOWED.

Associated GHS Pictogram: CHRONIC HAZARD: Paint Caution Blue 15 Oz
IARC LISTS ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B).

MATERIAL SAFETY DATA SHEET (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO XYLENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER-OL ABNORMALITIES, KIDNEY, LUNG, SPLEEN, EYE AND BLOOD DAMAGE AS WELL AS WWW. REPRODUCTIVE DISORDERS. EFFECTS IN HUMANS, DUE TO CHRONIC OVEREXPOSURE, HAVE INCLUDED LIVER, CARDIAC ABNORMALITIES AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO TOLUENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG AND SPLEEN DAMAGE. EFFECTS IN HUMANS HAVE INCLUDED LIVER AND CARDIAC ABNORMALITIES.

RUST-OLEUM HIGH PERFORMANCE INDUSTRIA

PRIMARY ROUTE(S) OF ENTRY:

SKIN CONTACT, SKIN ABSORPTION, INHALATION, EYE CONTACT

IDENTIFICATION NUMBER:

V2324838, V2344838, V2345838, V2392838, V2363838

SECTION 4 - FIRST AID MEASURES

PROD

FIRST AID - EYE CONTACT:

HOLD EYELIDS APART AND FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

RUST-

11 HAWTHORN PARKWAY

PERSONAL PROTECTION:

WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

MANUFACTURER:

RUST-OLEUM CORPORATION:
IF YOU EXPERIENCE DIFFICULTY BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY. VERNON USA

PREPARED RECOMMENDATION:**ASPIRATION HAZARD:**

DO NOT INDUCE VOMITING OR INDUCE EMESIS BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION.

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME SECTION NUMBER FIGHTING MEASURES % LESS THAN**FLASH POINT:** -156 F (SETAFLASH) 67-64-1 30.0**LOWER EXPLOSIVE LIMIT:** 0.7 % 68476-86-8 30.0**UPPER EXPLOSIVE LIMIT:** 12.8 %

ALIPHATIC HYDROCARBON 64742-89-8

EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, WATER FOG

TITANIUM DIOXIDE

UNUSUAL FIRE AND EXPLOSION HAZARDS:

WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR! NAP
PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY CLOSED. MAGNESIUM

EXTINGUISHING PROCEDURES: 100-41-4 5.0

EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE.

PIGMENT YELLOW 73

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CHEM

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR LEAKED: CEILING
CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE ACET WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED LIQUID CONTAINERS. GAS

ALIPHATIC HYDROCARBON 300 PPM N.E. 300 PPM N.E.

SECTION 7 - HANDLING AND STORAGE

TITA

HANDLING:

WASH HANDS BEFORE EATING. WASH THOROUGHLY AFTER HANDLING. USE ONLY IN A WELL-VENTILATED AREA. AVOID BREATHING VAPOR OR MIST. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES.

XYLENE 100 PPM 150 PPM 100 PPM N.E.

STORAGE:

DO NOT STORE ABOVE 120 DEG. F. STORE IN SMALL QUANTITIES IN BUILDINGS/MEANS OF TRANSPORTATION AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F. PIGMENT

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

USE PROCESS ENCLOSURES/CONTAINERS WITH PRESSURIZATION POSITIVE VENTILATION OR EXHAUST CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. REMOVABLE EXPLOSION-PROOF VENTILATION EQUIPMENT. PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION.

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT PROLONGED RESPIRATOR USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN SLIGHT ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS. HIGH

LUNGS. AVOID BREATHING VAPORS OR MISTS. HIGH GAS, VAPOR, MIST OR DUST
DO NOT STORE ABOVE 120 DEG. F. STORE IN SMALL QUANTITIES IN BUILDINGS/MEANS OF TRANSPORTATION AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F. PIGMENT

SECTION 15 - REGULATORY INFORMATION

SKIN

NEED TO WEAR GLOVES AND AFFORD ADEQUATE SKIN PROTECTION.
 THIS PRODUCT HAS BEEN REVIEWED AND DETERMINED TO BE A HAZARDOUS SUBSTANCE UNDER THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES: EYE PROTECTION
 IMMEDIATE HEALTH HAZARD USE SAFETY EYEWEAR
 CHRONIC HEALTH HAZARD
 FIRE HAZARD OTHER PROTECTIVE EQUIPMENT:

REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION.
 RECOMMENDED PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION.
 LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE HYGIENIC SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372: WASH THE

CHEMICAL NAME	CAS NUMBER	SECTION 9 - PHYSICAL AND C
---------------	------------	----------------------------

TOLUENE	108-88-3	BOILING RANGE: -34 - 900 F
XYLENE	1330-20-7	VAPOR DENSITY: HEAVIER THAN AIR
ETHYLBENZENE	100-41-4	ODOR: SOLVENT LIKE

TOXIC SUBSTANCES CONTROL ACT:
 LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES: NONE KNOWN APPEAR

ENVIRONMENTAL RELEASE INFORMATION

THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT. FREEZE

SPECIFIC GRAVITY: 0.8990 CAS NUMBER

VAPOR PRESSURE: 1317-65-3

MIXTURED ALKYL PROPRIETARY

PERMANENTLY CONTAINED IN THIS PRODUCT THAT ARE GREATER THAN 3%. (SEE SE

CHEMICAL NAME	CAS NUMBER	SECTION 10 - STABILITY
---------------	------------	------------------------

CALCIUM CARBONATE	1317-65-3	CONDITIONS TO AVOID: AVOID ALL POSSIBLE SOURCES OF IGNITION.
-------------------	-----------	---

INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDIC
 WARNING!

HAZARDOUS DECOMPOSITION:
 THIS PRODUCT MAY CONTAIN SUBSTANCES THAT ARE KNOWN TO BE CARCINOGENIC OR CAUSE CANCER. DECOMPOS

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY INFORMATION: THIS PRODUCT IS NOT KNOWN TO BE AFFECTED BY TEMPERATURE, HUMIDITY, OR LIGHT. IT DOES NOT CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

SECTION 11 - TOXICOLOGICAL INFORMATION

THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS: AB5, D2A, D2B	CHEMICAL NAME
ACETONE	N.D.

LIQUEFIED PETROLEUM GAS	SECTION 16 - OTHER INFORMATION	N.D.
METHANOL	N.D.	N.D.
HEALTH	2*	N.D.
FLAMMABILITY	4	TITANIUM DIOXIDE
REACTIVITY	0	>7500 MG/KG (ORAL, RAT)
PERSONAL PROTECTION	XOLUENE	N.D.
		N.D.

ORGANIC COMPOUNDS, G/5000 MG/KG (ORAL, RAT) N.D.

REASON FOR REVISION: N.D. N.D.

METHANOL SILICATE	N.D.	TCLO: 11 MG/M3 INH.
N.A. - NOT APPLICABLE		
N.E. - NOT ESTABLISHED		3500 MG/KG (ORAL, RAT)
N.D. - NOT DETERMINED		

PIGMENT YELLOW 73 N.D.
 THE INFORMATION CONTAINED ON THIS MSDS HAS BEEN CHECKED AND SHOULD BE ACCURATE. HOWEVER, IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

ECOLOGICAL INFORMATION: PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

SECTION 13 - DISPOSAL INFORMATION

DISPOSAL INFORMATION:
 DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER STORM DRAINS OR SEWER SYSTEMS.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: AEROSOL

DOT TECHNICAL NAME:

DOT HAZARD CLASS: 2.1

DOT UN/NA NUMBER: UN1950

PACKING GROUP:

HAZARD SUBCLASS:

RESP. GUIDE PAGE: 126

ITEM: 5H912 - Marking Paint Hi Vis Yellow 15 Oz

PICK REQ: 1061383294

MATERIAL SAFETY DATA SHEET (MSDS)

MSDS: A9371

This MSDS should be attached or kept with the respective product with which it is associated.

MAY BE HARMFUL IF SWALLOWED.

Associated Overexposures: CHRONIC MARKING: Paint Hi Vis Yellow 15 Oz
IARC LISTS ETHYLENENE AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B).

MATERIALS SAFETY DATA SHEET (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO XYLENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG, SPLEEN, EYE AND BLOOD DAMAGE AS WELL AS WWW. REPRODUCTIVE DISORDERS. EFFECTS IN HUMANS, DUE TO CHRONIC OVEREXPOSURE, HAVE INCLUDED LIVER, CARDIAC ABNORMALITIES AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO TOLUENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG AND SPLEEN DAMAGE. EFFECTS IN HUMANS HAVE INCLUDED LIVER AND CARDIAC ABNORMALITIES.

RUST-OLEUM HIGH PERFORMANCE INDUSTRIA

PRIMARY ROUTE(S) OF ENTRY:

SKIN CONTACT, SKIN ABSORPTION, INHALATION, EYE CONTACT

IDENTIFICATION NUMBER:

V2324838, V2344838, V2345838, V2354838, V2392838, V2363838

SECTION 4 - FIRST AID MEASURES

PROD

FIRST AID - EYE CONTACT:

HOLD EYELIDS APART AND FLUSH WITH PLenty OF WATER FOR AT LEAST 15 MINUTES.

GET MEDICAL ATTENTION.

RUST-

11 HAWTHORN PARKWAY

PERSONAL PROTECTION:

WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR

PERSISTS.

MANUFACTURER:

RUST-OLEUM CORPORATION:

IF YOU EXPERIENCE DIFFICULTY BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE. VERNON IMMEDIATELY. USA

FIRE FIGHTING INFORMATION:

ASPIRATION HAZARD:

DO NOT INDUCE VOMITING. HIGHLY FLAMMABLE. DO NOT SMOKE BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION.

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME SECTION NUMBER FIGHTING MEASURES % LESS THAN

FLASH POINT: -156 F (SETAFLASH) 67-64-1 30.0

LOWEST FLASH POINT: 0.7 % 68476-86-8 30.0

UPPER EXPLOSIVE LIMIT: 12.8 %

ALIPHATIC HYDROCARBON 64742-89-8

EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, WATER FOG

TITANIUM DIOXIDE

UNUSUAL FIRE AND EXPLOSION HAZARDS:

WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO

TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. FLASH POINT IS

LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR! NAP

PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN.

ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. VAPORS CAN

TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY

CLOSED. MAGNESIUM

FIRE FIGHTING PROCEDURES: 100-41-4

5.0

EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE.

PIGMENT YELLOW 73

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CHEM

STEPS TO BE TAKEN IMMEDIATELY IN CASE OF SPILL OR LEAK:

CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS

SUCH AS SAWDUST. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE ACET

WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL,

STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED LIQU

CONTAINERS. GAS

ALIPHATIC HYDROCARBON 300 PPM N.E. 300 PPM N.E.

SECTION 7 - HANDLING AND STORAGE

TITA

HANDLING:

WASH HANDS BEFORE EATING. WASH THOROUGHLY AFTER HANDLING. USE ONLY IN A

WELL-VENTILATED AREA. AVOID BREATHING VAPOR OR MIST. FOLLOW ALL MSDS/LABEL

PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT. NAPHT

RESIDUES. 300

XYLENE 100 PPM 150 PPM 100 PPM N.E.

STORAGE:

DO NOT STORE IN A WARMED SPACE. STORE IN A COOL, DRY PLACE. DO NOT EXPOSE TO

AND PROTECTED FOR STORAGE OF NEPA CLASS I FLAMMABLE LIQUIDS. KEEP CONTAINERS

TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN

FLAME. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120

DEG. F. PIGMENT

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

USE PROCESS ENCLOSURES OR EQUIPMENT WITH PRESSURIZATION FOR CONTAINMENT OF VAPOR OR EX
CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. REMOVABLE
EXPLOSION-PROOF VENTILATION EQUIPMENT. PREVENT BUILD-UP OF VAPORS BY OPENING

ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION.

EFFECTS OF OVEREXPOSURE -

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT PROLONGED

REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT PROLONGED

RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN SIGHT

ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN

CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE

LIMITS. HIGH

LUNGS. AVOID BREATHING VAPORS OR MISTS. HIGH GAS, VAPOR, MIST OR DUST

EXPOSURE MAY BE HARMFUL. IMMEDIATELY OBTAIN MEDICAL ATTENTION IF A POSITIVE

PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN

UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR ANY OTHER EFFECTS OF

CIRCUMSTANCES WHERE AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION

SECTION 15 - REGULATORY INFORMATION

SKIN

NEED TO WEAR GLOVES TO AFFORD ADEQUATE SKIN PROTECTION. THIS PRODUCT HAS BEEN REVIEWED UNDER THE SUPERFUND AMENDMENT AND THE CONTACT PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND THE MAT REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES: EYE PRO IMMEDIATE HEALTH HAZARD USE SAFETY EYEWEAR CHRONIC HEALTH HAZARD FIRE HAZARD OTHER PROTECTIVE EQUIPMENT:

REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION. LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE HYGI SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372: WASH THO

CHEMICAL NAME	CAS NUMBER	SECTION 9 - PHYSICAL AND C
---------------	------------	----------------------------

TOLUENE	108-88-3	BOILING RANGE: -34 - 900 F
XYLENE	1330-20-7	VAPOR DENSITY: HEAVIER THAN AIR
ETHYLBENZENE	100-41-4	ODOR: SOLVENT LIKE

TOXIC SUBSTANCES CONTROL ACT: LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES: NONE KNOWN APPEAR

EVAPORATION RATE: 0.8990 CAS NUMBER

THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT. FREEZE

SHEETAL NITRITY: 0.8990 CAS NUMBER

VAPOR PRESSURE: 1317-65-3

MIXED ALKYL PROPRIETARY

THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%. (SEE SE

CHEMICAL NAME	CAS NUMBER	SECTION 10 - STABILITY
---------------	------------	------------------------

CALCIUM CARBONATE	1317-65-3	CONDITIONS TO AVOID: AVOID ALL POSSIBLE SOURCES OF IGNITION.
-------------------	-----------	--

INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG AC WARNING!

HAZARDOUS DECOMPOSITION: THIS PRODUCT CONTAINS A MIXTURE OF NON-HAZARDOUS INGREDIENTS THAT MAY CAUSE CANCER. DECOMPOS

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS. TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

SECTION 11 - TOXICOLOGICAL INFORMATION

THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS: AB5, D2A, D2B	CHEMICAL NAME
ACETONE	N.D.

LIQUEFIED PETROLEUM GAS	SECTION 16 - OTHER INFORMATION	N.D.
-------------------------	--------------------------------	------

HEALTH	2*	N.D.
FLAMMABILITY	4	TITANIUM DIOXIDE >7500 MG/KG (ORAL, RAT)
REACTIVITY	0	N.D.
PERSONAL PROTECTION	XOLUENE	N.D.

HAZARDOUS ORGANIC COMPOUNDS, G/5000 MG/KG (ORAL, RAT) N.D.

REASON FOR REVISION: N.D.

HAZARDOUS SILICATE N.D. TCLO: 11 MG/M3 INH.

N.A. - NOT APPLICABLE

N.E. - NOT ESTABLISHED

N.D. - NOT DETERMINED

PIGMENT YELLOW 73 N.D. THE INFORMATION CONTAINED ON THIS MSDS HAS BEEN CHECKED AND SHOULD BE ACCURATE. HOWEVER, IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

ECOLOGICAL INFORMATION: PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

SECTION 13 - DISPOSAL INFORMATION

DISPOSAL INFORMATION: DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER STORM DRAINS OR SEWER SYSTEMS.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: AEROSOL

DOT TECHNICAL NAME:

DOT HAZARD CLASS: 2.1

DOT UN/NA NUMBER: UN1950

PACKING GROUP:

HAZARD SUBCLASS:

RESP. GUIDE PAGE: 126

ITEM: 5H915 - Mark Paint Fluorescent Red Orange

PICK_REQ: 1061383294

MATERIAL SAFETY DATA SHEET (MSDS)

MSDS: B0841

This MSDS should be attached or kept with the respective product with which it is associated.

#####

INCLUDED LIVER AND CARDIAC ABNORMALITIES.

REMARKS: 5H915 - Mark Paint Fluorescent Red Orange
SKIN CONTACT, SKIN ABSORPTION, INHALATION, EYE CONTACT

MATERIAL SAFETY DATA SHEET

SECTION 4 - FIRST AID MEASURES

24 H

FIRST AID - EYE CONTACT:
HOLD EYELIDS APART AND FLUSH WITH RUST-OLEUM CORPORATION FOR AT LEAST 15 MINUTES.
GET MEDICAL ATTENTION.

WWW.RUSTOLEUM.COM

FIRST AID - SKIN CONTACT:
WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

FIRST AID - INHALATION:

IF YOU EXPERIENCE DIFFICULTY BREATHING, MOVE TO A FRESH AIR AREA IMMEDIATELY. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE. SPRAYS IMMEDIATELY.

REVISION DATE: 06/21/2005

FIRST AID - INGESTION:
ASPIRATION HAZARD: IDENTIFICATION NUMBER: V2333838, V2355838, V2358838
DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION.

SUPPLIER:

RUST-OLEUM CORPORATION

11 HAWTHORN PARKWAY SECTION 5 - FIRE FIGHTING MEASURES

VERN

FLASH POINT (SETAFLASH): -156 F

MINERALS EXPOSURE LIMIT: 0.9 %

UPPER EXPLOSIVE LIMIT: 11.2 RUST-OLEUM CORPORATION

11 HAWTHORN PARKWAY

11 HAWTHORN PARKWAY MEDEA 06 DRY CHEMICAL, FOAM, WATER FOG

USA

UNUSUAL FIRE AND EXPLOSION HAZARDS:

PERFORATION OF THE PRESSURIZED CONTAINER MAY OCCUR WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY CLOSED. FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR! ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CHEM

SPECIAL FIREFIGHTING PROCEDURES:

EVACUATE AREA AND FIGHT FIRE FROM UPWIND. RUST-OLEUM GAS 68476-86-8 30.0

ALIPHATIC PETROLEUM 64742-89-8 15.0 400 PPM N.E.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

DO NOT BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: 150 PPM
REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE POLYMER (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE CONTAINERS SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. NAPH

ETHYLBENZENE 100-41-4 1.0 100 PPM 125 PPM

SECTION 7 - HANDLING AND STORAGE

CHEM

HANDLING:

AVOID BREATHING VAPORS OR DUST. GASES ONLY IN WELL-VENTILATED AREA. WASH HANDS BEFORE EATING. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. WASH THOROUGHLY AFTER ALIPH DISTILL

DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F. NAPHTHA

ETHYLBENZENE 100 PPM N.E.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS/SECTION 3 - HAZARDS IDENTIFICATION

USE EXPLOSION-PROOF VENTILATION EQUIPMENT. USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE EMERGEN LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION. SYSTEM CA

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN EFFECTS ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN PROLONGED CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

EFFECTS OF OVEREXPOSURE - INHALATION:

EXHAUSTION, HEADACHE, DROWSINESS, IRRITATION OF THE EYES, SLIMED, THROAT, AND IRRITATIVE PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN LUNG UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR ANY OTHER CONCENTRATION CIRCUMSTANCES WHERE AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION.

ASPIRATION HAZARD IF SWALLOWED; CAN ENTER LUNGS AND CAUSE DAMAGE. USE IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THIS MATERIAL THROUGH THE SKIN. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION. IARC LI

CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A L EXHAUSTION, WEARINESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION)

USE SAFETY EYEWEAR/ GOGGLES TO PROTECT AGAINST SPRAYS OR FOGS. PROLONGED OVEREXPOSURE TO VAPORS OR DUSTS IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER

REFER TO SAFETY SUPERVISOR OR HUMANITARIAN FOR INFORMATION REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION. REPROD

OVEREXPOSURE TO VAPORS OR DUSTS IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER

WASH THOROUGHLY WITH SOAP AND WATER IMMEDIATELY AFTER EXPOSURE. INCLUDED LIVER,

WASH THOROUGHLY WITH SOAP AND WATER IMMEDIATELY AFTER EXPOSURE. INCLUDED LIVER,

WASH THOROUGHLY WITH SOAP AND WATER IMMEDIATELY AFTER EXPOSURE. INCLUDED LIVER,

LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES: NONE KNOWN

BOILING POINT: 155°F

NON-FLAMMABLE: YES

THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT.

ODOR: S

CHEMICAL NAME: ND CAS NUMBER

REFERENCE: LIQUID 7732-18-5

EMULSIFIER: FASTER THAN OTHER

BENZYLALCOHOL: 100%

THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%.

FREEZE

SOLUBLE: 0.8700

CAS NUMBER

WATER PRESSURE: ND

7732-18-5

ETHYLENE CARBONATE

1317-65-3

ETHYLENE GLYCOL

7727-43-7

ETHYLENE GLYCOL MONOETHYLENE GLYCOL MIXTURE

POLYMER ANCHORED ORANGE DYE DISPERSION MIXTURE

MODIFIED ALKYL

PROPRIETARY

SECTION 10

CONDITIONS TO AVOID: WARMING! THIS PRODUCT CONTAINS CHEMICAL(S) KNOWN BY THE STATE OF CALIFORNIA TO CAUSE CANCER.

INCOMPAT

HAZARDOUS DECOMPOSITION:

THIS PRODUCT CONTAINS CHEMICAL(S) KNOWN BY THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

OPEN FLA

HAZARDOUS DECOMPOSITION: WARMING! THIS PRODUCT CONTAINS CHEMICAL(S) KNOWN BY THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

HAZARDOUS DECOMPOSITION: WARMING! THIS PRODUCT CONTAINS CHEMICAL(S) KNOWN BY THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

HAZARDOUS DECOMPOSITION: WARMING! THIS PRODUCT CONTAINS CHEMICAL(S) KNOWN BY THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

CANADIAN WHMIS CLASS: AB5, D2A, D2B

PRODUCT LD50: ND

PRODUCT LC50: ND

SECTION 16 - OTHER INFORMATION

CHEM

HMS RATINGS:

HEALTH: LIQUEFIED PETROLEUM GAS N.D.

N.D.

FLAMMABILITY: 4

REACTIVITY: ALIPHATIC PETROLEUM

N.D.

N.D.

PERSONAL PROTECTION: DISTILLATES

VOLATILE ORGANIC COMPOUNDS, DG/L: 540 MAX

N.D.

HAZARDOUS DECOMPOSITION: WARMING! THIS PRODUCT CONTAINS CHEMICAL(S) KNOWN BY THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

N.D.

LEGEND: DYE DISPERSION

N.A. - NOT APPLICABLE

N.E. - NOT ESTABLISHED

N.D. - NOT DETERMINED

>25 ML/KG (ORAL, RAT)

>700 PPM (

3500 MG/KG (ORAL, RAT) N.D.

THE INFORMATION CONTAINED ON THIS MSDS HAS BEEN CHECKED AND SHOULD BE ACCURATE. HOWEVER, IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

ECOLOGICAL INFORMATION: PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

SECTION 13 - DISPOSAL INFORMATION

DISPOSAL INFORMATION:

DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER STORM DRAINS OR SEWER SYSTEMS.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: AEROSOL

PACKING GROUP:

DOT TECHNICAL NAME:

HAZARD SUBCLASS:

DOT HAZARD CLASS: 2.1

RESP. GUIDE PAGE: 126

DOT UN/NA NUMBER: UN1950

SECTION 15 - REGULATORY INFORMATION

CERCLA - SARA HAZARD CATEGORY:

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA "HAZARD CATEGORIES" PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES: IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

SARA SECTION 313:

LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME CAS NUMBER

TOLUENE 108-88-3

ETHYLBENZENE 100-41-4

TOXIC SUBSTANCES CONTROL ACT:

ITEM: 5H917 - Marking Paint White 15 Oz

PICK REQ: 1061383294

MATERIAL SAFETY DATA SHEET (MSDS)

MSDS: A9371

This MSDS should be attached or kept with the respective product with which it is associated.

#####

MAY BE HARMFUL IF SWALLOWED.

Associated Hazards: CHRONIC HAZARD: Paint White 15 Oz
IARC LISTS ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B).

MATERIALS SAFETY DATA SHEET SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL HOURS OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO XYLENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER-OL ABNORMALITIES, KIDNEY, LUNG, SPLEEN, EYE AND BLOOD DAMAGE AS WELL AS WWW. REPRODUCTIVE DISORDERS. EFFECTS IN HUMANS, DUE TO CHRONIC OVEREXPOSURE, HAVE INCLUDED LIVER, CARDIAC ABNORMALITIES AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO TOLUENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER-ABNORMALITIES, KIDNEY, LUNG AND SPLEEN DAMAGE. EFFECTS IN HUMANS HAVE INCLUDED LIVER AND CARDIAC ABNORMALITIES.

PRODUCT

PRIMARY ROUTE(S) OF ENTRY:

SKIN CONTACT, SKIN ABSORPTION, INHALATION, EYE CONTACT

IDENTIFICATION NUMBER:

V2324838, V2344838, V2345838, V2354838, V2392838, V2363838

SECTION 4 - FIRST AID MEASURES

PROD

FIRST AID - EYE CONTACT:

HOLD EYELIDS APART AND FLESH WITH PLenty OF WATER FOR AT LEAST 15 MINUTES.

GET MEDICAL ATTENTION.

RUST-

11 HAWTHORN PARKWAY

PERSONAL SKIN CONTACT:

WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

MANUFACTURER:

RUST-OLEUM CORPORATION:

IF YOU EXPERIENCE DIFFICULTY BREATHING LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY.

USA

PREPARED BY: RUST-OLEUM CORPORATION

ASPIRATION HAZARD:

DO NOT INDUCE VOMITING. IF SWALLOWED, DO NOT INDUCE VOMITING BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION.

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME SECTION NUMBER FIGHTING MEASURES % LESS THAN

FLASH POINT: -156 F (SETAFLASH) 67-64-1 30.0

LOWER EXPOSURE LIMIT: 0.7 % 68476-86-8 30.0

UPPER EXPOSURE LIMIT: 12.8 %

ALIPHATIC HYDROCARBON 64742-89-8

EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, WATER FOG

TITANIUM DIOXIDE

UNUSUAL FIRE AND EXPLOSION HAZARDS:

WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO

TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. FLASH POINT IS

LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR! NAP

PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN.

ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. VAPORS CAN TRAVEL

TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY

CLOSED. MAGNESIUM

FIGHTING PROCEDURES: 100-41-4 5.0

EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE.

PIGMENT YELLOW 73

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR WASHED: CEILING

CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS

SUCH AS SAWDUST. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE ACET

WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE

(PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. LIQUID

GAS

ALIPHATIC HYDROCARBON 300 PPM N.E. 300 PPM N.E.

SECTION 7 - HANDLING AND STORAGE

TITA

HANDLING:

WASH HANDS BEFORE EATING. WASH THOROUGHLY AFTER HANDLING. USE 300 PPM A

WELL-VENTILATED AREA. AVOID BREATHING VAPOR OR MIST. FOLLOW ALL MSDS/LABEL

PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT

RESIDUES. NAPH

XYLENE 100 PPM 150 PPM 100 PPM N.E.

STORAGE:

DO NOT STORE IN A SPACE OF 100 F. STORE IN SMALL QUANTITIES IN BUILDINGS

AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. KEEP CONTAINERS

TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN

FLAME. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120

DEG. F. PIGMENT

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EMERGENCY PROCEDURES:

USE PROCESS ENCLOSURES OR EQUIPMENT WITH PRESSURE TIGHT CONTAINERS. IF FIRE OR EX

POSURE TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. REMOVABLE

EXPLOSION-PROOF VENTILATION EQUIPMENT. PREVENT BUILD-UP OF VAPORS BY OPENING

ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION. EFFECTS OF OVEREXPOSURE -

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT PROLONGED

RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN SLIGHT

ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN

CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE

LIMITS. HIGH

LUNGS. AVOID BREATHING VAPORS OR MISTS. HIGH GAS, VAPOR, MIST OR DUST

CONCENTRATIONS MAY BE HARMFUL IF INHALED. IMMEDIATELY USE A POSITIVE

PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN

UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR ANY OTHER EFFECTS OF

CIRCUMSTANCES WHERE AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION

SECTION 15 - REGULATORY INFORMATION

SKIN

NEED TO WEAR PROTECTIVE EQUIPMENT TO AFFORD ADEQUATE SKIN PROTECTION.
 THIS PRODUCT HAS BEEN REVIEWED AND DETERMINED TO BE A HAZARDOUS SUBSTANCE IN CONTACT
 PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER
 APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES: EYE PROTECTION
 IMMEDIATE HEALTH HAZARD
 CHRONIC HEALTH HAZARD
 FIRE HAZARD
 OTHER PROTECTIVE EQUIPMENT: USE SAFETY EYEWEAR

REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION.
 RECOMMENDED PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION.
 LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE
 SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE HYGIENE
 SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372: WASH THE

CHEMICAL NAME	CAS NUMBER	SECTION 9 - PHYSICAL AND C
---------------	------------	----------------------------

TOLUENE	108-88-3	BOILING RANGE: -34 - 900 F
XYLENE	1330-20-7	VAPOR DENSITY: HEAVIER THAN AIR
ETHYLBENZENE	100-41-4	ODOR: SOLVENT LIKE

TOXIC SUBSTANCES CONTROL ACT:
 LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE
 SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE
 UNITED STATES: NONE KNOWN APPEAR

ENVIRONMENTAL RELEASE INFORMATION

THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE
 COMPONENTS IN THIS PRODUCT. FREEZE

SPECIFIC GRAVITY: 0.8990 CAS NUMBER

VAPOR PRESSURE: 1317-65-3

MIXED ALKYL PROPRIETARY

THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT
 GREATER THAN 3%. (SEE SE

CHEMICAL NAME	CAS NUMBER	SECTION 10 - STABILITY
---------------	------------	------------------------

CALCIUM CARBONATE	1317-65-3	CONDITIONS TO AVOID: AVOID ALL POSSIBLE SOURCES OF IGNITION.
-------------------	-----------	---

UNCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG AC
 WARNING!

HAZARDOUS DECOMPOSITION:
 THIS PRODUCT MAY DECOMPOSE AND RELEASE TOXIC GASES WHEN EXPOSED TO
 CAUSE CANCER. DECOMPOS

WILL NOT OCCUR UNDER NORMAL CONDITIONS.

CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

SECTION 11 - BIOLOGICAL INFORMATION

THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT
 REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS: AB5, D2A, D2B	CHEMICAL NAME
-------------------------------------	---------------

LIQUEFIED PETROLEUM GAS	OTHER INFORMATION	N.D.
HEAVY METAL CARBON	N.D.	N.D.
HEALTH	2*	N.D.
FLAMMABILITY	4 TITANIUM DIOXIDE	>7500 MG/KG (ORAL, RAT)
REACTIVITY	0	N.D.
PERSONAL PROTECTION XOLUENE	N.D.	N.D.

ORGANIC COMPOUNDS, G/5000 MG/KG (ORAL, RAT) N.D.

REASON FOR REVISION: N.D. N.D.

HEAVY METAL SILICATE	N.D.	TCLO: 11 MG/M3 INH.
N.A. - NOT APPLICABLE		
N.E. - NOT ESTABLISHED		
N.D. - NOT DETERMINED		3500 MG/KG (ORAL, RAT)

PIGMENT YELLOW 73 N.D.
 THE INFORMATION CONTAINED ON THIS MSDS HAS BEEN CHECKED AND SHOULD BE
 ACCURATE. HOWEVER, IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH
 ALL FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

ECOLOGICAL INFORMATION: PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

SECTION 13 - DISPOSAL INFORMATION

DISPOSAL INFORMATION:
 DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE AND FEDERAL REGULATIONS
 AND ORDINANCES. DO NOT ALLOW TO ENTER STORM DRAINS OR SEWER SYSTEMS.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: AEROSOL

DOT TECHNICAL NAME:

DOT HAZARD CLASS: 2.1

DOT UN/NA NUMBER: UN1950

PACKING GROUP:

HAZARD SUBCLASS:

RESP. GUIDE PAGE: 126

ITEM: 6H084 - Paint Striping Red

PICK REQ: 1061383294

MATERIAL SAFETY DATA SHEET (MSDS)

MSDS: A7757

This MSDS should be attached or kept with the respective product with which it is associated.

LUNGS. AVOID BREATHING VAPORS OR MISTS. HIGH GAS, VAPOR, MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. HARMFUL IF INHALED. #####

EFFECTS OF OVEREXPOSURE - INGESTION: Associated Grai
ASPIRATION HAZARD IF SWALLOWED; CAN ENTER LUNGS AND CAUSE DAMAGE.
SUBSTANCE MAY BE HARMFUL IF SWALLOWED. MATERIAL SA

EXPOSURE ASSOCIATED RISKS:
IARC LISTS ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B). MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO XYLENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG, SPLEEN, EYE AND BLOOD DAMAGE AS WELL AS REPRODUCTIVE DISORDERS. EFFECTS IN HUMANS, DUE TO CHRONIC OVEREXPOSURE, HAVE INCLUDED LIVER, CARDIAC ABNORMALITIES AND NERVOUS SYSTEM DAMAGE. PRO OVEREXPOSURE TO TOLUENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH ABNORMALITIES, KIDNEY, LUNG AND SPLEEN DAMAGE. EFFECTS IN HUMANS HAVE INCLUDED LIVER AND CARDIAC ABNORMALITIES. CONTAINS CARBON BLACK. CHRONIC REVISIO INFLAMMATION, LUNG FIBROSIS, AND LUNG TUMORS HAVE BEEN OBSERVED IN SOME RATS EXPERIMENTALLY EXPOSED FOR LONG PERIODS OF TIME TO EXCESSIVE CONCENTRATIONS OF CARBON BLACK AND SEVERAL INSOLUBLE FINE DUST PARTICLES. TUMORS HAVE NOT BEEN OBSERVED IN OTHER ANIMAL SPECIES (I.E., MOUSE AND HAMSTER) UNDER SIMILAR CIRCUMSTANCES AND STUDY CONDITIONS. EPIDEMIOLOGICAL STUDIES OF NORTH AMERICAN WORKERS SHOW NO EVIDENCE OF CLINICALLY SIGNIFICANT ADVERSE HEALTH EFFECTS DUE TO OCCUPATIONAL EXPOSURE TO CARBON BLACK. CARBON BLACK IS LISTED AS A GROUP 2B - "POSSIBLY CARCINOGENIC TO HUMANS" BY IARC AND IS PROPOSED TO BE LISTED AS A4 - "NOT CLASSIFIED AS A HUMAN CARCINOGEN" BY THE AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS. SIGNIFICANT EXPOSURE IS NOT ANTICIPATED DURING BRUSH APPLICATION OR DRYING. RISK OF OVEREXPOSURE DEPENDS ON DURATION AND LEVEL OF EXPOSURE TO DUST FROM REPEATED SANDING SURFACES OR SPRAY MIST AND THE ACTUAL CONCENTRATION OF CARBON BLACK IN THE FORMULA.

VERNON HILLS, IL 60061

PRIMARY ROUTE(S) OF ENTRY:

SKIN CONTACT, SKIN ABSORPTION, INHALATION, EYE CONTACT

PREPARER: CZICZO, RAY

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT:

HOLD EYELIDS APART AND FLUSH WITH LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

LIQUIFIED PETROLEUM GAS 68476-86-8 25.0

FIRST AID - SKIN CONTACT:

WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION/DEVELOPS OR PERSISTS.

ALIPHATIC HYDROCARBON 64742-89-8 10.0

FIRST AID - INHALATION:

IF YOU EXPERIENCE DIFFICULTY BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY.

NAPHTHA

ASPIRATION HAZARD: 67-64-1 5.0 500 PPM

DO NOT INDUCE VOMITING.

DO NOT INDUCE VOMITING. DO NOT INDUCE VOMITING BY INDUCING REFLEX. BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION.

PIGMENT B

AROMATIC HYDROCARBON 64742-95-6 5.0

N.E.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: -156 F (SETAFLASH)

1,2,4-TRIMETHYLBENZENE 95-63-6 5.0

LOWER EXPLOSIVE LIMIT: 1.0%

UPPER EXPLOSIVE LIMIT: 12.8% ETHYLBENZENE 100-41-4 1.0

EMERGENCY RESPONSE MEDIA: ACRYLONITRILE, POLYMER, OSHA PEL-CEILING

UNUSUAL FIRE AND EXPLOSION HAZARDS: 1000 PPM N.E.

VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. WATER SPRAY MAY BE INEFFECTIVE.

FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR. N.E. PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. KEEP CONTAINERS TIGHTLY CLOSED.

NAPHTHA

N.E.

N.E.

SPECIAL FIRE FIGHTING PROCEDURES:

EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE.

750 PPM

75

STODDARD SOLVENTS

N.E.

500 PPM

N.E.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

1,2,4-TR

ETHYLBENZENE

125 PPM

100 PPM

N.E.

SECTION 7 - HANDLING AND STORAGE

HANDLING:

SECTION 3 - HAZARDS IDENTIFICATION

WASH THOROUGHLY AFTER HANDLING. WASH HANDS BEFORE EATING. USE ONLY IN A WELL-VENTILATED AREA. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. AVOID BREATHING VAPOR OR HARMFUL MIST.

FLASH FIRE OR EXPLOSION. EXTREMELY FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED.

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F.

SLIGHT SKIN IRRITATION.

EFFECTS OF OVEREXPOSURE EXPOSURE CONTROLS/PERSONAL PROTECTION

HIGH

ENGINEERING CONTROLS:
 ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO
 CONTROL AIRBORNE LEVELS OF THIS PRODUCT TO PREVENT EXPOSURE TO HAZARDOUS
 CONCENTRATIONS OF THIS PRODUCT.

RESPONSE INFORMATION:
 DISPOSE OF MATERIAL IN A RECEPTACLE PROVIDED FOR THIS PURPOSE. DO NOT ALLOW TO ENTER STORM DRAINS OR SEWER SYSTEMS. RESPIRATORY PROTECTION MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE THE EXPOSURE LEVELS DO NOT EXCEED THE PERMISSIBLE EXPOSURE LIMIT.

DOT PROPER SHIPPING NAME: AEROSOL
 PROTECTION PROVIDED BY AIR PURIFYING RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR A DOT HAZARD CLASSIFICATION FOR AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION.

DOT UN/NA NUMBER: UN 1950
 SKIN PROTECTION:
 WEAR GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THIS MATERIAL, THROUGH THE SKIN. NITRILE OR NEOPRENE GLOVES MAY AFFORD PROTECTION.

HAZARD STATEMENT: 1
 PRECAUTIONARY STATEMENT: 126
 USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH

OTHER PROTECTIVE EQUIPMENT: 15 - REGULATORY INFORMATION
 REFERENCE TO THE EQUIPMENT AND ITS APPLICATION.
 THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA "HAZARD CATEGORIES" PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER THE APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:
 IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

SARA SECTION 313:
 LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372: VAPOR D

CHEMICAL NAME	CAS NUMBER
ETHYL BENZENE	100-41-4
FORMALDEHYDE	50-00-0
BENZENE	71-43-2
ARSENIC COMPOUNDS	NOT SPECIFIED
CADMIUM COMPOUNDS	NOT SPECIFIED
MERCURY COMPOUNDS	NOT SPECIFIED

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 NON-FLAMMABLE AND NON-TOXIC: PROPRIETARY
 AVOID ALL POSSIBLE SOURCES OF IGNITION. AVOID T
 PENNSYLVANIA RIGHT-TO-KNOW:
 THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT
 GREATER THAN 3%.

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 WHEN HEATED TO DECOMPOSITION IT EMITS ACRID SMOKE
 CARBON MONOXIDE AND CARBON DIOXIDE.

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 NO HAZARDOUS REACTIONS ARE KNOWN TO OCCUR UNDER NORMAL CONDITIONS.

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE	50-00-0			
BENZENE	71-43-2			
ARSENIC COMPOUNDS	NOT SPECIFIED			
CADMIUM COMPOUNDS	NOT SPECIFIED			
MERCURY COMPOUNDS	NOT SPECIFIED			
NICKEL COMPOUNDS	NOT SPECIFIED			
LEAD COMPOUNDS	NOT SPECIFIED			
STODDARD SOLVENTS				

HAZARD STATEMENT: 153 - STABILITY AND REACTIVITY
 THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS:

CHEMICAL NAME	CAS NUMBER	PRODUCT LC50: ND	LD50	LC50
ETHYL BENZENE	100-41-4			
MICROCRYSTALLINE SILICA	14808-60-7			
FORMALDEHYDE				

LEAD COMPOUNDS NOT SPECIFIED

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS:
THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT
REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS:
AB5
D2A
D2B

SECTION 16 - OTHER INFORMATION

HMIS RATINGS:
HEALTH: 2*
FLAMMABILITY: 4
REACTIVITY: 0
PERSONAL PROTECTION: X

VOLATILE ORGANIC COMPOUNDS, G/L: 523 MAX

REASON FOR REVISION:

LEGEND:
N.A. - NOT APPLICABLE
N.E. - NOT ESTABLISHED
N.D. - NOT DETERMINED

THE INFORMATION CONTAINED ON THIS MSDS HAS BEEN CHECKED AND SHOULD BE
ACCURATE. HOWEVER, IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL
FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

ORDER: 10613832044CH78 - Marking Paint Fluorescent Green 15 HAZMAT: 4CH78

HAZARD MATERIAL WARNING SHEET (HAZMAT)

When shipment is complete, retain for daily Hazmat audit

GRAINGER SHIPPING INFORMATION

STOCK # : 4CH78
MSDS # : B0841
FREIGHT CODE : 0896
DOT PROPER SHIP NAME : CONSUMER COMMODITY, ORM-D FLASHPOINT -73 DGS C, -99
DGS F

FLASHPOINT : -73 DEGREES CELSIUS, -99 DEGREES FAHRENHEIT

UPS RESTRICTIONS :

HAZARDOUS CLASS NUMBER : ORM-D

UN ID # :

PACKING GROUP :

SHIPPING LABEL : Consumer Commodity ORM-D

LIMITED QUANTITY : YES

CARTON INSTRUCTIONS : CAN REPACK IN GRAINGER S CARTON

DOT/UPS EXEMPTION NO. :

COMMENTS : HAZARDOUS MATERIAL. DO NOT SHIP AIR!!

SHIPPING-PAPERS :

PLACARD OFFERED ? YES () NO () PLEASE MARK ONE

ORDER: 1061383294 5H911 - Marking Paint Caution Blue 15 Oz HAZMAT: 5H911

HAZARD MATERIAL WARNING SHEET (HAZMAT)

When shipment is complete, retain for daily Hazmat audit

GRAINGER SHIPPING INFORMATION

STOCK # : 5H911
MSDS # : A9371
FREIGHT CODE : 0896
DOT PROPER SHIP NAME : CONSUMER COMMODITY, ORM-D FLASHPOINT -73 DGS C, -99
DGS F

FLASHPOINT : -73 DEGREES CELSIUS, -99 DEGREES FAHRENHEIT

UPS RESTRICTIONS :

HAZARDOUS CLASS NUMBER : ORM-D
UN ID # :
PACKING GROUP :
SHIPPING LABEL : Consumer Commodity ORM-D

LIMITED QUANTITY : YES
CARTON INSTRUCTIONS : CAN REPACK IN GRAINGER S CARTON
DOT/UPS EXEMPTION NO. :
COMMENTS : HAZARDOUS MATERIAL. DO NOT SHIP AIR!!
SHIPPING-PAPERS :

PLACARD OFFERED ? YES () NO () PLEASE MARK ONE

ORDER: 1061383204 5H912 - Marking Paint Hi Vis Yellow 15 Oz HAZMAT: 5H912

HAZARD MATERIAL WARNING SHEET (HAZMAT)

When shipment is complete, retain for daily Hazmat audit

GRAINGER SHIPPING INFORMATION

STOCK # : 5H912
MSDS # : A9371
FREIGHT CODE : 0896
DOT PROPER SHIP NAME : CONSUMER COMMODITY, ORM-D FLASHPOINT -73 DGS C, -99
DGS F

FLASHPOINT : -73 DEGREES CELSIUS, -99 DEGREES FAHRENHEIT

UPS RESTRICTIONS :

HAZARDOUS CLASS NUMBER : ORM-D

UN ID # :

PACKING GROUP :

SHIPPING LABEL : Consumer Commodity ORM-D

LIMITED QUANTITY : YES

CARTON INSTRUCTIONS : CAN REPACK IN GRAINGER S CARTON

DOT/UPS EXEMPTION NO. :

COMMENTS : HAZARDOUS MATERIAL. DO NOT SHIP AIR!!

SHIPPING-PAPERS :

PLACARD OFFERED ? YES () NO () PLEASE MARK ONE

ORDER: 10613832045H915 - Mark Paint Fluorescent Red Orange HAZMAT: 5H915

HAZARD MATERIAL WARNING SHEET (HAZMAT)

When shipment is complete, retain for daily Hazmat audit

GRAINGER SHIPPING INFORMATION

STOCK # : 5H915
MSDS # : B0841
FREIGHT CODE : 0896
DOT PROPER SHIP NAME : CONSUMER COMMODITY, ORM-D FLASHPOINT -73 DGS C, -99
DGS F

FLASHPOINT : -73 DEGREES CELSIUS, -99 DEGREES FAHRENHEIT

UPS RESTRICTIONS :

HAZARDOUS CLASS NUMBER : ORM-D

UN ID # :

PACKING GROUP :

SHIPPING LABEL : Consumer Commodity ORM-D

LIMITED QUANTITY : YES

CARTON INSTRUCTIONS : CAN REPACK IN GRAINGER S CARTON

DOT/UPS EXEMPTION NO. :

COMMENTS : HAZARDOUS MATERIAL. DO NOT SHIP AIR!!

SHIPPING-PAPERS :

PLACARD OFFERED ? YES () NO () PLEASE MARK ONE

ORDER: 1061383294 ITEM: 5H917 - Marking Paint White 15 Oz HAZMAT: 5H917

HAZARD MATERIAL WARNING SHEET (HAZMAT)

When shipment is complete, retain for daily Hazmat audit

GRAINGER SHIPPING INFORMATION

STOCK # : 5H917
MSDS # : A9371
FREIGHT CODE : 0896
DOT PROPER SHIP NAME : CONSUMER COMMODITY, ORM-D FLASHPOINT -73 DGS C, -99
DGS F

FLASHPOINT : -73 DEGREES CELSIUS, -99 DEGREES FAHRENHEIT

UPS RESTRICTIONS :

HAZARDOUS CLASS NUMBER : ORM-D

UN ID # :

PACKING GROUP :

SHIPPING LABEL : Consumer Commodity ORM-D

LIMITED QUANTITY : YES

CARTON INSTRUCTIONS : CAN REPACK IN GRAINGER S CARTON

DOT/UPS EXEMPTION NO. :

COMMENTS : HAZARDOUS MATERIAL. DO NOT SHIP AIR!!

SHIPPING-PAPERS :

PLACARD OFFERED ? YES () NO () PLEASE MARK ONE

ORDER: 1061383294

ITEM: 6H084 - Paint Striping Red

HAZMAT: 6H084

HAZARD MATERIAL WARNING SHEET (HAZMAT)

When shipment is complete, retain for daily Hazmat audit

GRAINGER SHIPPING INFORMATION

STOCK # : 6H084
MSDS # : A7757
FREIGHT CODE : 0843
DOT PROPER SHIP NAME : CONSUMER COMMODITY, ORM-D FLASHPOINT -104 DGS C,
-156 DGS F

FLASHPOINT : -104 DEGREES CELSIUS, -155 DEGREES FAHRENHEIT

UPS RESTRICTIONS :

HAZARDOUS CLASS NUMBER : ORM-D
UN ID # :
PACKING GROUP :
SHIPPING LABEL : Consumer Commodity ORM-D

LIMITED QUANTITY : YES
CARTON INSTRUCTIONS : CAN REPACK IN GRAINGER S CARTON
DOT/UPS EXEMPTION NO. :
COMMENTS : HAZARDOUS MATERIAL. DO NOT SHIP AIR!!
SHIPPING-PAPERS :

PLACARD OFFERED ? YES () NO () PLEASE MARK ONE
