PICK REO: 0129999246 MSDS: 75M38

**ITEM: 4Z910** 

## MATERIAL SAFETY DATA SHEET (MSDS)

This MSDS should be attached or kept with the respective product with which it is a

This MSDS should be attached or kept w	ith the respective product with which it is a
MATERIAL SAFETY DATA SHEET - 7SM38	Null
- 7000	Null
Associated Grainger Items	Null
22425, 42123, 42672, 42908, 42909, 42910, 42911, 42912	Null
	Null
22425, 42123, 42672, 42908, 42909, 42910, 42911, 42912	Null
Null	Null
MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD, 29 CFR	Null
1910.1200. STANDARD MUST BE CONSULTED FOR SPECIFIC REQUIREMENTS.	Null
Null	Null
U.S. DEPARTMENT OF LABOR	Null
OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION	Null
(NON-MANDATORY FORM)	SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS
FORM APPROVED	
OMB NO. 1218-0072	BOILING POINT: NA SPECIFIC GRAVITY (H2O=1): VARIES
Null	VAPOR PRESSURE (MM Hg.): NA MELTING POINT: 0
IDENTITY (AS USED ON LABEL AND LIST): GRINDING WHEELS	VAPOR DENSITY (AIR=1): NA EVAPORATION RATE (BUTYL ACETATE=1): NA
Null	SOLUBILITY IN WATER: NA
NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, OR	APPEARANCE AND ODOR: ALUMINUM OXIDE: PINK, RED, BROWN, BLUE, GRAY, OR WHITE
NO INFORMATION IS AVAILABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.	NO ODOR. SILICON CARBIDE: BLACK OR GREEN; NO ODOR.
Mull	Null
SECTION I	SECTION IV - FIRE AND EXPLOSION HAZARD DATA
DELIAM A	SECTION AT - FARE AND EXCENSION EMERGE MAIN
	FLASH POINT (METHOD USED): NA
ADDRESS (NUMBER, STREET, CITY,	FLAMMABLE LIMITS: NA LEL: UEL:
STATE AND ZIP CODE): NO. 8, LANE 109, DAH-HU ROAD	EXTINGUISHING MEDIA: NA
YING-KO, TAIPEI HSIEN - 239	SPECIAL FIRE FIGHTING PROCEDURES: NA
TAIWAN, R.O.C.	UNUSUAL FIRE AND EXPLOSION HAZARDS: DOES NOT BURN OR EXPLODE.
EMERGENCY TELEPHONE NUMBER: (02) 670-6158	Null
TELEPHONE NUMBER FOR INFORMATION: (02) 670-6158	SECTION V - REACTIVITY DATA
Null	
DATE PREPARED:	STABILITY: UNSTABLE ( ) STABLE (X)
SIGNATURE OF PREPARER (OPTIONAL):	CONDITIONS TO AVOID:
Null	Null
SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION	INCOMPATIBILITY (MATERIALS TO AVOID):
<u> </u>	- HAZARDOUS DECOMPOSITION OR BYPRODUCTS:
HAZARDOUS COMPONENTS (SPECIFIC OSHA ACGIH OTHER LIMITS %	Null
CHEMICAL IDENTITY; COMMON NAME(S)) PEL TLV RECOMMENDED (OPTIONAL	HAZARDOUS POLYMERIZATION: MAY OCCUR ( ) WILL NOT OCCUR (X)
	- CONDITIONS TO AVOID:
ALUMINUM OXIDE ABRASIVE 15 MG/M3 10 MG/M3 (TOTAL DUST) 50 PLUS	Null
CAS # 1344-28-1	SECTION VI - HEALTH HAZARD DATA
SILICON CARBIDE ABRASIVE 15 MG/M3 10 MG/M3 (TOTAL DUST) 50 PLUS	
CAS # 409-21-2	ROUTE(S) OF ENTRY: INHALATION? ( ) SKIN? ( ) INGESTION? ( )
Null	Null
MAY CONTAIN ONE OF THE FOLLOWING AS SOLID TREATMENTS	HEALTH HAZARDS (ACUTE AND CHRONIC):
SULFUR 15 MG/M3 1 PLUS	INHALATION DURING GRINDING - COUGHING, SHORTNESS OF BREATH.
CAS # 7704-39-9	INGESTION - NO KNOWN ADVERSE EFFECTS, BUT NOT RECOMMENDED.
PARAFFIN OR WAX 2 MG/M3 1 PLUS	SKIN - SOME MAY EXPERIENCE IRRITATION FROM DUST.
Null	EYE - DUST MAY IRRITATE EYES.
NOTE: CAS # UNIQUE IDENTIFICATION NUMBER FROM THE CHEMICAL ABSTRACT SERVICE	Null
OF THE AMERICAN CHEMICAL SOCIETY.	CARCINOGENICITY: NTP? ( ) IARC MONOGRAPHS? ( ) OSHA REGULATED? ( )
	Null
SIGNS AND SYMPTOMS OF EXPOSURE: GRINDING WHEELS BREAK DOWN DURING USE. THE	VENTILATION:
RESULTING DUST IS CLASSIFIED AS INERT NUISANCE DUST AND WOULD HAVE THE	LOCAL EXHAUST: UTILIZE LOCAL EXHAUST TO KEEP DUST BELOW

Null	SPECIAL:	
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:	OTHER:	
Null	Null	
EMERGENCY AND FIRST AID PROCEDURES: IF INHALATION OVEREXPOSURE OCCURS,	PROTECTIVE GLOVES: MAY BE REQUIRED IN GRINDING OPERATIONS.	
REMOVE INDIVIDUAL TO FRESH AIR AND CONTACT PHYSICIAN, IF NECESSARY.	EYE PROTECTION: REQUIRED.	
Null	OTHER PROTECTIVE CLOTHING OR EQUIPMENT: WHEN REQUIRED FOR OPERATOR	
Null	PROTECTION.	
Null	Null	
Null	WORK HYGIENIC PRACTICES:	
Null	Null	
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE	Null	
	Null	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:	Null	
Null	Null	
WASTE DISPOSAL METHOD:	Null	
Null	Null	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: TAKE MEASURES TO INSURE	Null	
AGAINST MECHANICAL DAMAGE.	Null	
Null	Null	
OTHER PRECAUTIONS:	Null	
1. STORE IN ACCORDANCE WITH ANSI B7, 1-1978.	Null	
2. RESPIRATORY PROTECTION MAY BE REQUIRED IN EXTREMELY DUSTY ENVIRONMENT.	Null	
SEE ANSI 243.1 FOR ADDITIONAL RECOMMENDATIONS.	Null	
3. USE IN ACCORDANCE WITH INSTRUCTIONS PACKED WITH WHEELS.	Null	
Null	Null	
SECTION VIII - CONTROL MEASURES	Null	
	Null	
RESPIRATORY PROTECTION (SPECIFY TYPE): DUST RESPIRATORS APPROVED BY NATIONAL	Null	
INSTITUTE OF SAFETY AND HEALTH MAY BE REQUIRED.	Null	
Null	I	
<b>▼</b> (1)		