

## 1. COMPANY AND PRODUCT IDENTIFICATION

DUNCAN ENTERPRISES

EMERGENCY TELEPHONE NUMBERS

5673 East Shields Avenue Fresno, CA 93727

Health Emergency: 559-291-4444 7:00 am – 3:30 pm Pacific Standard Time

**559-291-4444** Spill and Off-Hour

**559-291-9444 (Fax)** Health Emergencies: 800-424-9300 U.S. and Canada

703-527-3887 Outside U.S. and

Canada (Collect)

Product Name: DUNCAN OA 901 ESSENCE
Product Category: Solvent - Based Extender

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

<b>Hazardous Components</b>	<b>OSHA PEL</b>	<b>ACGIH TLV</b>	CAS#	%
Camphor	2 ppm	2 ppm	76-22-2	15-20
Cyclohexanone	50 ppm	25 ppm	108-94-1	20-25
*o-Dichlorobenzene	50 ppm (C)	25 ppm	95-50-1	25-30
Stoddard Solvent	500 ppm	100 ppm	8052-41-3	20-25

Other Information
(C) Ceiling Limit Value
\*Withheld as a trade secret.

## 3. HAZARDS IDENTIFICATION

#### **HMIS Hazard Ratings for Product**

Health:3\*0 = MinimalFlammability:41 = SlightReactivity:02 = ModeratePersonal Protection:See Section 83 = Serious

4 = Severe \* = Chronic Effects

#### **Routes of Exposure**

Exposure may be by inhalation and / or skin or eye contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

#### **Effects of Overexposure**

Irritation of eyes, skin, and upper respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

# Signs and Symptoms of Overexposure

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

## **Cancer Information**

For complete discussion of toxicology data refer to Section 11.

# Page 1 of 5 **Duncan Enterprises Material Safety Data Sheet – OA 901 Essence**

#### 4. FIRST AID MEASURES

**Eye contact:** Flush with water at least 15 minutes, and contact physician immediately.

**Skin contact:** Wash with soap and water. Remove contaminated clothing and shoes. Wash or

clean before reuse.

**Inhalation:** Remove from exposure to fresh air. Give artificial respiration if not breathing.

If breathing is difficult, give oxygen. Contact a physician immediately.

Ingestion: Give milk or water. Do not give anything to an unconscious person. Induce

vomiting. Contact a physician immediately.

#### 5. FIRE FIGHTING MEASURES

Flash Point: 108°F (Setaflash Closed Cup)
Flammable Limits LEL: N/A UEL: N/A

**Extinguishing Media** 

CO<sub>2</sub>, dry chemical or Chemical Foam. **Do not use water jet.** 

**Special Fire Fighting Procedures** 

Fire Fighters should wear NIOSH/MSHA approved pressure demand self-contained breathing apparatus.

**Unusual Fire And Explosion Hazards** Toxic fumes may be evolved in a fire.

#### **6. ACCIDENTAL RELEASE MEASURES**

## Steps To Be Taken In Case Material Is Released Or Spilled

Promptly absorb spill using inert materials such as sand, vermiculite or sawdust. Remove all sources of ignition. Cover drains to prevent entry into waterways. If a Reportable Quantity is exceeded for any ingredients, contact the National Response Center.

## 7. HANDLING AND STORAGE

#### **Precautions To Be Taken In Handling And Storing**

Keep away from, open flame, and sources of ignition. Store as flammable liquid. Store in a cool dry place. See Reactivity Section.

#### **Other Precautions**

Follow good industrial hygiene and housekeeping practices. Wash hands before eating, drinking, smoking, or applying cosmetics, and at the end of the work shift. Avoid contact with eyes, skin, or clothing.

#### 8. EXPOSURE CONTROL AND PERSONAL PROTECTION

#### Respiratory Protection (Specify Type)

If there is a possibility that the TLVs or PELs may be exceeded, a NIOSH/MSHA approved respirator with organic vapor cartridge represents the minimum level or respiratory protection. To insure proper respirator selection and use, refer to the requirements of 29 CFR 1910.134 and the latest addition of ANSIZ 88.2.

Ventilation

**Local Exhaust:** Fume hood at point of generation with sufficient exhaust

**Mechanical (General):** Must be sufficient to remove vapors from breathing zone

Protective Gloves: Solvent impermeable gloves
Eye Protection: Safety glasses or goggles

**Other Protective Clothing** 

**Or Equipment:** Eve bath and safety shower.

Work/Hygienic Practices: Wear disposable protective clothing to facilitate recovery of any

materials spilled. Use adequate ventilation.

# Page 2 of 5 **Duncan Enterprises Material Safety Data Sheet – OA 901 Essence**

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Clear yellow liquid with solvent odor

Specific Gravity (Water = 1): < 1
Boiling Point: N/A
Evaporation Rate (butyl acetate = 1): > 1
Melting Point: N/A

Vapor Density (Air = 1): Heavier than air

Vapor Pressure:

Water Solubility, %:

Percent Volatiles by Volume:

PH:

N/A

Immiscible

100%

N/A

#### 10. STABILITY AND REACTIVITY

Stability Unstable: Stable: X

**Conditions To Avoid** 

Avoid heating substance where it may be inhaled, open flames, oxidizers and sources of ignition. Solvent vapors are heavier than air and can accumulate, travel to sources of ignition and flash back.

#### Incompatibility (Materials To Avoid)

Oxidizers such as chlorates, perchlorates, permanganates, and nitrates.

## **Hazardous Decomposition or Byproducts**

Carbon dioxide, carbon monoxide, hydrochloric acid, oxides of sulfur and carbonaceous fumes.

Hazardous Polymerization May Occur: Will Not Occur: X

Conditions To Avoid: N/A

## 11. TOXICOLOGICAL INFORMATION

Routes of Entry

Inhalation: Yes Skin: Yes Ingestion: Yes

**Health Hazards (Acute and Chronic)** 

Short-term liquid or vapor contact may result in slight eye irritation. Prolonged and repeated contact may be more irritating. Prolonged and repeated liquid contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis. Avoid breathing vapor or spray. Solvents can act as central nervous system depressants, exhibiting narcotic and anesthetic effects. Overexposure to some of these components may cause headaches, nausea, vomiting, drowsiness, diarrhea, liver, and kidney damage.

Carcinogenicity NTP: yes IARC Monographs: yes OSHA Regulated: yes

#### 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

#### **Waste Disposal Method**

Return accumulated residues, to refinery for metals recovery. Follow local, state and federal regulations for packaging, labeling, manifesting, transportation and disposal.

#### 14. TRANSPORT INFORMATION

#### **U.S. Department of Transportation Information**

**DOT Shipping Name:** Consumer Commodity ORM-D

DOT Hazard Class: Glazes or Stains OA/OG 88690 Sub. 1

**U.N. Number:** 1950

Page 3 of 5

**Duncan Enterprises Material Safety Data Sheet - OA 901 Essence** 

## 15. REGULATORY INFORMATION

#### **California Proposition 65**

**WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

## **TSCA Certification**

All chemicals in this product are listed, or are exempt from listing, on the TSCA inventory.



Products bearing the Caution Label are certified to be properly labeled in a program of toxicological evaluation by a nationally recognized toxicologist. The products are certified by the toxicologist to be labeled in accordance with the chronic hazard labeling standard ASTM D-4236.

#### 16. OTHER INFORMATION

#### **Table of Abbreviations**

**ACGIH** American Conference of Governmental Industrial Hygienists

ANSI Aboriginal Independent Community Schools
ANSI American National Standards Institute
ASTM American Society for Testing Materials

°C Degrees Centigrade
CAS Chemical Abstract Service

CERCLA Comprehensive Environmental Response, Compensation and Liability Act

CFR Code of Federal Regulations
CPR Controlled Products Regulations
DOT Department of Transportation
DSL Domestic Substances List
ECL Education Counseling Service

**EINECS** European Inventory of Existing Commercial Chemical Substances

ENCS Existing and New Chemical Substances
EPA Environmental Protection Agency

°F Degrees Fahrenheit

**FDA** Food & Drug Administration

**Hg** Mercury

HMIS Hazardous Materials Identification System
IARC International Agency for Research on Cancer

IATA International Air Transport Association
ICAO International Civil Aviation Organization
IMO International Maritime Organization

**LD** Lethal Dose

mg / kg Milligram per kilogram

MITI Ministry of International Trade and Industry

mm Millimeter

MSDS Material Safety Data Sheet

MSHA Mine Safety and Health Administration

N / A Not Applicable

**NFPA** National Fire Protection Association

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

**OSHA** Occupational Safety and Health Administration

Page 4 of 5

#### **Duncan Enterprises Material Safety Data Sheet - OA 901 Essence**

#### 16. OTHER INFORMATION (Continued)

## **Table of Abbreviations (Continued)**

**ppm** Parts per million

**SARA** Superfund Amendment and Reauthorization Act

STELShort-Term Exposure LimitTDGTransport Dangerous GoodsTSCAToxic Substances Control ActTWATime - Weighted Average

**U.N.** United Nations

WHMIS Workplace Hazardous Materials Information System

Greater ThanLess Than

Creation Date: 09/00
Revision Date: 08/08/06
Technical Contact: Candi Prado

Senior R&D Specialist Duncan Enterprises 5673 East Shields Avenue

Fresno, CA 93727 559-291-4444 559-291-9444 (Fax)

#### **Disclaimer**

The information given and the recommendations made herein apply to our product(s) alone and not combined with any other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guarantee of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.