

 Close this window

SDS

Common Name: DUST-OFF COMPRESSED GAS DUSTER**Manufacturer:** FALCON SAFETY PRODUCTS**SDS Revision Date:** 5/15/2018**SDS Format:** GHS-US**Item Number(s):** 1VND6, 2EPX2, 2EPX3, 2EPX4, 2EPX5, 40KJ48, 40KJ49, 40KJ50, 40KJ51, 645W42, 645W44**Manufacturer Model Number(s):**

SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

[SECTION 1: IDENTIFICATION](#)[SECTION 2: HAZARDS IDENTIFICATION](#)[SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS](#)[SECTION 4: FIRST AID MEASURES](#)[SECTION 5: FIREFIGHTING MEASURES](#)[SECTION 6: ACCIDENTAL RELEASE MEASURES](#)[SECTION 7: HANDLING AND STORAGE](#)[SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION](#)[SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES](#)[SECTION 10: STABILITY AND REACTIVITY](#)[SECTION 11: TOXICOLOGICAL INFORMATION](#)[SECTION 12: ECOLOGICAL INFORMATION](#)[SECTION 13: DISPOSAL CONSIDERATIONS](#)[SECTION 14: TRANSPORT INFORMATION](#)[SECTION 15: REGULATORY INFORMATION](#)[SECTION 16: OTHER INFORMATION](#)

FALCON

SAFETY DATA SHEET

DUST-OFF COMPRESSED GAS DUSTER

ACCORDING TO THE HAZARD COMMUNICATION STANDARD (CFR29 1910.1200)
HAZCOM 2012 AND THE HAZARDOUS PRODUCTS REGULATIONS (HPR) WHMIS 2015

DATE OF ISSUE: 10/15/2015

REVISION DATE: 5/15/2018

VERSION: 2.0

SECTION 1: IDENTIFICATION



1.1. PRODUCT IDENTIFIER:

SUBSTANCE NAME: DUST-OFF COMPRESSED GAS DUSTER

PRODUCT CODE:

3.5 OZ., 7 OZ., 10 OZ., PROFESSIONAL 12 OZ., JUMBO 17 OZ., CLASSIC

AND PLUS

1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:

USE OF THE SUBSTANCE/MIXTURE: DUST REMOVAL

1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

FALCON SAFETY PRODUCTS, INC.

25 IMCLONE DRIVE

BRANCHBURG, NJ 08876

USA

T: (908) 707-4900

1.4. EMERGENCY TELEPHONE NUMBER:

EMERGENCY NUMBER: (800) 498-7192

SECTION 2: HAZARDS IDENTIFICATION



GHS-US AND GHS-CA CLASSIFICATION:

FLAM. AEROSOL 2

PRESS. GAS (LIQUIFIED GAS)

2.2. LABEL ELEMENTS:

GHS-US AND GHS-CA LABELLING:

HAZARD PICTOGRAMS (GHS-US/GHS-CA):

GHS02: FLAME

GHS04: GAS CYLINDER

SIGNAL WORD (GHS-US/GHS-CA): WARNING

HAZARD STATEMENTS (GHS-US/GHS-CA):

FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

PRECAUTIONARY STATEMENTS (GHS-US/GHS-CA):

KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING.

DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE.

PRESSURIZED CONTAINER:

DO NOT PIERCE OR BURN, EVEN AFTER USE. PROTECT FROM SUNLIGHT.

DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F.

STORE IN A WELL-VENTILATED PLACE.

2.3. OTHER HAZARDS: DO NOT STORE IN ENCLOSED VEHICLE.

2.4. UNKNOWN ACUTE TOXICITY (GHS US/GHS CA): NOT APPLICABLE.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS



3.1. SUBSTANCE:

NAME	PRODUCT IDENTIFIER	%
1,1-DIFLUOROETHANE	(CAS NO) 75-37-6	100

3.2. MIXTURE: NOT APPLICABLE.

SECTION 4: FIRST AID MEASURES



4.1. DESCRIPTION OF FIRST AID MEASURES:

FIRST-AID MEASURES AFTER INHALATION:

IF BREATHING IS DIFFICULT, REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. GET MEDICAL ADVICE/ATTENTION IF YOU FEEL UNWELL.

FIRST-AID MEASURES AFTER SKIN CONTACT:

IN CASE OF CONTACT, IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING AND SHOES. WASH CLOTHING BEFORE REUSE. CALL A PHYSICIAN IF IRRITATION DEVELOPS AND PERSISTS. MAY CAUSE FROSTBITE.

FIRST-AID MEASURES AFTER EYE CONTACT:

IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER. REMOVE CONTACT LENSES, IF WORN. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

FIRST-AID MEASURES AFTER INGESTION:

IF SWALLOWED, DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET MEDICAL ADVICE/ATTENTION IF YOU FEEL UNWELL.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

SYMPTOMS/INJURIES AFTER INHALATION:

MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CAUSE DROWSINESS, DIZZINESS AND CENTRAL NERVOUS SYSTEM DEPRESSION.

SYMPTOMS/INJURIES AFTER SKIN CONTACT:

MAY CAUSE SKIN IRRITATION. SYMPTOMS MAY INCLUDE REDNESS, DRYING, DEFATTING AND CRACKING OF THE SKIN. MAY CAUSE FROSTBITE ON CONTACT WITH THE LIQUID.

SYMPTOMS/INJURIES AFTER EYE CONTACT:

MAY CAUSE EYE IRRITATION. SYMPTOMS MAY INCLUDE DISCOMFORT OR PAIN, EXCESS BLINKING AND TEAR PRODUCTION, WITH POSSIBLE REDNESS AND SWELLING. MAY CAUSE FROSTBITE ON CONTACT WITH THE LIQUID.

SYMPTOMS/INJURIES AFTER INGESTION: NOT A NORMAL ROUTE OF EXPOSURE.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

SYMPTOMS MAY NOT APPEAR IMMEDIATELY. IN CASE OF ACCIDENT OR IF YOU FEEL UNWELL, SEEK MEDICAL ADVICE IMMEDIATELY (SHOW THE LABEL OR SDS WHERE POSSIBLE).

SECTION 5: FIREFIGHTING MEASURES



5.1. EXTINGUISHING MEDIA:

SUITABLE EXTINGUISHING MEDIA:

WATER SPRAY, WATER FOG, DRY CHEMICAL, ALCOHOL RESISTANT FOAM, CARBON DIOXIDE.

UNSUITABLE EXTINGUISHING MEDIA: NONE KNOWN.

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

FIRE HAZARD:

FLAMMABLE AEROSOL. PRODUCTS OF COMBUSTION MAY INCLUDE, AND ARE NOT LIMITED TO:
OXIDES OF CARBON, HYDROFLUORIC ACID, CARBONYL FLUORIDE.

EXPLOSION HAZARD:

HEAT MAY BUILD PRESSURE, RUPTURING CLOSED CONTAINERS, SPREADING FIRE

AND INCREASING RISK OF BURNS AND INJURIES.

5.3. ADVICE FOR FIREFIGHTERS:

FIREFIGHTING INSTRUCTIONS:

DO NOT FIGHT FIRE WHEN FIRE REACHES EXPLOSIVES. EVACUATE AREA. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL CONSIDERABLE DISTANCE TO AN IGNITION SOURCE AND FLASH BACK TO SOURCE OF VAPORS.

PROTECTION DURING FIREFIGHTING:

KEEP UPWIND OF FIRE. WEAR FULL FIRE FIGHTING TURN-OUT GEAR (FULL BUNKER GEAR) AND RESPIRATORY PROTECTION (SCBA).

SECTION 6: ACCIDENTAL RELEASE MEASURES



6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

GENERAL MEASURES:

USE PERSONAL PROTECTION RECOMMENDED IN SECTION 8. ISOLATE THE HAZARD AREA AND DENY ENTRY TO UNNECESSARY AND UNPROTECTED PERSONNEL. ELIMINATE SOURCES OF IGNITION.

6.2. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

FOR CONTAINMENT:

VENTILATE THE AREA THOROUGHLY, ESPECIALLY LOW LYING AREAS (BASEMENTS, WORKPITS ETC).

METHODS FOR CLEANING UP:

LEAVE THE PRODUCT TO EVAPORATE. PROVIDE VENTILATION.

6.3. REFERENCE TO OTHER SECTIONS:

SEE SECTION 8 FOR FURTHER INFORMATION ON PROTECTIVE CLOTHING AND EQUIPMENT AND SECTION 13 FOR ADVICE ON WASTE DISPOSAL.

SECTION 7: HANDLING AND STORAGE



7.1. PRECAUTIONS FOR SAFE HANDLING:

ADDITIONAL HAZARDS WHEN PROCESSED:

HAZARDOUS WASTE DUE TO POTENTIAL RISK OF EXPLOSION.

PRESSURIZED CONTAINER:

DO NOT PIERCE OR BURN, EVEN AFTER USE. KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.

PRECAUTIONS FOR SAFE HANDLING:

DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE. AVOID CONTACT WITH SKIN AND EYES. AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY. DO NOT SWALLOW. PROVIDE LOCAL EXHAUST OR GENERAL ROOM VENTILATION. WHEN USING DO NOT EAT, DRINK OR SMOKE. PREVENT THE BUILD-UP OF ELECTROSTATIC CHARGE. USE NON-SPARKING TOOLS.

HYGIENE MEASURES:

LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, DRINKING, OR SMOKING.

7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

TECHNICAL MEASURES:

PROPER GROUNDING PROCEDURES TO AVOID STATIC ELECTRICITY SHOULD BE FOLLOWED.

STORAGE CONDITIONS:

KEEP OUT OF THE REACH OF CHILDREN. KEEP CONTAINER DRY AND IN A WELL-VENTILATED PLACE. PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 deg. C/122 deg. F. KEEP IN FIREPROOF PLACE. STORE IN ORIGINAL CONTAINER. DO NOT STORE IN ENCLOSED VEHICLE.

7.3. SPECIFIC END USE(S): NOT AVAILABLE.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. CONTROL PARAMETERS:**

1,1-DIFLUOROETHANE (75-37-6):

ACGIH: NOT APPLICABLE.

OSHA: NOT APPLICABLE.

NIOSH: NOT APPLICABLE.

IDLH: NOT APPLICABLE.

8.2. EXPOSURE CONTROLS:**APPROPRIATE ENGINEERING CONTROLS:**

USE VENTILATION ADEQUATE TO KEEP EXPOSURES (AIRBORNE LEVELS OF DUST, FUME, VAPOR, ETC.) BELOW RECOMMENDED EXPOSURE LIMITS.

HAND PROTECTION: WEAR SUITABLE GLOVES.

EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS.

SKIN AND BODY PROTECTION: WEAR SUITABLE PROTECTIVE CLOTHING.

RESPIRATORY PROTECTION:

IN CASE OF INSUFFICIENT VENTILATION, WEAR SUITABLE RESPIRATORY EQUIPMENT. RESPIRATOR SELECTION MUST BE BASED ON KNOWN OR ANTICIPATED EXPOSURE LEVELS, THE HAZARDS OF THE PRODUCT AND THE SAFE WORKING LIMITS OF THE SELECTED RESPIRATOR.

ENVIRONMENTAL EXPOSURE CONTROLS:

MAINTAIN LEVELS BELOW COMMUNITY ENVIRONMENTAL PROTECTION THRESHOLDS.

OTHER INFORMATION:

DO NOT EAT, SMOKE OR DRINK WHERE MATERIAL IS HANDLED, PROCESSED OR STORED. WASH HANDS CAREFULLY BEFORE EATING OR SMOKING. HANDLE ACCORDING TO ESTABLISHED INDUSTRIAL HYGIENE AND SAFETY PRACTICES.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: GAS

APPEARANCE: CLEAR

COLOR: COLOURLESS

ODOR: SLIGHT, ETHER-LIKE

ODOR THRESHOLD: NO DATA AVAILABLE

PH: NEUTRAL

MELTING POINT: NO DATA AVAILABLE

FREEZING POINT: NO DATA AVAILABLE

BOILING POINT: -13 DEG. F (- 25 DEG. C)

FLASH POINT: <58 DEG. F (<14.4 DEG. C)

RELATIVE EVAPORATION RATE (BUTYL ACETATE=1): NO DATA AVAILABLE

FLAMMABILITY (SOLID, GAS): FLAMMABLE

EXPLOSION LIMITS: 3.9-16.9

EXPLOSIVE PROPERTIES: NO DATA AVAILABLE

OXIDIZING PROPERTIES: NO DATA AVAILABLE

VAPOR PRESSURE: 5960 KPA AT 77 DEG. F (25 DEG. C)

RELATIVE DENSITY: 0.91

RELATIVE VAPOR DENSITY AT 20 DEG. C: 2.4 AT 77 DEG. F (25 DEG. C)

SPECIFIC GRAVITY / DENSITY: 0.9

SOLUBILITY: SLIGHTLY

PARTITION COEFFICIENT N-OCTANOL/WATER: NO DATA AVAILABLE

AUTO-IGNITION TEMPERATURE: NO DATA AVAILABLE

DECOMPOSITION TEMPERATURE: NO DATA AVAILABLE

VISCOSITY: NO DATA AVAILABLE

VISCOSITY, INEMATIC: NO DATA AVAILABLE

VISCOSITY, DYNAMIC: NO DATA AVAILABLE

9.2. OTHER INFORMATION:
NO ADDITIONAL INFORMATION AVAILABLE.

SECTION 10: STABILITY AND REACTIVITY



10.1. REACTIVITY:
NO DANGEROUS REACTION KNOWN UNDER CONDITIONS OF NORMAL USE.

10.2. CHEMICAL STABILITY:
STABLE UNDER NORMAL STORAGE CONDITIONS. FLAMMABLE AEROSOL. CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED. DO NOT PUNCTURE. DO NOT BURN.

10.3. POSSIBILITY OF HAZARDOUS REACTIONS:
NO DANGEROUS REACTION KNOWN UNDER CONDITIONS OF NORMAL USE.

10.4. CONDITIONS TO AVOID:
HEAT. INCOMPATIBLE MATERIALS. SOURCES OF IGNITION. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/ 122 DEG. F.

10.5. INCOMPATIBLE MATERIALS:
ALKALI AND ALKALINE EARTH METALS. POWDERED METALS. POWDERED METALLIC SALTS.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS:
MAY INCLUDE, AND ARE NOT LIMITED TO:
OXIDES OF CARBON, HYDROFLUORIC ACID, CARBONYL FLUORIDE.

SECTION 11: TOXICOLOGICAL INFORMATION



11.1. INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY: NOT CLASSIFIED

DUST OFF COMPRESSED GAS DUSTER:

LD50 ORAL RAT: 1500 MG/KG

LD50 DERMAL RABBIT: NO DATA AVAILABLE

LC50 INHALATION RAT: 64000 PPM

SKIN CORROSION/IRRITATION:

BASED ON AVAILABLE DATA, THE CLASSIFICATION CRITERIA ARE NOT MET.

SERIOUS EYE DAMAGE/IRRITATION:

BASED ON AVAILABLE DATA, THE CLASSIFICATION CRITERIA ARE NOT MET.

RESPIRATORY OR SKIN SENSITIZATION:

BASED ON AVAILABLE DATA, THE CLASSIFICATION CRITERIA ARE NOT MET.

GERM CELL MUTAGENICITY:

BASED ON AVAILABLE DATA, THE CLASSIFICATION CRITERIA ARE NOT MET.

CARCINOGENICITY:

BASED ON AVAILABLE DATA, THE CLASSIFICATION CRITERIA ARE NOT MET.

REPRODUCTIVE TOXICITY:

BASED ON AVAILABLE DATA, THE CLASSIFICATION CRITERIA ARE NOT MET.

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE):

BASED ON AVAILABLE DATA, THE CLASSIFICATION CRITERIA ARE NOT MET.

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE):

BASED ON AVAILABLE DATA, THE CLASSIFICATION CRITERIA ARE NOT MET.

ASPIRATION HAZARD:

BASED ON AVAILABLE DATA, THE CLASSIFICATION CRITERIA ARE NOT MET.

SYMPTOMS/INJURIES AFTER INHALATION:

MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CAUSE DROWSINESS, DIZZINESS AND CENTRAL NERVOUS SYSTEM DEPRESSION.

SYMPTOMS/INJURIES AFTER SKIN CONTACT:

MAY CAUSE SKIN IRRITATION. SYMPTOMS MAY INCLUDE REDNESS, DRYING, DEFATTING AND CRACKING OF THE SKIN. MAY CAUSE FROSTBITE ON CONTACT WITH THE LIQUID.

SYMPTOMS/INJURIES AFTER EYE CONTACT:

MAY CAUSE EYE IRRITATION. SYMPTOMS MAY INCLUDE DISCOMFORT OR PAIN, EXCESS BLINKING AND TEAR PRODUCTION, WITH POSSIBLE REDNESS AND SWELLING. MAY CAUSE FROSTBITE ON CONTACT WITH THE LIQUID.

SYMPTOMS/INJURIES AFTER INGESTION: NOT A NORMAL ROUTE OF EXPOSURE.

SECTION 12: ECOLOGICAL INFORMATION



12.1. TOXICITY:

ECOLOGY - GENERAL:

MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

12.2. PERSISTENCE AND DEGRADABILITY:

DUST OFF COMPRESSED GAS DUSTER:

PERSISTENCE AND DEGRADABILITY: NOT ESTABLISHED.

12.3. BIOACCUMULATIVE POTENTIAL:

DUST OFF COMPRESSED GAS DUSTER:
BIOACCUMULATIVE POTENTIAL: NOT ESTABLISHED.

12.4. MOBILITY IN SOIL: NO ADDITIONAL INFORMATION AVAILABLE.

12.5. OTHER ADVERSE EFFECTS:

EFFECT ON THE GLOBAL WARMING:
NO KNOWN ECOLOGICAL DAMAGE CAUSED BY THIS PRODUCT.

SECTION 13: DISPOSAL CONSIDERATIONS



13.1. WASTE TREATMENT METHODS:

WASTE DISPOSAL RECOMMENDATIONS:
THIS MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE, PROVINCIAL, AND FEDERAL REGULATIONS. THE GENERATION OF WASTE SHOULD BE AVOIDED OR MINIMIZED WHEREVER POSSIBLE. CONTAINER UNDER PRESSURE. DO NOT DRILL OR BURN EVEN AFTER USE.

ADDITIONAL INFORMATION: FLAMMABLE VAPORS MAY ACCUMULATE IN THE CONTAINER.

SECTION 14: TRANSPORT INFORMATION



DEPARTMENT OF TRANSPORTATION (DOT):

IN ACCORDANCE WITH DOT:

UN-NO. (DOT): UN1030

PROPER SHIPPING NAME (DOT): 1,1-DIFLUOROETHANE

TRANSPORT HAZARD CLASS(ES) (DOT): 2.1

HAZARD LABELS (DOT): FLAMMABLE GAS, CLASS/DIVISION 2.1

PACKAGING EXCEPTIONS:

FALCON SAFETY PRODUCTS HAS BEEN GRANTED A DOT SPECIAL PERMIT. A COPY OF DOT SPECIAL PERMIT SP-11516 CAN BE OBTAINED BY CALLING FALCON SAFETY PRODUCTS, INC. AT 908-707-4900.

TRANSPORTATION OF DANGEROUS GOODS (TDG):

IN ACCORDANCE WITH TDG:

UN-NO.(TDG): UN1030

PROPER SHIPPING NAME (TDG): 1,1-DIFLUOROETHANE

CLASS (TDG): 2.1

HAZARD LABELS (TDG): CLASS 2.1, FLAMMABLE GASES

PACKAGING EXCEPTIONS:

TDG CANADA:

FALCON SAFETY PRODUCTS HAS BEEN GRANTED EQUIVALENCY CERTIFICATE SU 9211 (REN. 1) BY THE TCSS, TDGD TO OFFER FOR TRANSPORT BY ROAD, RAIL AND MARINE.

TRANSPORT BY SEA:

UN-NO. (IMDG): UN1030

PROPER SHIPPING NAME (IMDG): 1,1-DIFLUOROETHANE (REFRIGERANT GAS R 152A)

CLASS (IMDG): 2.1

AIR TRANSPORT:

UN-NO. (IATA): UN1030

PROPER SHIPPING NAME (IATA): 1,1-DIFLUOROETHANE

CLASS (IATA): 2.1

ADDITIONAL INFORMATION:

OTHER INFORMATION: NO SUPPLEMENTARY INFORMATION AVAILABLE.

SPECIAL TRANSPORT PRECAUTIONS:

DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

SECTION 15: REGULATORY INFORMATION



15.1. FEDERAL REGULATIONS:

ALL COMPONENTS OF THIS PRODUCT ARE LISTED, OR EXCLUDED FROM LISTING, ON THE UNITED STATES ENVIRONMENTAL PROTECTION AGENCY TOXIC SUBSTANCES CONTROL ACT (TSCA) INVENTORY

1,1-DIFLUOROETHANE (75-37-6):

LISTED ON THE CANADIAN DSL (DOMESTIC SUBSTANCES LIST)

15.2. US STATE REGULATIONS:

DUST OFF COMPRESSED GAS DUSTER:

STATE OR LOCAL REGULATIONS:

THIS PRODUCT DOES NOT CONTAIN A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER,

DUST OFF COMPRESSED GAS DUSTER: BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

SECTION 16: OTHER INFORMATION



DATE OF ISSUE: 10/15/2015

REVISION DATE: 5/15/2018

OTHER INFORMATION: NONE.

MEXICO CLASSIFICATION:

1
4
0

BLUE = HEALTH

RED = FLAMMABILITY

YELLOW = REACTIVITY

WHITE = SPECIAL

HAZARD RATING:

0 = MINIMAL
1 = SLIGHT
2 = MODERATE
3 = SEVERE
4 = EXTREME

DISCLAIMER:

WE BELIEVE THE STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE RELIABLE, BUT THEY ARE GIVEN WITHOUT WARRANTY OR GUARANTEE OF ANY KIND. THE INFORMATION CONTAINED IN THIS DOCUMENT APPLIES TO THIS SPECIFIC MATERIAL AS SUPPLIED. IT MAY NOT BE VALID FOR THIS MATERIAL IF IT IS USED IN COMBINATION WITH ANY OTHER MATERIALS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR THE USER'S OWN PARTICULAR USE.

EN (ENGLISH US)