

W I T C O MATERIAL SAFETY DATA SHEET

KENDALL HYKEN GOLDEN HYDRAULIC FLUID

Product Code: H42 7354

PAGE 1

HAZARD RATING
 N 4 - Extreme
 F 3 - High
 P 2 - Moderate
 A 1 - Slight
 0 - Insignificant

Fire
 Toxicity
 Reactivity

1	0
1	0

DIVISION AND LOCATION---SECTION I

Division: KENDALL REFINING COMPANY

Location:

77 N. KENDALL AVE., BRADFORD, PA, 16701

Emergency Telephone Number: (814) 368-6111

Transportation Emergency: CHEM TREC 1-(800) 424-9300 (U.S. and Canada)

CHEMICAL AND PHYSICAL PROPERTIES---SECTION II

Chemical Name:

petroleum hydrocarbon plus additives

Formula: not applicable

Hazardous Decomposition Products:

carbon monoxide and carbon dioxide from burning.
 oxides of phosphorous from burning
 oxides of sulfur

Compatibility (Keep away from):

strong oxidizers such as hydrogen peroxide, bromine, and chromic acid.

Toxic and Hazardous Ingredients:

none

Form: liquid

Odor: bland

Appearance: liquid

Color: straw

Specific Gravity (water=1): .86

Boiling Point: greater than 330°C (625°F)

Melting Point: less than -37°C (-35°F)

Solubility in Water (by weight %): 0 at 20°C

Volatile (by weight %): 0

Evaporation Rate: 0

Vapor Pressure (mm Hg at 20°C): 0

Vapor Density (air=1): not volatile

(as is): not applicable

Stability: Product is stable under normal conditions

Acidity SUS at 100°F: Greater than or = to 100

RE AND EXPLOSION DATA---SECTION III

Special Fire Fighting Procedures:

Do not use water except as fog

Usual Fire and Explosion Hazards:

none

(Continued on next page)

PAGE 2 IS
 MISSING

DALL HYKEN GOLDEN HYDRAULIC FLUID

PAGE 3

Product Code: H42 7354

SPECIAL PRECAUTIONS---SECTION VII

Precautions to be taken in handling and storage:

Do not handle or store at temperatures over
Maximum Storage Temperature: 38°C (100°F)

TRANSPORTATION DATA---SECTION VIII

O.T.: Not RegulatedPortable Quantity: not applicableWeight Classification: Petroleum Lubricating OilSpecial Transportation Notes:

none

REMARKS---SECTION IX

used in applications where a mist may be generated, observe a TWA/PEL of 5
/m3 for mineral oil mist (OSHA and ACGIH).

Signature: Luther DromgoldTitle: Manager, New ProductsOriginal Date: 08/28/81 Sent to:Revision Date: 01/28/87Revised By: 06/20/86Date Sent:

believe the statements, technical information and recommendations contained herein
are reliable, but they are given without warranty or guarantee of any kind, express
implied, and we assume no responsibility for any loss, damage, or expense, direct
consequential, arising out of their use.