

MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Labels must be consulted for specific hazard contents.

SAFETEC OF AMERICA

HMIS HAZARD RATING

HEALTH	0	0 = INSIGNIFICANT	3 = HIGH
FLAMMABILITY	1	1 = SLIGHT	4 = EXTREME
REACTIVITY	0	2 = MODERATE	

TRANSPORTATION INFORMATION

PROPER SHIPPING NAME	Safetec Antibiotic Ointment		
HAZARD CLASS/PKG. GRP.	Not Applicable	REF.	Not Applicable
IDENTIFICATION NUMBER	Not Applicable	LABEL	None Required Ground

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)

Page 1 of 2

Safetec Antibiotic Ointment with Bacitracin

MANUFACTURER'S NAME

Safetec of America, Inc.

EMERGENCY TELEPHONE NUMBER (24 Hours)

(800) 255-3924

ADDRESS (NUMBER, STREET, P.O. BOX)

887 Kensington Ave.

TELEPHONE NUMBER FOR INFORMATION

(716) 895-1822

(CITY, STATE AND ZIP CODE)

Buffalo, NY 14215

DATE PREPARED

September 1, 2010

SUPERSEDES

January 27, 2009

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (wt.) (OPTIONAL)	ACGIH TLV/TWA/STEL	
			PPM	MG/M ³
Petrolatum USP	8009-03-8	Proprietary	None Established	None Established
Bacitracin Zinc USP	1405-89-6	Prop'	None Established	None Established

This product is not known to contain a substance subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR 372 at or above minimal amounts.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES
SKIN: May cause irritation. May cause skin discoloration. May cause reddening of the skin.	Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If material is hot, submerge injured area in cold water. If victim is severely burned, remove to a hospital immediately.
INHALATION: This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product.	If vapor or mist is generated when the material is heated or handled, remove victim from exposure.
EYES: This product is minimally irritating to the eyes upon direct contact.	Immediately flush eyes with copious amounts of water for at least 15 minutes or until irritation subsides. If material is hot, treat for thermal burns and take victim to hospital immediately.
INGESTION: DO NOT INGEST. This product is practically non-toxic by ingestion. Laxative properties may result in abdominal cramps and diarrhea.	Do not induce vomiting due to aspiration hazard. If vomiting should occur, lower head below knees to avoid aspiration.

HEALTH HAZARDS (ACUTE AND CHRONIC):

Acute: May induce a dermal reaction in sensitive individuals. Chronic: Repeated or prolonged exposure may cause allergic reaction in susceptible individuals. Repeated or prolonged exposure may produce chronic eye irritation. Ingestion of product in large quantities may produce a mild laxative effect. Repeated or prolonged inhalation can cause lipid pneumonia or lipid granuloma of the lung.

CARCINOGENICITY

No additional information

NTP?

No

IARC MONOGRAPHS?

No

OSHA REGULATED?

No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: May cause hypersensitivity.

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)

Safetec Antibiotic Ointment with Bacitracin

Page 2 of 2

Date: January 27, 2009

SECTION 4 - FIRE FIGHTING MEASURES**FLASH POINT (METHOD USED)**

Higher than 93.3°C (200°F) closed cup

FLAMMABLE LIMITS (% Volume in Air for Lowest Flashing Component)

LEL: Not Available

UEL: Not Available

EXTINGUISHING MEDIA

Use dry chemical, foam, or carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES

Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS

Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

SECTION 5 - PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES**STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED**

Contain spill immediately. Do not allow spill to enter sewers or watercourses. Small spills: Absorb with appropriate inert material such as sand, clay, etc. and dispose of into a suitable container. Large spills: Large spills can be picked up using vacuum pumps, shovels, buckets, or other means and placed in drums or other suitable containers.

WASTE DISPOSAL METHODS

Dispose of in accordance with Local, State, and Federal regulations. Products classified as non-hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260-299" for complete waste disposal regulations. Consult your Local, State, or Federal Environmental Protection Agency before disposing of any chemicals.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Handling: Avoid breathing vapors or mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Wash clothing prior to reuse. May be slippery when spilled. Storage: Do not transfer to unmarked containers. Store in closed containers away from heat, sparks, open flame, or oxidizing materials.

SECTION 6 - EXPOSURE CONTROLS/PERSONAL PROTECTION**RESPIRATORY PROTECTION**

Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified.

VENTILATION

LOCAL EXHAUST: Recommended

MECHANICAL (GENERAL): Not required

PROTECTIVE GLOVES

For prolonged or repeated exposures, use impervious gloves. If handling hot material use insulated protective gloves.

EYE PROTECTION

Not required for normal use. If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT**WORK/HYGIENIC PRACTICES**

Eye wash stations should be nearby and ready for use.

Consumption of food and beverage should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, or smoking.

SECTION 7 - PHYSICAL/CHEMICAL PROPERTIES**BOILING POINT**

343°C (650°F)

SPECIFIC GRAVITY (WATER = 1)

0.86-0.87

VAPOR PRESSURE (mm Hg)

No data

MELTING POINT

51.7-54.4°C (125-130°F)

VAPOR DENSITY (AIR = 1)

No data

pH (1% solution in water)

No data

SOLUBILITY IN WATER

Insoluble

EVAPORATION RATE (IPA = 1)

No data

APPEARANCE AND ODOR

White to off-white ointment

% VOLATILES (BY VOLUME)

No data

SECTION 8 - STABILITY AND REACTIVITY**STABILITY**

UNSTABLE:

STABLE: XXX

CONDITIONS TO AVOID

Heat and oxidizing

INCOMPATIBILITIES (MATERIALS TO AVOID)

Extreme heat, sparks, open flame and oxidizers.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

May give off fumes of carbon monoxide and carbon dioxide and other oxides generated during combustion.

HAZARDOUS POLYMERIZATION MAY OCCUR:

WILL NOT OCCUR: XXX

CONDITIONS TO AVOID

Temperatures above 300°C

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.