

☒ Close this window

SDS

**Common Name:** SUPER LUBE DRI-FILM AEROSOL WITH SYNCOLON (PTFE)**Manufacturer:** SYNCO CHEMICAL**SDS Revision Date:** 2/10/2016**SDS Format:** GHS-US**Grainger Item Number(s):** 44N743, 45NA63**Manufacturer Model Number(s):****SDS Table of Contents**

Click the desired link below to jump directly to that section in the SDS.

- [1 IDENTIFICATION](#)
- [2 HAZARD\(S\) IDENTIFICATION](#)
- [3 COMPOSITION/INFORMATION ON INGREDIENTS](#)
- [4 FIRST-AID MEASURES](#)
- [5 FIRE-FIGHTING MEASURES](#)
- [6 ACCIDENTAL RELEASE MEASURES](#)
- [7 HANDLING AND STORAGE](#)
- [8 EXPOSURE CONTROLS/PERSONAL PROTECTION](#)
- [9 PHYSICAL AND CHEMICAL PROPERTIES](#)
- [10 STABILITY AND REACTIVITY](#)
- [11 TOXICOLOGICAL INFORMATION](#)
- [12 ECOLOGICAL INFORMATION](#)
- [13 DISPOSAL CONSIDERATIONS](#)
- [14 TRANSPORT INFORMATION](#)
- [15 REGULATORY INFORMATION](#)
- [16 OTHER INFORMATION](#)

SYNCO (R\*)

SUPER LUBE (R\*)

SAFETY DATA SHEET

ACCORDING TO (EU) 2015 / 830 AND OSHA GHS

REVISION: FEBRUARY 10, 2016

**1 IDENTIFICATION**

PRODUCT IDENTIFIER:

TRADE NAME: SUPER LUBE (R\*) DRI-FILM AEROSOL WITH SYNCOLON (R\*) (PTFE)

ARTICLE NUMBER: NO OTHER IDENTIFIERS

RECOMMENDED USE AND RESTRICTION ON USE:

RECOMMENDED USE: LUBRICANT

RESTRICTIONS ON USE: SEE SECTIONS 8 AND 10 FOR FURTHER INFORMATION.

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

MANUFACTURER/SUPPLIER:

SYNCO CHEMICAL CORPORATION  
24 DAVINCI DR.  
P.O. BOX 405  
BOHEMIA, NY 11716

TELEPHONE: 631-567-5300

EMAIL: INFO@SUPER-LUBE.COM

INFORMATION DEPARTMENT: PRODUCT SAFETY DEPARTMENT

EMERGENCY TELEPHONE NUMBER:

CHEMTREC:  
1-800-424-9300 (US/CANADA)  
+01 703-527-3887 (INTERNATIONAL)

## 2 HAZARD(S) IDENTIFICATION



CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

GHS02: FLAME  
GHS04: GAS CYLINDER

FLAM. AEROSOL 1:  
H222: EXTREMELY FLAMMABLE AEROSOL.

GHS04: GAS CYLINDER

PRESS. GAS:  
H280: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

GHS08: HEALTH HAZARD

REPR. 2:  
H361: SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

STOT RE 2:  
H373:  
MAY CAUSE DAMAGE TO THE NERVOUS SYSTEM THROUGH PROLONGED OR REPEATED EXPOSURE.

ROUTE OF EXPOSURE: INHALATIVE.

ASP. TOX. 1:  
H304: MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

GHS07: EXCLAMATION MARK

SKIN IRRIT. 2:  
H315: CAUSES SKIN IRRITATION.

STOT SE 3:  
H336: MAY CAUSE DROWSINESS OR DIZZINESS.

ADDITIONAL INFORMATION:  
THERE ARE NO OTHER HAZARDS NOT OTHERWISE CLASSIFIED THAT HAVE BEEN IDENTIFIED.

0 PERCENT OF THE MIXTURE CONSISTS OF INGREDIENT(S) OF UNKNOWN TOXICITY.

LABEL ELEMENTS:

GHS LABEL ELEMENTS:  
THE PRODUCT IS CLASSIFIED AND LABELED ACCORDING TO THE GLOBALLY HARMONIZED SYSTEM (GHS).

HAZARD PICTOGRAMS:

GHS02: FLAME  
GHS04: GAS CYLINDER  
GHS07: EXCLAMATION MARK  
GHS08: HEALTH HAZARD

SIGNAL WORD: DANGER

HAZARD-DETERMINING COMPONENTS OF LABELING: N-HEXANE

HAZARD STATEMENTS:

H222: EXTREMELY FLAMMABLE AEROSOL.

H280: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

H315: CAUSES SKIN IRRITATION.

H361: SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

H336: MAY CAUSE DROWSINESS OR DIZZINESS.

H373:

MAY CAUSE DAMAGE TO THE NERVOUS SYSTEM THROUGH PROLONGED OR REPEATED EXPOSURE.

ROUTE OF EXPOSURE: INHALATIVE.

H304: MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

PRECAUTIONARY STATEMENTS:

P210:

KEEP AWAY FROM HEAT, SPARKS, OPEN FLAMES, AND HOT SURFACES. - NO SMOKING.

P251:

PRESSURIZED CONTAINER: DO NOT PIERCE OR BURN, EVEN AFTER USE.

P260: DO NOT BREATHE MIST/VAPOURS/SPRAY.

P211: DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE.

P280: WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION.

P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

P201: OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.

P202:

DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

P304+P340:

IF INHALED:

REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING.

P312: CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL.

P331: DO NOT INDUCE VOMITING.

P302+P352:

IF ON SKIN: WASH WITH PLENTY OF WATER.

P362+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH IT BEFORE REUSE.

P410+P412:

PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 122 DEG. F (50 DEG. C).

P403+P233: STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

P501:

DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH LOCAL/REGIONAL/NATIONAL/

## INTERNATIONAL REGULATIONS.

## HAZARD DESCRIPTION:

## WHMIS-SYMBOLS:

A - COMPRESSED GAS

B5 - FLAMMABLE AEROSOL

D2A - VERY TOXIC MATERIAL CAUSING OTHER TOXIC EFFECTS

## CLASSIFICATION SYSTEM:

## NFPA RATINGS (SCALE 0 - 4):

HEALTH 2

FIRE 4

REACTIVITY 3

## HMIS-RATINGS (SCALE 0 - 4):

HEALTH 2\*

FIRE 4

REACTIVITY 3

\* - INDICATES A LONG TERM HEALTH HAZARD FROM REPEATED OR PROLONGED EXPOSURES.

## OTHER HAZARDS:

## RESULTS OF PBT AND VPVB ASSESSMENT:

PBT: NOT APPLICABLE.

VPVB: NOT APPLICABLE.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

## CHEMICAL CHARACTERIZATION: MIXTURES

## DESCRIPTION:

MIXTURE OF THE SUBSTANCES LISTED BELOW WITH NONHAZARDOUS ADDITIONS.

## DANGEROUS COMPONENTS:

110-54-3	N-HEXANE FLAM. LIQ. 2, H225  REPR. 2, H361 STOT RE 2, H373 ASP. TOX. 1, H304  SKIN IRRIT. 2, H315 STOT SE 3, H336	25-50%
74-98-6	PROPANE FLAM. GAS 1, H220 PRESS. GAS, H280	25-50%
106-97-8	BUTANE FLAM. GAS 1, H220 PRESS. GAS, H280	25-50%
124-38-9	CARBON DIOXIDE PRESS. GAS, H280	2.5-10%

## ADDITIONAL INFORMATION:

FOR THE LISTED INGREDIENTS, THE IDENTITY AND EXACT PERCENTAGES ARE BEING WITHHELD AS A TRADE SECRET.

**4 FIRST-AID MEASURES**

## DESCRIPTION OF FIRST AID MEASURES:

## GENERAL INFORMATION:

TAKE AFFECTED PERSONS OUT INTO THE FRESH AIR.

IMMEDIATELY REMOVE ANY CLOTHING SOILED BY THE PRODUCT.

SYMPTOMS OF POISONING MAY EVEN OCCUR AFTER SEVERAL HOURS; THEREFORE MEDICAL OBSERVATION FOR AT LEAST 48 HOURS AFTER THE ACCIDENT.

## AFTER INHALATION:

SUPPLY FRESH AIR; CONSULT DOCTOR IN CASE OF COMPLAINTS.

PROVIDE OXYGEN TREATMENT IF AFFECTED PERSON HAS DIFFICULTY BREATHING.

IN CASE OF UNCONSCIOUSNESS PLACE PATIENT STABLY IN SIDE POSITION FOR TRANSPORTATION.

## AFTER SKIN CONTACT:

IMMEDIATELY WASH WITH WATER AND SOAP AND RINSE THOROUGHLY.

IF SKIN IRRITATION CONTINUES, CONSULT A DOCTOR.

IN CASES OF FROSTBITE, RINSE WITH PLENTY OF WATER. DO NOT REMOVE CLOTHING.

## AFTER EYE CONTACT:

REMOVE CONTACT LENSES IF WORN.

RINSE OPENED EYE FOR SEVERAL MINUTES UNDER RUNNING WATER. IF SYMPTOMS PERSIST, CONSULT A DOCTOR.

## AFTER SWALLOWING:

UNLIKELY ROUTE OF EXPOSURE.

RINSE OUT MOUTH AND THEN DRINK PLENTY OF WATER.

DO NOT INDUCE VOMITING; IMMEDIATELY CALL FOR MEDICAL HELP.

A PERSON VOMITING WHILE LYING ON THEIR BACK SHOULD BE TURNED ONTO THEIR SIDE.

## INFORMATION FOR DOCTOR:

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

HEADACHE

BREATHING DIFFICULTY

FROSTBITE

DIZZINESS

COUGHING

IRRITANT TO SKIN AND MUCOUS MEMBRANES.

SLIGHT IRRITANT EFFECT ON EYES.

## DANGER:

VAPORS HAVE NARCOTIC EFFECT.

DANGER OF DISTURBED CARDIAC RHYTHM.

CONDITION MAY DETERIORATE WITH ALCOHOL CONSUMPTION.

DANGER OF IMPAIRED BREATHING.

MAY CAUSE NEUROTOXIC EFFECTS.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

## INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

LATER OBSERVATION FOR PNEUMONIA AND PULMONARY EDEMA.

TREAT FROST-BITTEN AREAS APPROPRIATELY.

IF SWALLOWED OR IN CASE OF VOMITING, DANGER OF ENTERING THE LUNGS.

MEDICAL SUPERVISION FOR AT LEAST 48 HOURS.

IF NECESSARY OXYGEN RESPIRATION TREATMENT.

**5 FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA:****SUITABLE EXTINGUISHING AGENTS:**

ALCOHOL RESISTANT FOAM

CARBON DIOXIDE

FIRE-EXTINGUISHING POWDER

GASEOUS EXTINGUISHING AGENTS

FOR SAFETY REASONS UNSUITABLE EXTINGUISHING AGENTS: WATER

**SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:**

FORMATION OF TOXIC GASES IS POSSIBLE DURING HEATING OR IN CASE OF FIRE.

DANGER OF RECEPTACLES BURSTING BECAUSE OF HIGH VAPOR PRESSURE IF HEATED.

**ADVICE FOR FIREFIGHTERS:****PROTECTIVE EQUIPMENT:**

WEAR SELF-CONTAINED RESPIRATORY PROTECTIVE DEVICE.

WEAR FULLY PROTECTIVE SUIT.

**ADDITIONAL INFORMATION:**

ELIMINATE ALL IGNITION SOURCES IF SAFE TO DO SO.

COOL ENDANGERED RECEPTACLES WITH WATER FOG.

LEAKING GAS FIRE: DO NOT EXTINGUISH, UNLESS LEAK CAN BE STOPPED SAFELY.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:**USE RESPIRATORY PROTECTIVE DEVICE AGAINST THE EFFECTS OF  
FUMES/DUST/AEROSOL.

ENSURE ADEQUATE VENTILATION.

WEAR PROTECTIVE EQUIPMENT. KEEP UNPROTECTED PERSONS AWAY.

KEEP AWAY FROM IGNITION SOURCES.

PROTECT FROM HEAT.

**ENVIRONMENTAL PRECAUTIONS:**

DO NOT ALLOW PRODUCT TO REACH SEWAGE SYSTEM OR ANY WATER COURSE.

INFORM RESPECTIVE AUTHORITIES IN CASE OF SEEPAGE INTO WATER COURSE OR  
SEWAGE SYSTEM.**METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:**

ALLOW TO EVAPORATE.

ABSORB WITH NON-COMBUSTIBLE LIQUID-BINDING MATERIAL (SAND, DIATOMITE, ACID  
BINDERS, UNIVERSAL BINDERS).

SEND FOR RECOVERY OR DISPOSAL IN SUITABLE RECEPTACLES.

DISPOSE CONTAMINATED MATERIAL AS WASTE ACCORDING TO ITEM 13.

**REFERENCE TO OTHER SECTIONS:**

SEE SECTION 7 FOR INFORMATION ON SAFE HANDLING.

SEE SECTION 8 FOR INFORMATION ON PERSONAL PROTECTION EQUIPMENT.

SEE SECTION 13 FOR DISPOSAL INFORMATION.

**7 HANDLING AND STORAGE****HANDLING:**

PRECAUTIONS FOR SAFE HANDLING:  
OPEN AND HANDLE RECEPTACLE WITH CARE.  
USE ONLY IN WELL VENTILATED AREAS.  
KEEP AWAY FROM HEAT AND DIRECT SUNLIGHT.

INFORMATION ABOUT PROTECTION AGAINST EXPLOSIONS AND FIRES:  
DO NOT SPRAY ON A NAKED FLAME OR ANY INCANDESCENT MATERIAL.

KEEP IGNITION SOURCES AWAY - DO NOT SMOKE.

PRESSURIZED CONTAINER:  
PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING  
120 DEG. F / 49 DEG. C, I.E. ELECTRIC LIGHTS. DO NOT PIERCE OR BURN, EVEN  
AFTER USE.

EMERGENCY COOLING MUST BE AVAILABLE IN CASE OF NEARBY FIRE.

KEEP RESPIRATORY PROTECTIVE DEVICE AVAILABLE.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

STORAGE:

REQUIREMENTS TO BE MET BY STOREROOMS AND RECEPTACLES:  
STORE IN A COOL LOCATION.

OBSERVE OFFICIAL REGULATIONS ON STORING PACKAGINGS WITH PRESSURIZED  
CONTAINERS.

AVOID STORAGE NEAR EXTREME HEAT, IGNITION SOURCES OR OPEN FLAME.

INFORMATION ABOUT STORAGE IN ONE COMMON STORAGE FACILITY:  
STORE AWAY FROM FOODSTUFFS.  
STORE AWAY FROM OXIDIZING AGENTS.

FURTHER INFORMATION ABOUT STORAGE CONDITIONS:  
STORE IN A COOL PLACE. HEAT WILL INCREASE PRESSURE AND MAY LEAD TO THE  
RECEPTACLE BURSTING.

PROTECT FROM HEAT AND DIRECT SUNLIGHT.

STORAGE TEMPERATURES: <122 DEG. F / <50 DEG. C.

SPECIFIC END USE(S): NO FURTHER RELEVANT INFORMATION AVAILABLE.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION



ADDITIONAL INFORMATION ABOUT DESIGN OF TECHNICAL SYSTEMS:  
NO FURTHER DATA; SEE ITEM 7.

CONTROL PARAMETERS:

COMPONENTS WITH LIMIT VALUES THAT REQUIRE MONITORING AT THE WORKPLACE:

110-54-3 N-HEXANE:  
PEL (USA):  
LONG-TERM VALUE: 1800 MG/M3, 500 PPM

REL (USA):  
LONG-TERM VALUE: 180 MG/M3, 50 PPM

TLV (USA):  
LONG-TERM VALUE: 176 MG/M3, 50 PPM  
SKIN; BEI

EL (CANADA):  
LONG-TERM VALUE: 20 PPM SKIN

EV (CANADA):

LONG-TERM VALUE: 176 MG/M3, 50 PPM

LMPE (MEXICO):

LONG-TERM VALUE: 50 PPM

PIEL, IBE

74-98-6 PROPANE:

REL (USA):

LONG-TERM VALUE: 1800 MG/M3, 1000 PPM

REL (USA):

LONG-TERM VALUE: 1800 MG/M3, 1000 PPM

TLV (USA): REFER TO APPENDIX F

EL (CANADA):

LONG-TERM VALUE: 1000 PPM

EV (CANADA):

LONG-TERM VALUE: 1.000 PPM

LMPE (MEXICO):

LONG-TERM VALUE: 1000 PPM

106-97-8 BUTANE:

REL (USA):

LONG-TERM VALUE: 1900 MG/M3, 800 PPM

TLV (USA):

SHORT-TERM VALUE: 2370 MG/M3, 1000 PPM

EL (CANADA):

SHORT-TERM VALUE: 750 PPM

LONG-TERM VALUE: 600 PPM

EV (CANADA):

LONG-TERM VALUE: 800 PPM

LMPE (MEXICO):

LONG-TERM VALUE: 1000 PPM

124-38-9 CARBON DIOXIDE:

REL (USA):

LONG-TERM VALUE: 9000 MG/M3, 5000 PPM

REL (USA):

SHORT-TERM VALUE: 54.000 MG/M3, 30.000 PPM

LONG-TERM VALUE: 9000 MG/M3, 5000 PPM

TLV (USA):

SHORT-TERM VALUE: 54.000 MG/M3, 30.000 PPM

LONG-TERM VALUE: 9000 MG/M3, 5000 PPM

EL (CANADA):

SHORT-TERM VALUE: 15000 PPM

LONG-TERM VALUE: 5000 PPM

EV (CANADA):

SHORT-TERM VALUE: 54.000 MG/M3, 30.000 PPM

LONG-TERM VALUE: 9.000 MG/M3, 5.000 PPM

LMPE (MEXICO):

SHORT-TERM VALUE: 30000 PPM

LONG-TERM VALUE: 5000 PPM

INGREDIENTS WITH BIOLOGICAL LIMIT VALUES:

110-54-3 N-HEXANE:



BEI (USA):  
0.4 MG/L  
MEDIUM: URINE  
TIME: END OF SHIFT AT END OF WORKWEEK  
PARAMETER: 2.5-HEXANEDIONE WITHOUT HYDROLYSIS

ADDITIONAL INFORMATION:  
THE LISTS THAT WERE VALID DURING THE CREATION WERE USED AS BASIS.

EXPOSURE CONTROLS:

PERSONAL PROTECTIVE EQUIPMENT:

GENERAL PROTECTIVE AND HYGIENIC MEASURES:  
THE USUAL PRECAUTIONARY MEASURES FOR HANDLING CHEMICALS SHOULD BE FOLLOWED.  
KEEP AWAY FROM FOODSTUFFS, BEVERAGES AND FEED.  
IMMEDIATELY REMOVE ALL SOILED AND CONTAMINATED CLOTHING.  
WASH HANDS BEFORE BREAKS AND AT THE END OF WORK.  
DO NOT INHALE GASES / FUMES / AEROSOLS.  
AVOID CONTACT WITH THE EYES AND SKIN.  
PREGNANT WOMEN SHOULD STRICTLY AVOID INHALATION OR SKIN CONTACT.

ENGINEERING CONTROLS: NO FURTHER RELEVANT INFORMATION AVAILABLE.

BREATHING EQUIPMENT:  
WEAR APPROPRIATE NIOSH RESPIRATOR WHEN VENTILATION IS INADEQUATE AND  
OCCUPATIONAL EXPOSURE LIMITS ARE EXCEEDED.

USE SUITABLE RESPIRATORY PROTECTIVE DEVICE IN CASE OF INSUFFICIENT  
VENTILATION.

PROTECTION OF HANDS: PROTECTIVE GLOVES

THE GLOVE MATERIAL HAS TO BE IMPERMEABLE AND RESISTANT TO THE PRODUCT/THE  
SUBSTANCE/THE PREPARATION. SELECTION OF THE GLOVE MATERIAL ON CONSIDERATION  
OF THE PENETRATION TIMES, RATES OF DIFFUSION AND THE DEGRADATION

MATERIAL OF GLOVES:  
THE SELECTION OF THE SUITABLE GLOVES DOES NOT ONLY DEPEND ON THE MATERIAL,  
BUT ALSO ON FURTHER MARKS OF QUALITY AND VARIES FROM MANUFACTURER TO  
MANUFACTURER. AS THE PRODUCT IS A PREPARATION OF SEVERAL SUBSTANCES, THE  
RESISTANCE OF THE GLOVE MATERIAL CAN NOT BE CALCULATED IN ADVANCE AND HAS  
THEREFORE TO BE CHECKED PRIOR TO THE APPLICATION.

PENETRATION TIME OF GLOVE MATERIAL:  
THE EXACT BREAK THROUGH TIME HAS TO BE FOUND OUT BY THE MANUFACTURER OF THE  
PROTECTIVE GLOVES AND HAS TO BE OBSERVED.

EYE PROTECTION: SAFETY GLASSES

BODY PROTECTION:  
NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.  
PROTECTION MAY BE REQUIRED FOR SPILLS.

LIMITATION AND SUPERVISION OF EXPOSURE INTO THE ENVIRONMENT:  
AVOID RELEASE TO THE ENVIRONMENT.

## 9 PHYSICAL AND CHEMICAL PROPERTIES



INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

GENERAL INFORMATION:

APPEARANCE:

FORM: AEROSOL

COLOR: TRANSPARENT

ODOR: SOLVENT-LIKE

ODOR THRESHOLD: NOT DETERMINED.

PH-VALUE: NOT DETERMINED.

CHANGE IN CONDITION:

MELTING POINT/MELTING RANGE: NOT APPLICABLE, AS AEROSOL.

BOILING POINT/BOILING RANGE: NOT APPLICABLE, AS AEROSOL.

FLASH POINT: -104 DEG. C (-155 DEG. F) EXTREMELY FLAMMABLE AEROSOL.

FLAMMABILITY (SOLID, GASEOUS): NOT APPLICABLE.

AUTO-IGNITION TEMPERATURE: NOT DETERMINED.

DECOMPOSITION TEMPERATURE: NOT DETERMINED.

AUTO IGNITING: PRODUCT IS NOT SELF-IGNITING.

DANGER OF EXPLOSION:

IN USE, MAY FORM FLAMMABLE/EXPLOSIVE VAPOUR-AIR MIXTURE.

EXPLOSION LIMITS:

LOWER: NOT DETERMINED.

UPPER: NOT DETERMINED.

VAPOR PRESSURE AT 20 DEG. C (68 DEG. F): 5.0-5.5 BAR

DENSITY: NOT DETERMINED.

RELATIVE DENSITY: NOT DETERMINED.

VAPOUR DENSITY: NOT DETERMINED.

EVAPORATION RATE: NOT APPLICABLE.

SOLUBILITY IN / MISCIBILITY WITH WATER: NOT MISCIBLE OR DIFFICULT TO MIX.

PARTITION COEFFICIENT (N-OCTANOL/WATER): NOT DETERMINED.

VISCOSITY:

DYNAMIC: NOT DETERMINED.

KINEMATIC: NOT DETERMINED.

SOLVENT CONTENT:

VOC (CALIFORNIA): EXEMPT

OTHER INFORMATION: NO FURTHER RELEVANT INFORMATION AVAILABLE.

## 10 STABILITY AND REACTIVITY



REACTIVITY:

CHEMICAL STABILITY:

THERMAL DECOMPOSITION / CONDITIONS TO BE AVOIDED:

KEEP AWAY FROM HEAT, SPARKS, OPEN FLAMES, AND HOT SURFACES. - NO SMOKING.

POSSIBILITY OF HAZARDOUS REACTIONS:

EXTREMELY FLAMMABLE AEROSOL.

CAN REACT VIOLENTLY WITH OXYGEN RICH (OXIDIZING) MATERIAL. DANGER OF EXPLOSION.

DEVELOPS READILY FLAMMABLE GASES / FUMES.

DANGER OF RECEPTACLES BURSTING BECAUSE OF HIGH VAPOR PRESSURE IF HEATED.

REACTS WITH PEROXIDES AND OTHER RADICAL FORMING SUBSTANCES.

CAN FORM EXPLOSIVE MIXTURES IN AIR IF HEATED ABOVE FLASH POINT AND/OR WHEN SPRAYED OR ATOMIZED.

CONDITIONS TO AVOID:

KEEP IGNITION SOURCES AWAY - DO NOT SMOKE.

STORE AWAY FROM OXIDIZING AGENTS.

INCOMPATIBLE MATERIALS: OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE AND CARBON DIOXIDE

## 11 TOXICOLOGICAL INFORMATION



INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

LD/LC50 VALUES THAT ARE RELEVANT FOR CLASSIFICATION: NONE.

PRIMARY IRRITANT EFFECT:

ON THE SKIN: IRRITANT TO SKIN AND MUCOUS MEMBRANES.

ON THE EYE: SLIGHT IRRITANT EFFECT ON EYES.

SENSITIZATION: NO SENSITIZING EFFECTS KNOWN.

SUBACUTE TO CHRONIC TOXICITY:

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

MAY CAUSE DAMAGE TO THE NERVOUS SYSTEM THROUGH PROLONGED OR REPEATED EXPOSURE.

ROUTE OF EXPOSURE: INHALATIVE.

ADDITIONAL TOXICOLOGICAL INFORMATION:

INHALATION OF CONCENTRATED VAPORS AS WELL AS ORAL INTAKE WILL LEAD TO ANAESTHESIA-LIKE CONDITIONS AND HEADACHE, DIZZINESS, ETC.

TOXIC AND/OR CORROSIVE EFFECTS MAY BE DELAYED UP TO 24 HOURS.

CARCINOGENIC CATEGORIES:

NTP (NATIONAL TOXICOLOGY PROGRAM): NONE OF THE INGREDIENTS IS LISTED.

OSHA-CA (OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION):

NONE OF THE INGREDIENTS IS LISTED.

PROBABLE ROUTES OF EXPOSURE:

INHALATION.

EYE CONTACT.

SKIN CONTACT.

ACUTE EFFECTS (ACUTE TOXICITY, IRRITATION AND CORROSIVITY):

VAPORS HAVE NARCOTIC EFFECT.

REPEATED DOSE TOXICITY:

MAY CAUSE DAMAGE TO THE NERVOUS SYSTEM THROUGH PROLONGED OR REPEATED EXPOSURE.

ROUTE OF EXPOSURE: INHALATIVE.

**12 ECOLOGICAL INFORMATION**

## TOXICITY:

AQUATIC TOXICITY: TOXIC FOR AQUATIC ORGANISMS

## PERSISTENCE AND DEGRADABILITY:

THE ORGANIC PORTION OF THE PRODUCT IS BIODEGRADABLE.

## BEHAVIOR IN ENVIRONMENTAL SYSTEMS:

BIOACCUMULATIVE POTENTIAL: DOES NOT ACCUMULATE IN ORGANISMS

MOBILITY IN SOIL: NO FURTHER RELEVANT INFORMATION AVAILABLE.

## ECOTOXICAL EFFECTS:

REMARK: TOXIC FOR FISH

## ADDITIONAL ECOLOGICAL INFORMATION:

## GENERAL NOTES:

THIS STATEMENT WAS DEDUCED FROM THE PROPERTIES OF THE SINGLE COMPONENTS.

DO NOT ALLOW PRODUCT TO REACH GROUND WATER, WATER COURSE OR SEWAGE SYSTEM.

DUE TO AVAILABLE DATA ON ELIMINABILITY/DECOMPOSITION AND BIOACCUMULATION  
POTENTIAL PROLONGED TERM DAMAGE OF THE ENVIRONMENT CAN NOT BE EXCLUDED.

## RESULTS OF PBT AND VPVB ASSESSMENT:

PBT: NOT APPLICABLE.

VPVB: NOT APPLICABLE.

OTHER ADVERSE EFFECTS: NO FURTHER RELEVANT INFORMATION AVAILABLE.

**13 DISPOSAL CONSIDERATIONS**

## WASTE TREATMENT METHODS:

## RECOMMENDATION:

CONTACT WASTE PROCESSORS FOR RECYCLING INFORMATION.

THE USER OF THIS MATERIAL HAS THE RESPONSIBILITY TO DISPOSE OF UNUSED  
MATERIAL, RESIDUES AND CONTAINERS IN COMPLIANCE WITH ALL RELEVANT LOCAL,  
STATE AND FEDERAL LAWS AND REGULATIONS REGARDING TREATMENT, STORAGE AND  
DISPOSAL FOR HAZARDOUS AND NONHAZARDOUS WASTES. RESIDUAL MATERIALS SHOULD  
BE TREATED AS HAZARDOUS.

## UNCLEANED PACKAGINGS:

RECOMMENDATION: DISPOSAL MUST BE MADE ACCORDING TO OFFICIAL REGULATIONS.

**14 TRANSPORT INFORMATION**

## UN-NUMBER:

DOT, ADR, IMDG, IATA: UN1950

## UN PROPER SHIPPING NAME:

LIMITED QUANTITY FOR PACKAGES LESS THAN 30 KG (66 LB) AND INNER PACKAGINGS  
LESS THAN 1 L (0.3 GAL).

DOT, IATA: AEROSOLS, FLAMMABLE

ADR: 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

IMDG: AEROSOLS, MARINE POLLUTANT

TRANSPORT HAZARD CLASS(ES):

DOT: FLAMMABLE GAS, CLASS/DIVISION 2.1

CLASS: 2.1

LABEL: 2.1

ADR:

CLASS 2.1, FLAMMABLE GASES

ENVIRONMENT

CLASS: 2 5F GASES

LABEL: 2.1

IMDG:

CLASS 2.1 - FLAMMABLE GASES

ENVIRONMENT

CLASS: 2.1

LABEL: 2.1

IATA: CLASS 2.1, FLAMMABLE GASES

CLASS: 2.1

LABEL: 2.1

PACKING GROUP:

DOT, ADR, IMDG, IATA: NOT REGULATED

ENVIRONMENTAL HAZARDS:

PRODUCT CONTAINS ENVIRONMENTALLY HAZARDOUS SUBSTANCES: N-HEXANE

MARINE POLLUTANT:

YES

SYMBOL (FISH AND TREE)

SPECIAL MARKING (ADR): SYMBOL (FISH AND TREE)

SPECIAL PRECAUTIONS FOR USER:

WARNING: GASES

DANGER CODE (KEMLER):

EMS NUMBER: F-D, S-U

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:  
NOT APPLICABLE.

TRANSPORT/ADDITIONAL INFORMATION:

DOT:

QUANTITY LIMITATIONS:

ON PASSENGER AIRCRAFT/RAIL: 75 KG

ON CARGO AIRCRAFT ONLY: 150 KG

UN "MODEL REGULATION":

UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

## 15 REGULATORY INFORMATION



SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE

## SUBSTANCE OR MIXTURE:

UNITED STATES (USA):

SARA:

SECTION 355 (EXTREMELY HAZARDOUS SUBSTANCES):  
NONE OF THE INGREDIENTS IS LISTED.

SECTION 313 (SPECIFIC TOXIC CHEMICAL LISTINGS):

110-54-3                    N-HEXANE

TSCA (TOXIC SUBSTANCES CONTROL ACT): ALL INGREDIENTS ARE LISTED.

PROPOSITION 65 (CALIFORNIA):

CHEMICALS KNOWN TO CAUSE CANCER: NONE OF THE INGREDIENTS ARE LISTED.

CHEMICALS KNOWN TO CAUSE REPRODUCTIVE TOXICITY FOR FEMALES:  
NONE OF THE INGREDIENTS ARE LISTED.

CHEMICALS KNOWN TO CAUSE REPRODUCTIVE TOXICITY FOR MALES:  
NONE OF THE INGREDIENTS IS LISTED.

CHEMICALS KNOWN TO CAUSE DEVELOPMENTAL TOXICITY:  
NONE OF THE INGREDIENTS IS LISTED.

CARCINOGENIC CATEGORIES:

EPA (ENVIRONMENTAL PROTECTION AGENCY):

110-54-3                    N-HEXANE                    II

IARC (INTERNATIONAL AGENCY FOR RESEARCH ON CANCER):

9002-84-0                    POLYTETRAFLUOROETHYLENE                    3

TLV (THRESHOLD LIMIT VALUE ESTABLISHED BY ACGIH):  
NONE OF THE INGREDIENTS IS LISTED.

NIOSH-CA (NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH):  
NONE OF THE INGREDIENTS IS LISTED.

STATE RIGHT TO KNOW LISTINGS: NONE OF THE INGREDIENTS IS LISTED.

CANADIAN SUBSTANCE LISTINGS:

CANADIAN DOMESTIC SUBSTANCES LIST (DSL): ALL INGREDIENTS ARE LISTED.

CANADIAN INGREDIENT DISCLOSURE LIST (LIMIT 0.1%):  
NONE OF THE INGREDIENTS IS LISTED.

CANADIAN INGREDIENT DISCLOSURE LIST (LIMIT 1%):

110-54-3                    N-HEXANE

106-97-8                    BUTANE

124-38-9                    CARBON DIOXIDE

OTHER REGULATIONS, LIMITATIONS AND PROHIBITIVE REGULATIONS:  
THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH HAZARD CRITERIA OF THE  
CONTROLLED PRODUCTS REGULATIONS AND THE SDS CONTAINS ALL THE INFORMATION  
REQUIRED BY THE CONTROLLED PRODUCTS REGULATIONS.

CHEMICAL SAFETY ASSESSMENT:  
A CHEMICAL SAFETY ASSESSMENT HAS NOT BEEN CARRIED OUT.

**16 OTHER INFORMATION**

THIS INFORMATION IS BASED ON OUR PRESENT KNOWLEDGE. HOWEVER, THIS SHALL NOT CONSTITUTE A GUARANTEE FOR ANY SPECIFIC PRODUCT FEATURES AND SHALL NOT ESTABLISH A LEGALLY VALID CONTRACTUAL RELATIONSHIP.

DATE OF PREPARATION / LAST REVISION: 03/18/2015 / 06/18/2015

**ABBREVIATIONS AND ACRONYMS:****ADR:**

ACCORD EUROPEEN SUR LE TRANSPORT DES MARCHANDISES DANGEREUSES PAR ROUTE  
(EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS  
GOODS BY ROAD)

IMDG: INTERNATIONAL MARITIME CODE FOR DANGEROUS GOODS

DOT: US DEPARTMENT OF TRANSPORTATION

IATA: INTERNATIONAL AIR TRANSPORT ASSOCIATION

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

EINECS: EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES

ELINCS: EUROPEAN LIST OF NOTIFIED CHEMICAL SUBSTANCES

CAS: CHEMICAL ABSTRACTS SERVICE (DIVISION OF THE AMERICAN CHEMICAL SOCIETY)

NFPA: NATIONAL FIRE PROTECTION ASSOCIATION (USA)

HMIS: HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (USA)

WHMIS: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (CANADA)

LC50: LETHAL CONCENTRATION, 50 PERCENT

LD50: LETHAL DOSE, 50 PERCENT

FLAM. GAS 1: FLAMMABLE GASES, HAZARD CATEGORY 1

FLAM. AEROSOL 1: FLAMMABLE AEROSOLS, HAZARD CATEGORY 1

**PRESS. GAS:**

GASES UNDER PRESSURE: COMPRESSED GAS

**PRESS. GAS:**

GASES UNDER PRESSURE: LIQUEFIED GAS

FLAM. LIQ. 2: FLAMMABLE LIQUIDS, HAZARD CATEGORY 2

SKIN IRRIT. 2: SKIN CORROSION/IRRITATION, HAZARD CATEGORY 2

REPR. 2: REPRODUCTIVE TOXICITY, HAZARD CATEGORY 2

**STOT SE 3:**

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE, HAZARD CATEGORY 3

**STOT RE 2:**

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE, HAZARD CATEGORY 2

ASP. TOX. 1: ASPIRATION HAZARD, HAZARD CATEGORY 1

**SOURCES:****SDS PREPARED BY:**

CHEMTEL INC.

1305 NORTH FLORIDA AVENUE

TAMPA, FLORIDA 33602-2902  
USA

TOLL FREE NORTH AMERICA: 1-888-255-3924

INTL.: +01 813-248-0573

WEBSITE: [WWW.CHEMTELINC.COM](http://WWW.CHEMTELINC.COM)