MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: White Lithium Grease Aerosol

Product Number (s): 03080, 83080

Manufactured By: CRC Industries, Inc. (215) 674-4300

885 Louis Drive, Warminster, PA 18974

24-Hour Emergency Information: CHEMTREC (800) 424-9300

Section 2: Composition/Information on Ingredients

Component	CAS	ACGIH	OSHA	OTHER	%
	NUMBER	TLV	PEL	LIMITS	
Mineral Oil (heavy)	64741-96-4	5 mg/m3	5 mg/m3	(mist)	17-27
Isohexanes	107-83-5	500 ppm	500 ppm	NE	27-37
n-Hexane	110-54-3	50 ppm	50 ppm	NE	< 10
Propane	74-98-6	NE	1000 ppm	NE	10-20
Isobutane	75-28-5	NE	NE	10000 ppm	10-20

Section 3: Hazards Identification

Emergency Overview

Appearance & Odor: Off-white viscous material, solvent odor.

Danger: Extremely Flammable. Harmful or Fatal if Swallowed. Contents Under Pressure.

Potential Health Effects:

Inhalation: Irritation of respiratory tract, headaches, dizziness and central nervous system depression.

Eyes: Irritation, burning

Skin: Irritation Ingestion: NA

Carcinogenicity: OSHA: No IARC: No NTP: No

Chronic Overexposure: Repeated overexposure may cause harm to nervous system.

Medical Conditions Aggravated by Exposure: Pre-existing lung disorders.

Section 4: First Aid Measures

Inhalation: Remove to fresh air. Give artificial respiration if necessary.

Eyes: Flush with large amounts of water for 15 minutes.

Skin: Remove contaminated clothing and wash area with soap and water.

Ingestion: Call a physician. Do not induce vomiting.

Product Name: White Lithium Grease Aerosol

Section 5: Fire-Fighting Measures

Flashpoint: <20°F Method: TCC LEL: ND UEL: ND

Extinguishing Media: CO₂, water fog and foam

Hazardous Combustion Products: Thermal - CO₂ and carbon monoxide

Fire-fighting Instructions: Remove containers from fire area if possible. Use self-contained

breathing apparatus for fire fighting. Aerosol cans may explode if heated

Product Number (s): 03080, 83080

above 120°F.

NFPA: Health: 1 Flammability: 3 Reactivity: 0

HMIS: Health: 1 Flammability: 3 Reactivity: 0 PPE: B

Section 6: Accidental Release Measures

Spill/Leak Procedures: Usually not a problem with aerosols. Area should be ventilated. Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

Section 7: Handling and Storage

Handling Procedures: Store in a cool, dry area. Aerosol cans must be maintained below 120°F to prevent cans from exploding.

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

Section 9: Physical & Chemical Properties

Physical State: Liquid Appearance & Odor: Off-white viscous material,

solvent odor

Specific Gravity: 0.7646 Boiling Point: 141°F (initial)

Freezing Point: NA Vapor Pressure: NA Evaporation Rate: NA Vapor Density (air = 1) > air

pH: NA Solubility: Negligible in water

Volatile Organic Compounds:%: 75 g/L: 483 lbs./gal: 4.03

Section 10: Stability and Reactivity

Stability: Stable Hazardous Polymerization: No

Chemical Incompatibilities: Strong oxidizers.

Materials to Avoid: Strong oxidizers.

Hazardous Decomposition Products: None

Product Number (s): 03080, 83080

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

Section 12: Ecological Information

Ecotoxicity: No data available.

Environmental Fate: No data available for biodegradation.

Section 13: Disposal Considerations

Disposal: This material if discarded may be hazardous waste under U.S. EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental agency for specific rules. Do not dump into sewers, on the ground or into any body of water.

Section 14: Transportation Information

Consumer Commodity Shipping Name:

Hazard Class: ORM-D UN Number: NA Packing Group: NA

Label: NA Placard: NA

Special Provisions: NA

Section 15: Regulatory Information

TSCA: All components are either listed under TSCA or are exempt.

Section 311/312: Acute/Pressure Section 313*: n-Hexane SARA Title III:

CERCLA/Superfund (RQ): NA Extremely Hazardous Substances: No

California Prop 65: This product contains chemicals known to the State of

California to cause cancer, birth defects and other

reproductive harm.

* See section 2 for percentage

Section 16: Additional Information

Adam M. Selisker Prepared By: Date: February 26, 2001

Technical Information: (800) 521-3168 CRC #: 568D

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by

CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: Chemical Abstract Service NA: Not Applicable Parts per Million ND: Not Determined ppm: Tag Closed Cup NE: Not Established TCC: Lower Explosive Limit grams per Liter LEL: g/L: UEL: Upper Explosive Limit lbs./gal: pounds per gallon Personal Protection Equipment Reportable Quantity PPE: RQ:

COC: Cleveland Closed Cup