PAGE



ALDRICH CHEMICAL COMPANY, INC. P.O. BOX 355 MILWAUKEE, WISCONSIN 53201, USA

ATTN: SAFETY DIRECTOR RECEIVING DOCK SCHOOLCRAFT COLLEGE 18600 HAGGERTY ROAD LIVONIA MI 48152

MATERIAL

EMERGENCY PHONE 1-414-273-3850

DATE 09/24/99

CUST#: 938609

PO#: 89527

SHEET

SECTION 1. - CHEMICAL IDENTIFICATION-27041-5 CATALOG #: PENTANE, 99+%, HPLC GRADE NAME: COMPOSITION/INFORMATION ON INGREDIENTS -SECTION 2. CAS #: 109-66-0 MF: C5H12 EC NO: 203-692-4 SYNONYMS AMYL HYDRIDE * PENTAN (POLISH) * PENTANE (ACGIH:OSHA) * PENTANEN (DUTCH) * PENTANI (ITALIAN) * SKELLYSOLVE A * - - - - HAZARDS IDENTIFICATION -SECTION 3. - - -LABEL PRECAUTIONARY STATEMENTS FLAMMABLE (USA) HIGHLY FLAMMABLE (EU) HARMFUL HARMFUL BY INHALATION AND IF SWALLOWED.
IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.
TARGET ORGAN(S): NERVES
KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.
TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHIN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY
WATER AND SEEK MEDICAL ADVICE.
WEAR SUITABLE GLOVES AND EYE/FACE PROTECTION.
OPEN CAREFULLY. AINST STATIC DISCHARGES. RINSE IMMEDIATELY WITH PLENTY OF SECTION 4. - - - -- - - - FIRST-AID MEASURES- -IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES OR SKIN WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES.
IF SWALLOWED, WASH OUT MOUTH WITH WATER PROVIDED PERSON IS CONSCIOUS. CALL A PHYSICIAN.
IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. SECTION 5. - - - -- - - FIRE FIGHTING MEASURES - -EXTINGUISHING MEDIA CARBON DIOXIDE, DRY CHEMICAL POWDER OR APPROPRIATE FOAM. DO NOT USE WATER. SPECIAL FIREFIGHTING PROCEDURES WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO CONTINUED ON NEXT PAGE

SAFETY

SIGMA AFILIKA ALDRICH RICHER SSUPELCO

We are Committed to the Success of our Customers through Science, Technology and Service.

SIGMA

779

ALDRICH CHEMICAL COMPANY, INC. P.O. BOX 355 MILWAUKEE, WISCONSIN 53201, USA

CUST#: 938609 PO#: 89527

MATERIAL SAFETY DATA SHEET PAGE 2 CATALOG #: 27041-5 PENTANE, 99+%, HPLC GRADE NAME: PREVENT CONTACT WITH SKIN AND EYES. USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS. UNUSUAL FIRE AND EXPLOSIONS HAZARDS
VAPOR MAY TRAVEL CONSIDERABLE DISTANCE TO SOURCE OF IGNITION AND FLASH BACK.
CONTAINER EXPLOSION MAY OCCUR UNDER FIRE CONDITIONS.
EXTREMELY FLAMMABLE. SECTION 6. - - - - - - - ACCIDENTAL RELEASE MEASURES-WEAR SELF-CONTAINED BREATHING APPARATUS, RUBBER BOOTS AND HEAVY RUBBER GLOVES.
COVER WITH AN ACTIVATED CARBON ADSORBENT, TAKE UP AND PLACE IN CLOSED CONTAINERS. TRANSPORT OUTDOORS.
VENTILATE AREA AND WASH SPILL SITE AFTER MATERIAL PICKUP IS COMPLETE. EVACUATE AREA.
SHUT OFF ALL SOURCES OF IGNITION. SECTION 7. - - -- - - HANDLING AND STORAGE- - -REFER TO SECTION 8. SECTION 8. - - - - - EXPOSURE CONTROLS/PERSONAL PROTECTION -SAFETY SHOWER AND EYE BATH.
MECHANICAL EXHAUST REQUIRED.
HARMFUL LIQUID.
IRRITANT. IRRITANT.
WASH THOROUGHLY AFTER HANDLING.
WASH CONTAMINATED CLOTHING BEFORE REUSE.
DO NOT BREATHE VAPOR.
AVOID CONTACT WITH EYES, SKIN AND CLOTHING.
NIOSH/MSHA-APPROVED RESPIRATOR.
RUBBER GLOVES.
CHEMICAL SAFETY GOGGLES.
KEEP TIGHTLY CLOSED.
KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. SECTION 9. - - - - - PHYSICAL AND CHEMICAL PROPERTIES -PHYSICAL PROPERTIES
BOILING POINT:
MELTING POINT:
FLASHPOINT - 36 C -120,2 -49 C -130 EXPLOSION LIMITS IN AIR: 8,3 % UPPER LOWER VAPOR PRESSURE: SPECIFIC GRAVITY: 1,394,866 MMHG 0,626 2,48 G/L

CONTINUED ON NEXT PAGE

VAPOR DENSITY:



ALDRICH CHEMICAL COMPANY, INC. P.O. BOX 355 MILWAUKEE, WISCONSIN 53201, USA

CUST#: 938609 PO#: 89527

MATERIAL SAFETY DATA SHEET PAGE
CATALOG #: 27041-5 NAME: PENTANE, 99+%, HPLC GRADE
ECTION 10 STABILITY AND REACTIVITY
INCOMPATIBILITIES OXIDIZING AGENTS
HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS CARBON MONOXIDE, CARBON DIOXIDE
ECTION 11 TOXICOLOGICAL INFORMATION
ACUTE EFFECTS CAUSES SKIN IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. HARMFUL IF INHALED OR SWALLOWED. VAPOR OR MIST IS IRRITATING TO THE EYES, MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT. EXPOSURE CAN CAUSE: DAMAGE TO THE LUNGS
CHRONIC EFFECTS TARGET ORGAN(S): DAMAGE TO THE LUNGS NERVES
RTECS #: RZ9450000 PENTANE
TOXICITY DATA IHL-RAT LC50:364 GM/M3/4H IVN-MUS LD50:446 MG/KG ONLY SELECTED REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES (RTECS) DATA IS PRESENTED HERE. SEE ACTUAL ENTRY IN RTECS FOR COMPLETE INFORMATION.
ECTION 12 ECOLOGICAL INFORMATION
DATA NOT YET AVAILABLE.
ECTION 13 DISPOSAL CONSIDERATIONS
BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. OBSERVE ALL FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS.
ECTION 14 TRANSPORT INFORMATION
CONTACT ALDRICH CHEMICAL COMPANY FOR TRANSPORTATION INFORMATION.
ECTION 15 REGULATORY INFORMATION
EUROPEAN INFORMATION
CONTINUED ON NEXT PAGE 781

We are Committed to the Success of our Customers through Science, Technology and Service.













ALDRICH CHEMICAL COMPANY, INC. P.O. BOX 355 MILWAUKEE, WISCONSIN 53201, USA

CUST#: 938609 PO#: 89527

MATERIAL SAFETY DATA SHEET

PAGE

CATALOG #: 27041-5 NAME: PENTANE, 99+%, HPLC GRADE EC INDEX NO: 601-006-00-1 HIGHLY FLAMMABLE HARMFÛL R 11 HIGHLY FLAMMABLE. KEEP CONTAINER IN A WELL-VENTILATED PLACE. KEĒP AWAY FROM SOURCES OF IGNITION - NO SMOKING. S 29

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES.

REVIEWS, STANDARDS, AND REGULATIONS

DO NOT EMPTY INTO DRAINS.

OEL=MAK
ACGIH TLV-STEL 2210 MG/M3 (750 PPM) DTLVS* TLV/BEI,1997
ACGIH TLV-TWA 1770 MG/M3 (600 PPM) DTLVS* TLV/BEI,1997
MSHA STANDARD-AIR:TWA 500 PPM (1475 MG/M3)
DTLVS* 3,200,1971
OSHA PEL (GEN INDU):8H TWA 1000 PPM (2950 MG/M3)
CFRGBR 29,1910.1000.1994
OSHA PEL (CONSTRUC):8H TWA 500 PPM (1500 MG/M3)
CFRGBR 29,1926.55,1994
OSHA PEL (SHIPYARD):8H TWA 500 PPM (1500 MG/M3)
CFRGBR 29,1915.1000.1993
OSHA PEL (FED CONT):8H TWA 1000 PPM (2950 MG/M3)
CFRGBR 41,50-204.50,1994
OEL-AUSTRALIA:TWA 600 PPM (1800 MG/M3);STEL 750 PPM (2250 MG/M3)
DEL-AUSTRIA: MAK 600 PPM (1800 MG/M3) OEL-AUSTRALIA:TWA 600 PPM (1800 MG/M3); STEL 750 PPM (2250 MG/M3) JAN 1993
OEL-AUSTRIA: MAK 600 PPM (1770 MG/M3); STEL 750 PPM (2210 MG/M3) JAN 1993
OEL-BELGIUM:TWA 600 PPM (1770 MG/M3); STEL 750 PPM (2210 MG/M3) JAN 1993
OEL-DENMARK: TWA 500 PPM (1500 MG/M3); STEL 625 PPM (1800 MG/M3) JAN 1993
OEL-FINLAND:TWA 500 PPM (1500 MG/M3); STEL 625 PPM (1800 MG/M3) JAN 1993
OEL-JAPAN: OEL 300 PPM (880 MG/M3), JAN 1993
OEL-HUNGARY:TWA 500 MG/M3; STEL 1500 MG/M3 JAN 1993
OEL-JAPAN:TWA 500 MG/M3; STEL 1500 MG/M3) JAN 1993
OEL-THE NETHERLANDS:TWA 600 PPM (1800 MG/M3) JAN 1993
OEL-POLAND: MAC(TWA) 1800 MG/M3, MAC(STEL) 2300 MG/M3, JAN1999
OEL-THE PHILIPPINES:TWA 1000 PPM (2950 MG/M3) JAN 1993
OEL-RUSSIA:TWA 300 PPM; STEL 300 MG/M3 JAN 1993
OEL-SWEDEN:TWA 600 PPM (1800 MG/M3); STEL 750 PPM (2000 MG/M3) JAN 1993
OEL-SWETZERLAND:TWA 600 PPM (1800 MG/M3) JAN 1993
OEL-TURKEY:TWA 1000 PPM (2950 MG/M3); STEL 750 PPM JAN 1993
OEL-TURKEY:TWA 1000 PPM (2950 MG/M3); STEL 750 PPM JAN 1993
OEL-TURKEY:TWA 1000 PPM (1800 MG/M3); STEL 750 PPM JAN 1993
OEL-UNITED KINGDOM:TWA 600 PPM (1800 MG/M3); STEL 750 PPM JAN 1993
OEL-IN BULGARIA, COLOMBIA, JORDAN, KOREA CHECK ACGIH TLV
NIOSH REL TO PENTANE-AIR:10H TWA 120 PPM; CL 610 PPM/15M
NIOSH* DHHS #92-100,1992
NOHS 1974: HZD 54243; NIS 31; TNF 3762; NOS 22; TNE 34548



ALDRICH CHEMICAL COMPANY, INC. P.O. BOX 355 P.O. BOX 355 MILWAUKEE, WISCONSIN 53201, USA

CUST#: 938609 PO#: 89527

SAFETY DATA HEET MATERIAL

5 PAGE

CATALOG #: NAME:

27041-5

PENTANE, 99+%, HPLC GRADE

NOES 1983: HZD 54243; NIS 24; TNF 1935; NOS 47; TNE 38465; TFE 10889 EPA TSCA SECTION 8(B) CHEMICAL INVENTORY EPA TSCA SECTION 8(D) UNPUBLISHED HEALTH/SAFETY STUDIES EPA TSCA TEST SUBMISSION (TSCATS) DATA BASE, JUNE 1999 NIOSH ANALYTICAL METHOD, 1994: HYDROCARBONS, BP 36-126 DEGREE C, NIOSH ANALYTICAL METHOD, 1996: VOLATILE ORGANIC COMPOUND, 2549 DEGREE C, 1500

SECTION 16. - OTHER INFORMATION- -

THE ABOVE INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ALDRICH SHALL NOT BE HELD LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING OR FROM CONTACT WITH THE ABOVE PRODUCT. SEE REVERSE SIDE OF INVOICE OR PACKING SLIP FOR ADDITIONAL TERMS AND CONDITIONS OF SALE.

COPYRIGHT 1998 SIGMA-ALDRICH CO. LICENSE GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.

783







