

-----  
SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION  
-----

## CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT CODE. . . . : 02966 658986 406  
PRODUCT NAME . . . : Bega Black II  
PRODUCT CLASS . . . : Aerosol Touch-up

MSDS PREPARATION DATE : 10/02/2001

## MANUFACTURER IDENTIFICATION:

RAABE CORPORATION  
PO BOX 1090

## CUSTOMER IDENTIFICATION:

Bega/US, Inc.  
1000 Bega Way

MENOMONEE FALLS

WI 53052

Carpinteria,

CA 93013

## EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC : 800-424-9300  
INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887  
8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

-----  
SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS  
-----

## 1 CARBON BLACK

CAS# 1333-86-4

## CARBON BLACK

PCT BY WT: .2370

LEL 99.00

## EXPOSURE LIMIT:

ACGIH TLV-TWA 3.5 mg/M3  
ACGIH TLV-STEL NO INFO  
OTHER IARC (2B)

## 2 ETHYLBENZENE

CAS# 100-41-4

## ETHYLBENZENE

PCT BY WT: .1510 VAPOR PRESSURE: 19.000 MMHG @ 68F LEL 1.20

## EXPOSURE LIMIT:

ACGIH TLV-TWA 100 ppm  
ACGIH TLV-STEL 125 ppm  
OSHA PEL-TWA 100 ppm  
OSHA PEL-STEL 125 ppm  
OTHER IARC (2B)

## 3 N-BUTANE

CAS# 106-97-8

## N-BUTANE

PCT BY WT: 6.0000 VAPOR PRESSURE: 879.100 MMHG @ 68F LEL 1.80

## EXPOSURE LIMIT:

ACGIH TLV-TWA 800 ppm

## RAABE CORPORATION

N92 W14701 Anthony Avenue  
Menomonee Falls, WI 53051-1630  
P.O. Box 1090 Menomonee Falls, WI 53052-1090  
800 966 7580 | 262 255 9500 | fax 262 255 0684  
www.raabeecorp.com

---

RAABE CORPORATION  
MATERIAL SAFETY DATA SHEET

02966 658986 406

---

RAABE CORPORATION  
MATERIAL SAFETY DATA SHEET

02966 658986 406

---

ACGIH TLV-STEL	NO INFO
OSHA PEL-TWA	800 ppm
COMPANY	N.E.

---

## 4 PROPANE

CAS# 74-98-6

## PROPANE

PCT BY WT: 18.0000 VAPOR PRESSURE: 5585.200 MMHG @ 68F LEL 2.20  
EXPOSURE LIMIT:  
ACGIH TLV-TWA 1000 ppm  
ACGIH TLV-STEL NO INFORMATION

---

## 5 ACETONE

CAS# 67-64-1

## ACETONE

PCT BY WT: 37.0000 VAPOR PRESSURE: 231.000 MMHG @ 68F LEL 2.60  
EXPOSURE LIMIT:  
ACGIH TLV-TWA 750 ppm  
ACGIH TLV-STEL 1000 ppm  
OSHA PEL-TWA 750 ppm  
OSHA PEL-STEL 1000 ppm  
COMPANY N.E.

---

## 6 METHYL ETHYL KETONE

CAS# 78-93-3

## METHYL ETHYL KETONE

PCT BY WT: 7.0000 VAPOR PRESSURE: 85.000 MMHG @ 68F LEL 1.80  
EXPOSURE LIMIT:  
ACGIH TLV-TWA 200 ppm  
ACGIH TLV-STEL 300 ppm  
OSHA PEL-TWA 200 ppm  
COMPANY N.E.

---

## 7 GLYCOL ETHER PM ACETATE

CAS# 108-65-6

## PROPYLENE GLYCOL METHYL ETHER ACETATE

PCT BY WT: 7.0000 VAPOR PRESSURE: 3.700 MMHG @ 68F LEL 1.30  
EXPOSURE LIMIT:  
ACGIH TLV-TWA NOT ESTABLISHED  
ACGIH TLV-STEL NOT ESTABLISHED

---

## 8 TOLUENE

CAS# 108-88-3

## TOLUENE

PCT BY WT: 12.0000 VAPOR PRESSURE: 38.000 MMHG @ 68F LEL 1.40  
EXPOSURE LIMIT:  
ACGIH TLV-TWA 50 ppm  
ACGIH TLV-STEL NO INFO

RAABE CORPORATION  
MATERIAL SAFETY DATA SHEET

02966 658986 406

OSHA PEL-TWA  
COMPANY

50 ppm  
N.E.

\*\*\*\*\*  
This product contains one or more reported carcinogens or suspected carcinogens which are noted NTP, IARC, or OSHA-Z in the other limits recommended column.  
\*\*\*\*\*

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Harmful if swallowed.  
Harmful if inhaled.  
Causes eye irritation.  
Causes skin irritation.  
Vapors irritating to eyes and respiratory tract.  
Extremely flammable liquid and vapor.  
Vapors may cause flash fire or explosion.  
Extremely flammable aerosol.  
Contents under pressure.

POTENTIAL HEALTH EFFECTS:

EYE:

May cause severe corneal injury if liquid comes in contact with the eyes.

SKIN:

May cause skin irritation.  
Repeated and prolonged contact with the skin may cause allergic dermatitis.

INHALATION:

Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.  
Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.  
Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.

INGESTION:

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.

CHRONIC EFFECTS:

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:

Kidney damage  
Eye damage  
Lung damage  
Liver damage  
Spleen damage  
Brain damage

RAABE CORPORATION  
MATERIAL SAFETY DATA SHEET

02966 658986 406

Chronic overexposure to a component or components of this product has been suggested as a cause of the following effects in humans:

Liver damage

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Repeated breathing or skin contact of methyl ethyl ketone may increase the potency of neurotoxins such as hexane if exposures occur at the same time.

Product contains toluene which may be harmful to the fetus based on animal studies.

Repeated exposure to toluene has been associated with high frequency hearing loss in laboratory animals. The human consequences of this finding is uncertain.

In April 1996, The International Agency for Research on Cancer (IARC) published Monograph 65 which reclassifies Carbon Black into Group 2B (possibly carcinogenic to humans).

In February 2000 the International Agency for Research on Cancer (IARC) classified ethylbenzene as possibly carcinogenic to humans (Group 2B) on the basis of sufficient evidence for carcinogenicity in experimental animals but inadequate evidence for cancer in humans.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN CONTACT:

Wash thoroughly with soap and water and seek medical attention. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION:

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

INGESTION:

Since this product may contain materials which can cause lung damage if aspirated into the lungs, the decision whether to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.

NOTE TO PHYSICIAN:

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

Flashpoint	: Less Than -25 °F
Explosion Level	: Low - 1.2
	High - 100.0
Flammability Limits	: Lower - -N/A
	Higher - -N/A

RAABE CORPORATION  
MATERIAL SAFETY DATA SHEET

02966 658986 406

**EXTINGUISHING MEDIA:**

Use Dry Chemical, Carbon Dioxide or Chemical Foam.

**FIRE-FIGHTING PROCEDURES AND EQUIPMENT:**

Contents under pressure. Do not use or store near sources of heat, sparks or open flame. Keep away from any source of heat such as sunlight, heaters or stoves that could cause the container to burst. Do not puncture or incinerate. Do not crush or place in a garbage compactor. Do not store above 120 degrees F. Aerosol containers may explode when exposed to extreme heat.

Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back.

Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used.

Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES****CLEAN-UP AND CONTAINMENT:**

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire.

Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

**SECTION 7 - HANDLING AND STORAGE****HANDLING:**

Wash hands thoroughly after handling.

**STORAGE:**

Store in a cool dry area with ventilation suitable for storing materials shown in section 2.

Keep away from heat, sparks and flame.

Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

**SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION****ENGINEERING CONTROLS:**

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

**RESPIRATORY PROTECTION:**

If workplace exposure limits are exceeded for any component(see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

**SKIN PROTECTION:**



RAABE CORPORATION  
MATERIAL SAFETY DATA SHEET

02966 658986 406

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

## EYE PROTECTION:

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

## OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

## HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure	: 5585.20	mm Hg @ 20 C
Vapor Density	: 3.70	
Boiling Range	: Lower - 1.0 °F	
	: Higher - 999.0 °F	
Specific Gravity	: .745	
Formula Weight per Volume	: 6.1984	LB/GL
VOC (Calculated, LB/GAL)	: 4.932	
VOC (Calculated, GM/L)	: 591.00	
Percent Volatile by Weight	: 88.7300	
Evaporation Rate	: 7.700	(n-Butyl Acetate = 1)
Viscosity	: -N/A	

## SECTION 10 - STABILITY AND REACTIVITY

## CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame.

Product may explode if heated. Keep cool, avoid exposure to heat.

## INCOMPATIBILITIES:

Strong oxidizing agents.

## DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

## POLYMERIZATION:

No hazardous polymerization will occur under normal conditions.

## STABILITY:

The product is stable under normal storage conditions.

## SECTION 11 - TOXICOLOGICAL INFORMATION

No specific information is available. Please refer to Section 3 for available information on potential health effects.

## SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product.

RAABE CORPORATION  
MATERIAL SAFETY DATA SHEET

02966 658986 406

## SECTION 13 - DISPOSAL CONSIDERATIONS

## WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

## SECTION 14 - TRANSPORT INFORMATION

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II

(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL

(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL

(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

## SECTION 15 - REGULATORY INFORMATION

## SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

## ETHYLBENZENE

CAS# 100-41-4 PCT BY WT: .1510

## METHYL ETHYL KETONE

CAS# 78-93-3 PCT BY WT: 7.1530

## TOLUENE

CAS# 108-88-3 PCT BY WT: 12.3180

## FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

## STATE REGULATIONS:



RAABE CORPORATION  
MATERIAL SAFETY DATA SHEET

02966 658986 406

-----  
This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California the following warning statement must appear on the label:

Warning! This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.

NEW JERSEY RIGHT-TO-KNOW

No non-hazardous ingredients are among the top five ingredients

PENNSYLVANIA RIGHT-TO-KNOW

No non-hazardous ingredients are present greater than 3%

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

-----  
The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

HMIS RATINGS:

HEALTH: 2\*    FLAMMABILITY: 4    REACTIVITY: 0    PERSONAL PROTECTION: G