

## LACQUER Sprays

DESCRIPTION	A fast-curing, hard coating that can be polished to an even higher gloss.
APPEARANCE	High gloss
PACKAGING	12 oz. can
RECOMMENDED PRIMER	None recommended
SURFACE PREPARATION	<p>Remove all dirt, grease, oil, salt or other contaminants by washing the surface with detergent or other suitable cleaner. Rinse thoroughly and allow to fully dry.</p> <p>Scrape and wire brush or power tool clean to remove loose rust, scale, and deteriorated coatings. Scarify previously painted coatings or smooth surfaces to promote adhesion. Test for compatibility with existing coating.</p>
APPLICATION	<p>Apply only when air and surface temperature is above 50°F (10°C). Apply two or more light coats a few minutes apart.</p> <p>Use in properly ventilated areas. Spraying can produce a fog that will travel. Protect surrounding area, clothing and skin from overspray.</p> <p>Do not use near open flame.</p>

### PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

RESIN TYPE	Acrylic Lacquer
VOLATILE ORGANIC COMPOUNDS	Maximum 65% by wt.
PRACTICAL COVERAGE	Approximately 7 sq. ft./can. (.63 M <sup>2</sup> /can)
DRY TIMES @ 70°F (21°C) and 50% RH	Tack Free: 20 minutes Handle: 30 minutes Recoat Anytime
DRY HEAT RESISTANCE	200°F (94° C)
SHELF LIFE	5 Years