

F76XX

86A

MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS AND RELATED MATERIALS
 (Approved by U.S. Department of Labor 'Essentially Similar' to form OSHA-20)

MANUFACTURER'S NAME THE SHERWIN-WILLIAMS COMPANY
 101 Prospect Avenue N.W.
 Cleveland, Ohio 44115
 DATE OF PREPARATION 10-Dec-86
 EMERGENCY TELEPHONE NO. (216) 566-2917
 INFORMATION TELEPHONE NO. (216) 566-2902

Section I -- PRODUCT IDENTIFICATION

PRODUCT NAME KEM AQUA* Gloss Enamel, Non-Lead Colors
 * - Trade Mark
 PRODUCT NUMBERS AND COLORS
 F76 B 21 Gloss Black. F76 R 27 Medium Red.
 F76 B 22 Flat Black. F76 R 28 Dark Red.
 F76 E 23 Light Orange. F76 V 100 Gloss Clear.
 F76 E 24 Internat. Orange. F76 W 9 White.
 F76 G 25 Green. F76 Y 21 Medium Yellow.
 F76 L 26 Gloss Blue. F76 Y 22 Gloss Yellow.
 --- Including Non-Lead Containing Custom Colors ---
 PRODUCT CLASS
 Water-reducible Alkyd Coating

Section II -- HAZARDOUS INGREDIENTS

CAS No.	INGREDIENT	% by weight	ACGIH-TLV	OSHA-PCL	UNITE	V.P.
111-76-2	2-Butoxyethanol	10-15	25	50	PPM	0.6
78-93-3	Methyl Ethyl Ketone.	0-5	200	200	PPM	70.0
13463-67-7	Titanium Dioxide.	0-25	10		Mg/M3	

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen

pH - 7-9

Section III -- PHYSICAL DATA

EVAPORATION RATE -- Slower than Ether VAPOR DENSITY -- Heavier than Air
 BOILING RANGE (F) 174 - 340 % VOLATILE VOLUME 65-80 WT/GAL 8.3-10.4

Section IV -- FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION FLASH POINT 120 F PHCC LEL 1.1
 Combustible, Flash above 99 and below 200 F
 EXTINGUISHING MEDIA
 Carbon Dioxide, Dry Chemical, Alcohol Foam
 UNUSUAL FIRE AND EXPLOSION HAZARDS
 Closed containers may explode (due to the build-up of steam pressure) when exposed to extreme heat.
 SPECIAL FIRE FIGHTING PROCEDURES
 Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Continued on page 2

F76XX

KEM AQUA* Gloss Enamel, Non-Lead Colors

page 2

Section V -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE -- See Section II

EFFECTS OF OVEREXPOSURE

ACUTE: Overexposure causes eye, skin and respiratory irritation. May cause nervous system depression accompanied by headache, dizziness, nausea, confusion and staggering gait. Extreme overexposure may result in unconsciousness and possibly death.
 CHRONIC: Prolonged overexposure to ingredients in Section II may cause adverse effects to the liver, urinary, blood forming and reproductive systems.
 Rats exposed to titanium dioxide dust at 250 mg./m3 developed lung cancer, however, such exposure levels are not attainable in the workplace.
 Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
 If on SKIN: Wash affected area thoroughly with soap and water.
 Remove contaminated clothing and launder before re-use.
 If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

Section VI -- REACTIVITY DATA

STABILITY -- Stable

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide
 HAZARDOUS POLYMERIZATION -- Will Not Occur

Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section VIII -- PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

Protect against dust which may be generated by sanding or abrading the dried film.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear respiratory device approved by NIOSH/MSHA for protection against materials in Section II.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section II.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Continued on page 3

F76XX KEM AQUA* Gloss Enamel, Non-Lead Colors

page 3

Section IX -- PRECAUTIONS

DOL STORAGE CATEGORY -- 2

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Contents are COMBUSTIBLE. Keep away from heat and open flame.
 Consult NFPA Code. Use approved Bonding and Grounding procedures.
 Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

This coating contains materials classified as nuisance particulates, for example titanium dioxide, calcium carbonate, etc. (see ACGIH TLV List, Preface and Appendix D), which may be present at hazardous levels only during sanding or abrading of the dried film.

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

HMIS

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0

This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CFR 1910.1200(g)(4), for similar complex mixtures.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.