

86 MATERIAL SAFETY DATA SHEET  
FOR COATINGS, RESINS AND RELATED MATERIALS  
(Approved by U.S. Department of Labor 'Essentially Similar' to form OSHA-20)

MANUFACTURER'S NAME THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, Ohio 44115  
DATE OF PREPARATION 21-Mar-86  
EMERGENCY TELEPHONE NO. (216) 566-2917  
INFORMATION TELEPHONE NO. (216) 566-2902

## Section I -- PRODUCT IDENTIFICATION

PRODUCT NAME \* - Trade Mark  
SUPER PAINT\* Semi-Gloss Latex Enamel  
PRODUCT NUMBERS AND COLORS  
A88 W 14 Pure White Base X  
A88 W 15 Base Y  
A88 W 16 Base Z  
--- Including Non-Lead Tinted Colors ---  
PRODUCT CLASS  
Latex Paint

## Section II -- HAZARDOUS INGREDIENTS

CAS No.	INGREDIENT	% by WEIGHT	ACGIH-TLV	OSHA-PCL	UNITS	V.P.
112-34-5	2-(2-Butoxyethoxy)-ethanol	<5	50		PPM	0.1
107-21-1	Ethylene Glycol.	<5	50		PPM	0.1

pH - 8.3-9.2

## Section III -- PHYSICAL DATA

EVAPORATION RATE -- Slower than Ether	VAPOR DENSITY -- Heavier than Air
BOILING RANGE (F) 212 - 448	% VOLATILE VOLUME 61-71
	WT/GAL 9.3-10.8

## Section IV -- FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION	FLASH POINT >199 F PMCC	LEL N.A.
-----------------------------	-------------------------	----------

EXTINGUISHING MEDIA  
Not Applicable  
Carbon Dioxide, Dry Chemical, Alcohol Foam  
UNUSUAL FIRE AND EXPLOSION HAZARDS  
Extreme heat may cause closed containers to burst.  
SPECIAL FIRE FIGHTING PROCEDURES  
Full protective equipment including self-contained breathing apparatus should be used.  
Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

## Section V -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE -- See Section II

## EFFECTS OF OVEREXPOSURE

ACUTE: In a confined area vapors in high concentration are anesthetic. Overexposure may result in lightheadedness and staggering gait.  
Irritant to skin and upper respiratory system.

Continued on page 2

## EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.  
If on SKIN: Wash affected area thoroughly with soap and water.  
Remove contaminated clothing and launder before re-use.  
If in EYES: Flush eyes with large amounts of water for 15 minutes.  
Get medical attention.

## Section VI -- REACTIVITY DATA

STABILITY -- Stable  
HAZARDOUS DECOMPOSITION PRODUCTS  
By fire: Carbon Dioxide, Carbon Monoxide  
HAZARDOUS POLYMERIZATION -- Will Not Occur

## Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED  
Remove all sources of ignition. Ventilate and remove with inert absorbent.  
WASTE DISPOSAL METHOD  
Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.  
Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

## Section VIII -- PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE  
Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.  
Protect against dust which may be generated by sanding or abrading the dried film.  
VENTILATION  
Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.  
RESPIRATORY PROTECTION  
If personal exposure cannot be controlled below applicable limits by ventilation, wear respiratory device approved by NIOSH/MSHA for protection against materials in Section II.  
PROTECTIVE GLOVES  
Wear gloves which are recommended by glove supplier for protection against materials in Section II.  
EYE PROTECTION  
Wear safety spectacles with unperforated sideshields.

## Section IX -- PRECAUTIONS

DOL STORAGE CATEGORY -- 3B  
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING  
Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.  
OTHER PRECAUTIONS  
This coating contains materials classified as nuisance particulates, for example titanium dioxide, calcium carbonate, etc. (see ACGIH TLV List, Preface and Appendix D), which may be present at hazardous levels only during sanding or abrading of the dried film.  
This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CFR 1910.1200(g)(4), for similar complex mixtures.  
The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.