GLUE FOR RC/CRIMINAL JUSTICE









MATERIAL SAFETY DATA SHEET M745-3152, M745-3511

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:

420 Satellite City Penetrating Instant Adhesive

Item No.: Product Type: M745-3512, M745-3511

Cyanoacrylate Ester

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredients

CAS No.

Ethyl Cyanoacrylale

7085-85-0

95-100

HYDROQUINONE

123-31-9 0-0.5

Ingredients which have exposure limits

Exposure Limits (TWA)

ACGIH

OSHA

OTHER

Ingredients Ethyl cyanoacrylate (TLV)

(PEL)

0.2 ppm TWA

None

None

HYDROQUINONE

2 mg/m3 TWA

2 mg/m3 TWA 4 mg/m3 STEL 2 mg/m3 TWA

ACGIH

OSHA

Exposure Limits (STEL) Ingredients

(TLV)

(PEL)

3. HAZARDS IDENTIFICATION

Toxicity:

Skin contact may cause burns.

Bonds Skin rapidly and strongly.

Skin and eye irritant.

Estimated oral L050 more than 5000mg/kg. Estimated dermal LD 50 more than 2000 mg/kg.

Primary Routes of Entry:

Signs and Symptoms

None known

of Exposure:

Vapor is irritating to eyes and mucous membranes

above TLV. Exposure to vapors above the established limits may cause symptoms of

non-allergic asthma.

Existing Conditions

Aggravated by Exposure: None known

Literature Referenced

Carcinogen

Ingredients

Target Organ and Other Health Effects

NTP IARC OSHA

Ethyl cyanoacrylate

ALG IRR RES

NO NO NO

HYDROQUINONE

BLO BNM CNS EYE IMM IRR UV MUT NO N/A NO

SKI THY

Abbreviations

N/A Not Applicable

BLO Blood

ALG Allergen **BNM** Bone Marrow

CNS Central nervous system

EYE Eyes

IMM Immune system

IRR Irritant

LIV Liver **RES Respiratory** MUT Mutagan SKI Skin

THY Thyroid

4. FIRST AID MEASURES

Ingestion:

Ingestion is not likely. See supplemental information for

emergency procedures.

Inhalation:

Remove to fresh air. If symptoms persist,

obtain medical attention.

Skin Contact

Soak in warm water. See supplemental information for

emergency procedures.

Eye Contact:

Flush with water. See supplemental information for

emergency procedures.

5. FIRE FIGHTING MEASURES

Flashpoint:

150-200 °F

Method:

Tag Closed Cup

Recommended

Extinguishing Agents:

Carbon dioxide, foam, dry chemical

Special Firefighting

Procedures:

Not available

Hazardous Products formed

by Fire or Thermal Decomp

Irritating organic fragments.

Unusual Fire or

Explosion Hazards:

None

Explosive Limits:

(% by volume in air)Lower Not available (% by volume in air)Upper Not available

6. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case

of spill or leak:

Flood with water to polymerize. Soak up with an Inert

absorbent.

7. HANDLING AND STORAGE

Safe Storage:

Store below 75 deg. F.

Handling:

Avoid contact with skin and eyes. Avoid breathing vapor.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Eyes:

Safety glasses or goggles.

Skin:

Nitrile or polyethylene gloves and aprons.

Do not use cotton

See supplemental page (or additional information.

Ventilation:

Positive down-draft exhaust ventilation should be provided to

maintain vapor concentration below TLV

Respiratory

Not available

See Section 2 for Exposure Limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Clear liquid.

Odor:

Sharp, irritating More than 300'F

Boiling Point: pH:

Does not apply

Solubility in Water:

Polymerized by water

Specific Gravity

Volatile Organic Compound •

(EPA Method 24)

98.8%; 1037.4 g/l

1.05 at 75°F

Vapor Pressure:

Less than 0.2 mm at 75°F Approximately 3

Vapor Density:

Evaporation Rate

(Ether =1) Not available

10. STABILITY AND REACTIVITY

Stability:

Stable

Hazardous Polymerization:

Will not occur Polymerized by contact with water, alcohols, amines, alkalies.

Incompatibility:

Not available

Conditions to Avoid: Hazardous Decomposition

Products (non-thermal):

None

11. TOX1GOLOGICAL INFORMATION

See Section 3.

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended methods of disposal: Incinerate following EPA and local regulations. EPA Hazardous Waste Number NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49 CFR 172)

Domestic Ground Transport

Proper Shipping Name:

Unrestricted (Not more than 450 liters):

Combustible liquids, n.o.s. (Cyanoacrylale ester)

(More than 450 liters)

Hazard Class or Division:

Unrestricted (Not more than 450 liters) Combustible liquid (More than 450 liters)

Identification Number:

None (Not more than 450 liters); NA 1993 (More than 450 liters)

Marine Pollutant:

None

IATA

Proper Shipping Name:

Unrestricted (Not more than one pint);

Aviation regulated liquid, n.o.s., (Cyanoacrylate

Ester) (More than one pint)

Class or Division:

Unrestricted (Not more than one pint);

Class 9 (More than one pint)

UN or ID Number

None (Not more than one pint) UN 3334 (More than one pint)

15. REGULATORY INFORMATION

CA Proposition 65:

Not available

16. OTHER INFORMATION

Estimated NFPA(R) Code:

Health Hazard: 2
Fire Hazard: 2
Reactivity Hazard: 1

Specific Hazard: Does not apply

Estimated HMIS(R) Code:

Health Hazard: 22
Flammability Hazard: 22
Reactivity Hazards: 1

Personal Protection: See Section 8.

Revision Date:

June 19, 2006

INFORMATION FOR FIRST AID AND CASUALTY ON TREATMENT FOR ADHESION OF HUMAN SKIN TO ITSELF IF CAUSED BY CYANOACRYLATE ADHESIVES

Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds human tissue including skin in seconds. Experience has shown that accidents due to cyanoacrylates are handled best by passive, nonsurgical first aid. Treatment of specific types of accidents are given below.

SKIN CONTACT Remove excess adhesive. Soak in warm, soapy water. The adhesive will come loose from the skin in several hours. Cured adhesive does not present a health hazard even when bonded to the skin.

Avoid contact with clothes, fabrics, rags, or tissue. Contact with these materials may cause polymerization. The polymerization of large amounts of adhesive will generate heat causing smoke, skin burns, and strong, irritating vapors. Wear nitrite or polyethylene gloves and apron when handling large amounts of adhesive.

SKIN ADHESION First immerse the bonded surfaces in warm, soapy water. Peel or roll the surfaces apart with the aid of a blunt edge, e.g. a spatula or a teaspoon handle; then remove adhesive from the skin with soap and water. Do not try to pull surfaces apart with a direct opposing action.

EYELID TO EYELID OR EYEBALL ADHESION In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in 1-4 days. There will be no residual damage. Do not try to open the eyes by manipulation.

ADHESIVE ON THE EYEBALL Cyanoacrylate introduced into the eyes will attach itself to the eye protein and will disassociate from it over intermittent periods, generally covering several hours. This will cause periods of weeping until clearance is achieved. During the period of contamination, double vision may be experienced together with a lachrymatory effect, and it is important to understand the cause and realize that disassociation will normally occur within a matter of hours, even with gross contamination.

MOUTH If lips are accidentally stuck together, apply lots of warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips with direct opposing action.

It is almost impossible to swallow Cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in one half to two days. In case a lump forms in the mouth,

position the patient to prevent ingestion of the lump when it detaches,

BURNS Cyanoacrytates give off heat on solidification. In rare cases a large drop will increase in temperature enough to cause a bum. Burns should be treated normally after the lump of Cyanoacrylate is released from the tissue as described above.

SURGERY It should never be necessary to use such a drastic method to separate accidentally bonded skin.

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.