MATERIAL SAFETY DATA SHEET

Super Freeze II 929-210

Post Office Box 949 Amarillo, TX 79105-0949 Phone: (806) 372-8523 FAX: (806) 372-8750 Toll-Free: (800) 858-4043

Hazardous Description: Chlorodifluoromethane, UN1018, Non-Flammable Gas (For Shipping Purposes Only)

Hazard Rating Health: 1 Fire: 0 Reactivity: 1 0-Least 1-Slight 2-Moderate 3-High 4-Extreme

Ingredient lorodifluoromethane	HAZARDOUS COMPON CAS No. 75-45-6	100	OSHA PEL NIF
lorodifluoromethane	75 45		ACGIH TLV 1000ppm Inhalation: LC50
			26,200 ppm/4hr. Oral ALD: >3725 mg/kg
			in rats
		1	
		1	
		1	
		36	

Boiling Point: -41 C -41F

pH: 7-8

Density: 1.194

lubility in Water: 0

por Density (Air=1): 3.0

Appearance: Clear water-white liquid with low odor.

Appearance: None TCC Method

Solids: 0

Evaporation Rate (H2O=1): >1

Appearance: Clear water-white liquid with low odor.

Flash Point: None TCC Method

Explosion
LEL: NA

Explosion Limits

foam, dry chemical, carbon dioxide.

Extinguishing Media: Water, foam, dry chemical, carbon dioxide.

Special Fire Fighting Procedures:
Fire fighters should wear self contained, positive-pressure breathing apparatus and avoid skin contact.

Unusual Fire and Explosion Hazards:
Aerosol cans may erupt with force at temperatures above 120 degrees F.

IV - HEALTH HAZARD DATA

INHALATION: Major potential rout of exposure. Minimal effects observed inhalation: Major potential rout of exposure. Minimal effects observed below 1000 ppm. Dizziness, drowsiness, and throat irritation below 1000 ppm. Dizziness, drowsiness, and throat irritation below 1000 ppm. Unconsciousness and death possible at levels above 1,000 ppm. Blood pressure depression, cardiac at levels above 10,000 ppm. Blood pressure depression, cardiac sensitization, and ventricular arrhythmia can result from exposure to near-anesthetic levels.

EYES: Liquid can cause slight, temporary irritation with slight temporary corneal injury. Vapors can irritate eyes.

SKIN: Prolonged or repeated contact with liquid can cause freezing of skin tissues, defatting, and dermatitis.

INGESTION: Single dose toxicity is low to moderate. If vomiting occurs the liquid can be aspirated into the lungs, which can cause chemical pneumonia and systemic effects. Human psychotropic, chemical pneumonia and systemic effects possible.

, OCT 18 '95 15:25 ZENITH MODEL SHOP [708] 391-7887

929-210

Emergency and First Aid Procedures
Emergency and First Aid Procedures
INHALATION: Remove to fresh air. If breathing has stopped, administer
artificial respiration. Seek medical attention.

EYES: Flush eyes for at least fifteen minutes with clear water. If irritation persists, seek medical attention.

SKIN: Wash with soap and water. For frostbite, seek immediate medical attention.

INGESTION: DO NOT INDUCE VOMITING! Give 2 glasses of water and immediately seek medical attention.

NOTE: Adrenalin and other similar cardiac stimulants should NOT be used to treat effects of overexposure to this product. See section I.

None of the ingredients in this product are listed on the OSHA, IAR list of possible carcinogenic, mutagenic, or teratogenic chemicals. IARC, NTP

Conditions to Avoid: None

V - REACTIVITY DATA
ons to Avoid: Contact with open flame, heat Stability: STABLE Conditions to Avoid: Contact Incompatibility (materials to avoid)
Reactive alkali metals, strong acids & bases.

Hazardous Decomposition Products:
Hydrogen Chloride, phosgene, chlorine, carbon dioxide, and carbon monoxide.
Hazardous Polymerization: WILL NOT OCCUR

VI - SPILL OR LEAK PROCEDURES

Evacuate area. Ventilate area well and avoid breathing vapors. Vapor concentration will be highest along floor and in low lying areas. Pick up liquid on suitable absorbent and store in sealed containers.

Waterial may be disposed of by a licensed reclaimer or incineration facility. Consult local, state, and federal disposal authorities for approved procedures.

Do not incinerate or destroy aerosol cans.

VIII - EMPLOYEE PROTECTION

Respiratory Protection:

If levels exceed TLVs, increased ventilation or organic vapor mask required Ventilation: Do not use in closed space. Ventilation required.

Hands: Solvent resistant gloves such as Viton, Polyvinyl alcohol.

Eyes: Wear splash proof safety goggles or glasses. Special Procautions:

Keep aerosol cans in cool place out of direct sunlight. Keep this and all chemicals out of reach of children. This product for industrial use only.

IX - OTHER INFORMATION