



Dry Lube

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.
Issue date: 11/3/2016 Revision date: 6/9/2022 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Dry Lube
Product code : 16-TDL

1.2. Recommended use and restrictions on use

Recommended use : Multi-Purpose Lubricant

1.3. Supplier

Manufacturer

Blaster LLC
8500 Sweet Valley Drive
44125 Valley View, Ohio - USA
T (216) 901-5800 - F (216) 901-5801
www.blasterproducts.com

1.4. Emergency telephone number

Emergency number : Chemtrec (800) 424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flam. Aerosol 2	Flammable aerosol
Press. Gas (Diss.)	Contains gas under pressure; may explode if heated
Asp. Tox. 1	May be fatal if swallowed and enters airways

2.2. GHS Label elements, including precautionary statements

This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: Flammable aerosol
Contains gas under pressure; may explode if heated
May be fatal if swallowed and enters airways

Precautionary statements (GHS US)

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
If swallowed: Immediately call a poison center or doctor.
Do NOT induce vomiting.
Store locked up.
Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dry Lube

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.
Distillates, petroleum, light distillate hydrotreating process, low-boiling	CAS-No.: 68410-97-9	80 - 100	Flam. Liq. 1;H224 Asp. Tox. 1;H304
Carbon dioxide	CAS-No.: 124-38-9	1 - 5	Press. Gas (Comp.);H280
Aluminum oxide (Al ₂ O ₃)	CAS-No.: 1344-28-1	1 - 5	Not classified
Cyclohexane	CAS-No.: 110-82-7	1 - 5	Flam. Liq. 2;H225 Skin Irrit. 2;H315 STOT SE 3;H336 Asp. Tox. 1;H304

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Dry Lube

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Carbon dioxide, dry chemical, halons. Foam.
Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Oxides of nitrogen.
Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.4. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

Dry Lube

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Hazardous waste due to potential risk of explosion. Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking.
Precautions for safe handling	: Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. Use non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharge. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas, fumes, vapour or spray. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Do not pierce or burn, even after use.
Hygiene measures	: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store away from direct sunlight or other heat sources. Keep in fireproof place.
Storage area	: Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Dry Lube-2022	
No additional information available	
Cyclohexane (110-82-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	100 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	1050 mg/m ³
OSHA PEL (TWA) [2]	300 ppm
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	1300 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	1050 mg/m ³
NIOSH REL TWA [ppm]	300 ppm
Carbon dioxide (124-38-9)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	5000 ppm
ACGIH OEL STEL [ppm]	30000 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	9000 mg/m ³
OSHA PEL (TWA) [2]	5000 ppm
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	40000 ppm

Dry Lube

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Carbon dioxide (124-38-9)	
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	9000 mg/m ³
NIOSH REL TWA [ppm]	5000 ppm
NIOSH REL (STEL)	54000 mg/m ³
NIOSH REL STEL [ppm]	30000 ppm
Aluminum oxide (Al ₂ O ₃) (1344-28-1)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9)	
No additional information available	

8.2. Appropriate engineering controls

- Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
- Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Wear chemically resistant protective gloves.
Eye protection:
Safety glasses or goggles are recommended when using product.
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Hazy. Aerosol.
Color	: Clear
Odor	: Mild aliphatic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 90 – 98 °C (195-208 °F)

Dry Lube

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Flash point	: -8 °C (14.6 °F)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Flammable aerosol.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.81
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

Heat of Combustion	: 24 kJ/g
Flame Projection	: > 21 inches
Flashback	: Yes

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Sources of ignition. Heat. Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Cyclohexane (110-82-7)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	---

Dry Lube

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Cyclohexane (110-82-7)	
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat	> 32.88 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
Aluminum oxide (Al2O3) (1344-28-1)	
LD50 oral rat	> 5000 mg/kg
Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9)	
LD50 oral rat	5170 mg/kg
LD50 dermal rabbit	> 3000 mg/kg
LC50 inhalation rat	> 12408 ppm/4h
ATE US (oral)	5170 mg/kg body weight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Aluminum oxide (Al2O3) (1344-28-1)	
NOAEL (animal/male, F0/P)	1000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure	: Not classified
Cyclohexane (110-82-7)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aluminum oxide (Al2O3) (1344-28-1)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.015 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: No data available
Cyclohexane (110-82-7)	
Viscosity, kinematic	1.161 mm²/s
Carbon dioxide (124-38-9)	
Vaporizer	Aerosol
Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9)	
Viscosity, kinematic	< 1 mm²/s Temp.: 'other:37.8°C' Parameter: 'kinematic viscosity (in mm²/s)'
Hydrocarbon	Yes
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Dry Lube

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Cyclohexane (110-82-7)	
LC50 - Fish [1]	4.53 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	0.9 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	23.03 – 42.07 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 72h - Algae [1]	3.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	9.317 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
Aluminum oxide (Al ₂ O ₃) (1344-28-1)	
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

Dry Lube-2022	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Dry Lube-2022	
Bioaccumulative potential	Not established.
Cyclohexane (110-82-7)	
Partition coefficient n-octanol/water	3.44
Carbon dioxide (124-38-9)	
BCF - Fish [1]	(no bioaccumulation)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

Dry Lube

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 13: Disposal considerations

13.1. Disposal methods

- Product/Packaging disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
- Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

DOT NA No : UN1950

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols flammable, (each not exceeding 1 L capacity)

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 2.1

Hazard labels (DOT) : 2.1



14.4. Packing group

Packing group (DOT) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

DOT

UN-No.(DOT) : UN1950

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Dry Lube

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Cyclohexane (110-82-7)

Subject to reporting requirements of United States SARA Section 313

CERCLA RQ	1000 lb
-----------	---------

Aluminum oxide (Al₂O₃) (1344-28-1)

Subject to reporting requirements of United States SARA Section 313

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Cyclohexane(110-82-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Carbon dioxide(124-38-9)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Aluminum oxide (Al ₂ O ₃)(1344-28-1)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

SECTION 16: Other information

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Issue date : 11/03/2016

Revision date : 06/09/2022

Full text of H-phrases	
Asp. Tox. 1	Aspiration hazard Category 1
Flam. Aerosol 2	Flammable aerosol Category 2
Press. Gas (Diss.)	Gases under pressure Dissolved gas

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.