PRODUCT NAME: FORMULA 815 MX

PRODUCT NUMBER: 111005

PAGE 1

MATERIAL SAFETY DATA SHEET

Per 29 CFR 1910.1200

DATE PREPARED: 11/16/95

SECTION I

BRULIN & COMPANY, INC.

P.O. BOX 270, INDIANAPOLIS, IN 46206-0270

(317) 923-3211

WEST COAST FACTORY

Richmond, California

SOUTHEASTERN FACTORY

Tampa, Florida

24 HOUR EMERGENCY NUMBER

CHEMTREC 1-800-424-9300

IDENTITY (As listed on label):

FORMULA 815 MX

HMIS HAZARD RATINGS: Flammability: 0

Health: 1

Reactivity: 0

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components

(Specific Chemical Identity: Common Name(s)

OSHA PEL

ACGIH TLV-TWA

3 РРМ

OTHER LIMITS

RECOMMENDED PERCENT

Ethanolamine, 2-Aminoethanol, Monoethanolamine

141-43-5

3 PPM

STEL 6 PPM

1-5

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:

212 F

Specific Gravity (H2O=1):

Vapor Pressure (mm Hg): Ethanolamine 0.2@68F

Melting Point:

Approx. 30 F

Vapor Density (Air=1):

Ethanolamine 2.1

CAS #

Evaporation Rate (water=1):

1.0

Solubility in Water:

Complete

Appearance and Odor:

Blue green liquid, citrus odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): None

Flammable Limits

LEL NA

UEL NA

Extinguishing Media: Not Applicable

Special Fire Fighting Procedures: Unusual Fire and Explosion Hazards: None None

PRODUCT NAME: FORMULA 815 MX

PRODUCT NUMBER: 111005

	1"	
DAGE	1	
PAGE	L .	

SECTION	V-REA	CTIVITY DATA	

Stability Unstable ___ Stable __X_

Conditions to Avoid: Freezing

Incompatibility (Materials to Avoid):

Strong oxidizers and acids.

Hazardous Decomposition or Byproducts:

Thermal decomposition can produce carbon monoxide,

carbon dioxide, nitrogen oxides.

Hazardous Polymerization: May Occur ___

_ May Not Occur _X_

Conditions to Avoid:

o Avoid: None

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry: Ir

Ingestion? No Skin? Yes Inhalation? Yes Eyes?

Health Hazards (Acute and Chronic):

Eye - Direct contact may cause irritation. Ingestion - May cause gastrointestinal irritation and irritation of mouth and throat. Skin - Prolonged or repeated contact may cause irritation. Inhalation - Excessive exposure

may cause respiratory irritation.

Carcinogenicity:

NTP?

No IARC Monographs? No

OSHA Regulated? No

Signs and Symptoms of Exposure:

Eye contact may cause irritation, seen as redness and swelling. Prolonged skin contact may cause irritation, seen as redness. Excessive inhalation of mists may be irritating and cause coughing and discomfort in the nose throat and chest. Ingestion may cause pain or discomfort in the mouth, throat, and

stomach.

Medical Conditions Generally Aggravated by Exposure: Ethanolamine may aggravate asthma and inflammatory or

fibrotic pulmonary disease. May also aggravate an existing

dermatitis

Emergency & First Aid Procedures:

Eye Contact: Flu

Flush with large amounts of water for at least 15 minutes lifting upper & lower lids

occasionally. Get medical attention.

Inhalation:

If affected, remove to fresh air.

Skin Contact: Ingestion:

Wash with mild soap and water. Remove contaminated clothing and launder before reuse. If conscious, dilute by giving at least two glasses of water. Call a physician or local poison

control center immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled:

Absorb on solid absorbent and shovel into

containers for disposal.

Waste Disposal Method:

Dispose of according to Federal, State and Local Laws and 40 CFR.

Precautions to be Taken in Handling and Storing:

Store between 40 and 120 F.

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type): Not normally required. Use NIOSH-MSHA approved respirator if TLV of

Ethanolamine is exceeded.

Ventilation: Mechanical (General): Normally Sufficient

Protective Gloves: Neoprene or butyl rubber on prolonged contact. Eye Protection: Goggles or safety glasses when handling conc.

Other Protective Clothing or Equipment:

None

Work/Hygienic Practices:

Avoid breathing spray mist.