S.C. Johnson Wax Racine, Wisconsin 53403-5011 Phone: (414) 631-2777 Emergency Phone: (800) 228-5635

Extension 092

International Emergency Phone: (612) 221-3999 Ext 092

4=Very High 3=High

2=Moderate

HAZARD RATING NFPA HMIS 1 Health 2 Flammability 1 2

1=Slight 0=Insignificant 0 Reactivity

MATERIAL SAFI SECTION I-PRODUCT		
PRODUCT NAME:		PRODUCT CODE: 11350-13
RAID WASP & HORNET KILLER X  CHEMICAL OR COMMON NAME: DATE ISSUED: SUPERSEDES: MS  NA 12/22/94 07/19/94 I	ods sections with char ${ m I}$	
SECTION II-INGRE	DIENT INFORMA	ATION
INGREDIENTS	WEIGHT %	EXPOSURE LIMIT
Petroleum Solvent (CAS# 64742-47-8)	65-75	200 PPM TLV-EXXON RECOMMENDED
Isopropanol (CAS# 67-63-0)	20-30	400 ppm OSHA/ACGIH TWA; 500 ppm OSHA/ACGIH STEL
Carbon Dioxide (CAS# 124-38-0)	1-5	5000 ppm OSHA PEL, ACGIH
Propoxur (CAS# 114-26-1)	under 0.5	0.5 MG/M3 ACGIH/OSHA TWA
Tetramethrin (CAS# 7696-12-0)	under 0.5	NOT ESTABLISHED
VAPOR PRESSURE (mm Hg): ND  SOLUBILITY IN WATER: Negligible  FREEZING POINT (°F): NA	PERCENT VOLATILE BY VOLUME (%): NA  VAPOR DENSITY (Air=1): ND  BOILING POINT (°F): ND	
ph: NA	EVAPORATION RATE (Butyl Acetate=1): NA	
pr: NA	EVALUATION AND COMPT INCOME.	
VOC (as packaged, minus H2O): ND	THEORETICAL VOC (lb/gal): ND	
SECTION IV-FIRE AND FLASH POINT (°F) (Method Used): 53 (TCC)	EXPLOSION IN	FORMATION
FLAMMABLE LIMITS: NA		
extinguishing media: Foam. CO2. Dry Chemica	l. Water Fog	•
SPECIAL FIREFIGHTING PROCEDURES: Normal fire fifire from maximum distance or protect self-contained breathing apparatus an unusual fire and explosion hazards: No special h	ed area. Fire	dures may be used. Fight e fighters should wear clothing.
SECTION V-HEA	LTH HAZARD D	ATA
PRIMARY ROUTE OF ENTRY: Skin contact.		

Page 2

S.C. Johnson Wax 1525 Howe Street Racine, Wisconsin

RAID WASP & HORNET KILLER X Product Number: 11350

Serial Number:

SECTION V-HEALTH HAZARD DATA (cont.)

SIGNS AND SYMPTOMS: Direct contact of product with eyes can cause irritation.

Prolonged or repeated contact of product with skin may cause irritation.

If taken internally, aspiration of liquid product can cause chemical

FIRST AID PROCEDURES: Flush eyes with water for 15-20 minutes. If irritation persists, seek medical aid. If product gets on skin, remove with soap and water. If product is swallowed, do not induce vomiting. Seek medical aid at once. Notes to physician: Atropine is antidotal and should be administered only after symptoms appear.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE:

53403

None known to S.C.

Johnson Wax

## SECTION VI-REACTIVITY DATA

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID:

None known

INCOMPATIBILITY: None known

HAZARDOUS DECOMPOSITION PRODUCTS:

When exposed to fire, produces normal products of

combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID:

None known

## SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wipe up spill with cloth and dispose of properly. Rinse affected area thoroughly with water.

WASTE DISPOSAL INFORMATION: Disposal of regulated quantities should be by incineration at a permitted facility in accordance with all Federal/State regulations and local ordinances regarding disposal of ignitable wastes. Recycle empty aerosol can to nearest steel recycling center. Use up package or give to someone who can.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: If ventilation is adequate, respiratory protection not required. VENTILATION: For outdoor use only. Do not use indoors or in poorly ventilated

If prolonged or repeated contact is possible: Any impervious PROTECTIVE GLOVES: material.

EYE PROTECTION: Chemical workers splash-proof goggles

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices. Where gross eye/skin contact may be a problem, wear/use appropriate protective equipment.

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONARY LABELING: CAUTION: Keep out of reach of children. Harmful if swallowed or absorbed through the skin. Avoid contact with skin, eyes or clothing. Eye contact with product stream may cause severe discomfort. If swallowed, call a physician or poison control center immediately. Gastric lavage is indicated if taken internally. Do not induce vomiting. See Section X.

MATERIAL SAFETY DATA SHEET

Page 3

S.C. Johnson Wax 1525 Howe Street Racine, Wisconsin

53403

RAID WASP & HORNET KILLER X Product Number: 11350 Serial Number:

SECTION IX-SPECIAL PRECAUTIONS (cont.)

Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Do not pressurize, cut, heat, weld or expose container to flame; explosion could occur. Wash thoroughly after handling. Keep out of reach of children.

SECTION X-ADDITIONAL INFORMATION

ADDITIONAL INFORMATION: NFPA 30B Level 3 Vomiting may cause aspiration pneumonia. Note to physician: If symptoms of cholinesterase inhibition are present, atropine sulfate is antidotal.

SECTION XI-TRANSPORTATION INFORMATION

DOT CLASS: ORM-D. DOT #: None Insecticides or insect repellents, NOI, other than poison. SHIPPING NAME: DOT NOTES:

NA-Not Applicable, NE-Not Established, NSR-No Special Requirement, ND-Not Determined The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use. R-106 (Rev 5 - 10/90)